

SET-UP SHEET

abb

NAME	John Ermen
CITY	St Willebrord
COUNTRY	The Netherlands
E-MAIL	john@jeracing.nl
COMMENT	no side plates, brass battery holder

RACE	1st Dutch National	DATE	5-4-2009
TRACK	Rucphen	RESULT	
SURFACE	<input type="checkbox"/> ASPHALT <input type="checkbox"/> OTHER SPECIFY	QUALIFYING POSITION	1
LAYOUT	<input type="checkbox"/> TECHNICAL <input type="checkbox"/> MIXED <input type="checkbox"/> FAST	QUALIFYING TIME	23/5:05.59
TRACTION	<input type="checkbox"/> LOW <input type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH	FINAL POSITION	9
TRACK TEMP	17	AIR TEMP	15

1ST	SPUR	2ND
<input type="checkbox"/> 47T <input type="checkbox"/> 48T <input checked="" type="checkbox"/> 49T	<input type="checkbox"/> 44T <input checked="" type="checkbox"/> 45T <input type="checkbox"/> 46T	
1ST	PINION	2ND
<input type="checkbox"/> 15T <input checked="" type="checkbox"/> 16T <input type="checkbox"/> 17T	<input type="checkbox"/> 18T <input checked="" type="checkbox"/> 19T <input type="checkbox"/> 20T	
DRIVE TRAIN		
MIDDLE AXLE PULLEY		<input type="checkbox"/> 24T <input checked="" type="checkbox"/> 25T

FRONT		REAR	
SHOCK ABSORBERS			
OIL/W		OIL/W	
45		45	
SPRING		SPRING	
Green		Red	

ANTI-ROLL BARS									
<input type="checkbox"/> 0°	<input type="checkbox"/> 30°	<input type="checkbox"/> 45°	<input type="checkbox"/> 60°	<input type="checkbox"/> 90°	<input type="checkbox"/> 0°	<input checked="" type="checkbox"/> 30°	<input type="checkbox"/> 45°	<input type="checkbox"/> 60°	<input type="checkbox"/> 90°

LEFT	RIGHT	TYRES	LEFT	RIGHT
ATS	ATS	MAKE	ATS	ATS
35 °	35 °	SHORE	35 °	35 °
67.5 mm	67.5 mm	DIAMETER	74 mm	74 mm
0.9 mm	1 mm	5-MIN WEAR	1 mm	1.5 mm

ENGINE		Novarossi	
VERSION	Flash	HEADSHIMS	0.7 mm
GLOWPLUG	7TGF	CARB DIA	8.5 mm

EXHAUST		2015	
FIXED HEADER	<input type="checkbox"/> long <input checked="" type="checkbox"/> med <input type="checkbox"/> short	CONICAL	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No

FUEL		Tornado	
NITRO	25 %		

BODY	Zytec	
WING		
TRIM TAB	2 mm	

FRONT	<input checked="" type="checkbox"/> APPLIED	REAR

DOWNSTOPS	SHIMS
1 mm	2 mm
1 mm	9 mm

CAMBER	WHEELBASE
L 1.5 ° R 2.0 °	L 2.5 ° R 3.0 °
10°	10°
6.5 mm	6.5 mm

TOE-IN(+) TOE OUT(-)	ACKERMANN
-1.5 °	3 mm
0mm <input type="checkbox"/> -1mm <input type="checkbox"/> -2mm <input checked="" type="checkbox"/> -3mm <input type="checkbox"/> -4mm <input type="checkbox"/>	ACKERMANN
WHEELBASE	3 mm

TRACK WIDTH
255 mm
264 mm