



SET UP

DIFFERENTIAL OIL

FRONT	CENTER	REAR
5000 CST	5000 CST	3000 CST

CLUTCH

TYPE: STANDARD ☒ OPTIONAL ☐

SHOE: ALU ☐ PCS SPRING

CARBON 4 PCS SPRING medium

GEARING

CLUTCH BELL 16 T SPUR GEAR 46 T

BRAKE BALANCERS

50/50	<input checked="" type="checkbox"/>	BALANCER CLIPS:	0.5 MM	<input type="checkbox"/> pcs
OPTION	<input type="checkbox"/>		0.75MM	<input type="checkbox"/> pcs
			1.0 MM	<input type="checkbox"/> pcs
			1.25MM	<input type="checkbox"/> pcs
			1.5 MM	<input type="checkbox"/> pcs

SHOCKS

FRONT	SPRING	REAR
C= 4.8 <input type="checkbox"/>	PINK	C= 2.8 <input checked="" type="checkbox"/>
C= 5.0 <input checked="" type="checkbox"/>	BLUE	C= 3.0 <input type="checkbox"/>
C= 5.2 <input type="checkbox"/>	PURPLE	C= 3.2 <input type="checkbox"/>
C= 5.4 <input type="checkbox"/>	GREEN	C= 3.4 <input type="checkbox"/>
C= 5.6 <input type="checkbox"/>	GREY	C= 3.6 <input type="checkbox"/>
C= 5.8 <input type="checkbox"/>	YELLOW	C= 3.8 <input type="checkbox"/>
C= 6.0 <input type="checkbox"/>	WHITE	C= 4.0 <input type="checkbox"/>
C= <input type="text"/>	OTHER	C= <input type="text"/>
450	OIL/CST	350
10	REBOUND %	10

PISTON

HOLES SIZE

<input type="checkbox"/>	1.1MM	<input type="checkbox"/>
<input type="checkbox"/>	1.2MM	<input checked="" type="checkbox"/>
<input checked="" type="checkbox"/>	1.3MM	<input type="checkbox"/>
<input type="checkbox"/>	1.4 MM	<input type="checkbox"/>
<input type="text"/>	OTHER	<input type="text"/>

TYRES

BRAND	Proline	BRAND	
TYPE	holeshot	TYPE	
INSERT	Proline	WING	OPTIONAL
WHEELS	Proline	STOCK	BRAND
			TYPE

ENGINE

TYPE	RB b10
MANIFOLD	
MUFFLER	2045
PLUG	RB 6
FUEL	RB fuel

COMMENTS

NAME Bacro.jonathan

RACE

coupe de france

DATE

TRACK Viglain

CITY/COUNTRY

France

CONTACT

TRACK SIZE ☐ OPEN ☐ MEDIUM ☐ TIGHT

TRACK TRACTION ☐ HIGH ☐ MEDIUM ☐ LOW

TRACK SURFACE ☐ SMOOTH ☐ MEDIUM ☐ BUMPY

TRACK TYPE ☐ HARD PACKED ☐ SOFT DIRT ☐ CLAY

☐ BLUE GROOVE ☐ ASTRO TURF ☐ GRASS

TRACK CONDITION ☐ DRY ☐ DUSTY ☐ MUD

TEMP. F° / °C

AIR TRACK

LAPS in LAP

BEST LAPTIME

RACE LENGTH

RACE RESULT

STEERING BLOCK ☒ PLASTIC ☐ ALU

CASTER BLOCK ☒ PLASTIC ☐ ALU

HEX ADAPTER ☐ -2MM ☐ -1MM ☒ 0MM

HEX ADAPTER ☐ -2MM ☐ -1MM ☒ 0MM

CASTER ☒ 10° ☐ 12°

SPINDLE ☐ HIGH ☐ LOW

BRACE ☒ PLASTIC ☐ ALU

BRACE ☒ PLASTIC ☐ ALU

INSERT NR. 2 ☒ UP ☐ DOWN

INSERT NR. 6 ☐ IN ☐ OUT

INSERT NR. 0 ☐ UP ☐ DOWN

INSERT NR. 0 ☐ UP ☐ DOWN

BRACE ☒ PLASTIC ☐ ALU

BRACE ☒ PLASTIC ☐ ALU

STANDARD BRACKET ☒ STANDARD BRACKET ☐ OPTIONAL TYPE

STANDARD BRACKET ☒ STANDARD BRACKET ☐ OPTIONAL TYPE

ANTI ROLLBAR ☐ 1.8MM ☐ 2.0MM ☐ 2.3MM ☒ 2.5MM ☐ 2.7MM

OUT (-) IN (+)

FRONT TOE - 0° + 0°

SERVO SAVER SPRING ☐ STANDARD ☒ HARD

STEERING BAR ☐ OPT 1 ☒ OPT 2 ☐ OPT 3

WHEELBASE SHIMS ☒ 1.25 ☐ 2.5 ☐ 3.75 ☐ 5MM

WING LOCATION IN MM

ANTI ROLLBAR ☐ 1.8MM ☐ 2.0MM ☒ 2.3MM ☐ 2.5MM ☐ 2.7MM

FRONT CAMBER + -1°

SHOCKLENGTH AT FULL DROOP MM

ADJUST SHOCKLENGTH WITH THIS SCREW

ADJUST RIDE HEIGHT WITH SPRING COLLAR

RIDE HEIGHT 24 MM

REAR CAMBER - 3° +

SHOCKLENGTH AT FULL DROOP MM

ADJUST SHOCKLENGTH WITH THIS SCREW

ADJUST RIDE HEIGHT WITH SPRING COLLAR

RIDE HEIGHT 26 MM