



# SET UP

NAME **R. LUIS**

TRACK

RACE

CITY/COUNTRY

DATE

CONTACT

TRACK SIZE ☐ OPEN ☒ MEDIUM ☐ TIGHT

TRACK TRACTION ☐ HIGH ☒ MEDIUM ☐ LOW

TRACK SURFACE ☒ SMOOTH ☐ MEDIUM ☐ BUMPY

TRACK TYPE ☒ HARD PACKED ☐ SOFT DIRT ☐ CLAY

☒ BLUE GROOVE ☐ ASTRO TURF ☐ GRASS

TRACK CONDITION ☐ DRY ☐ DUSTY ☐ MUD

TEMP. F° / °C **12**

AIR TRACK

LAPS

BEST LAP TIME in LAP

RACE LENGTH

RACE RESULT

## DIFFERENTIAL OIL

FRONT

CENTER

REAR

**6000** CST

**6000** CST

**3000** CST

## CLUTCH

TYPE: STANDARD ☒ OPTIONAL

SHOE: ALU **2** PCS

SPRING **1.0**

CARBON **2** PCS

SPRING **1.0**

## GEARING

CLUTCH BELL **46** T

SPUR GEAR **46** T

## BRAKE BALANCERS

50/50 ☒

BALANCER CLIPS: 0.5 MM

PCS

OPTION ☐

0.75MM

PCS

1.0 MM

PCS

1.25MM

PCS

1.5 MM

PCS

## SHOCKS

FRONT

SPRING

REAR

C= 4.8 ☐

PINK

C= 2.8 ☐

C= 5.0 ☐

BLUE

C= 3.0 ☐

C= 5.2 ☒

PURPLE

C= 3.2 ☒

C= 5.4 ☐

GREEN

C= 3.4 ☐

C= 5.6 ☐

GREY

C= 3.6 ☐

C= 5.8 ☐

YELLOW

C= 3.8 ☐

C= 6.0 ☐

WHITE

C= 4.0 ☐

C= ☐

OTHER

C= ☐

**400**

OIL/CST **300**

**30**

REBOUND % **30**

## PISTON

HOLES SIZE

☐ 1.1MM

☐ 1.2MM

☒ 1.3MM ☒

☐ 1.4 MM

OTHER

## TYRES

## BODY

BRAND **TC**

BRAND **TC**

TYPE

TYPE

INSERT **TC**

WING

OPTIONAL

WHEELS **TC**

STOCK

BRAND **TC**

TYPE **NEW**

## ENGINE

TYPE **0.5**

MANIFOLD **HA**

MUFFLER **2042**

PLUG **P3**

FUEL **XCEED**

## COMMENTS

MEDIAS CAMBER COM  
BRAÇOS PARALELOS  
AO CHÃO EM CIMA DE  
MESA PISTA XCEED.

## STEERING BLOCK

☒ PLASTIC

☐ ALU

## CASTER BLOCK

☒ PLASTIC

☐ ALU

HEX ADAPTER ☐ -2MM ☐ -1MM ☒ 0MM

HEX ADAPTER ☐ -2MM ☐ -1MM ☒ 0MM

## CASTER

☒ 10°

☐ 12°

## SPINDLE

☒ HIGH

☐ LOW

## BRACE

☐ PLASTIC

☒ ALU

INSERT NR. **5**

☒ UP

☐ DOWN

INSERT NR. **6**

☐ IN

☐ OUT

☒ STANDARD BRACKET

☐ OPTIONAL TYPE

☒ STANDARD BRACKET

☐ OPTIONAL TYPE

## ANTI ROLLBAR

☐ 1.8MM

☐ 2.0MM

☒ 2.3MM

☐ 2.5MM

☐ 2.7MM

## STEERING BAR

☐ OPT 1

☐ OPT 2

☒ OPT 3 **STOCK**

## FRONT CAMBER

☐ + ☐ 0 ☒ -1

SHOCKLENGTH  
AT FULL DROOP

MM **STOCK**

ADJUST  
SHOCKLENGTH  
WITH THIS SCREW

ADJUST RIDE HEIGHT WITH  
SPRING COLLAR

RIDE HEIGHT **27.5** MM

## WHEELBASE SHIMS

☒ 1.25

☐ 2.5

☐ 3.75

☐ 5MM

## ANTI ROLLBAR

☐ 1.8MM

☐ 2.0MM

☐ 2.3MM

☒ 2.5MM

☐ 2.7MM

## REAR CAMBER

☐ + ☐ 0 ☒ -2.5

SHOCKLENGTH  
AT FULL DROOP

MM **STOCK**

ADJUST  
SHOCKLENGTH  
WITH THIS SCREW

ADJUST RIDE HEIGHT WITH  
SPRING COLLAR

RIDE HEIGHT **29** MM