

SET UP



NAME Mikael F		RACE SSIC Alvesta	DATE 2011-01-22	SURFACE
FRONT SPRING 18 / 0.45 ☒ 22 / 0.50 ☐ 26 / 0.55 ☐		CAMBER L 2 ° R 2 °		FRONT TIRES Brand Parma Magenta Hardness _____ Diameter _____ Additive _____ Additive time 5-10 min Treated surface I/3
FRONT SUSPENSION BRACKET 0 ☐ 3 ☐ 6 ☐ 9 ☒		TOE L 0 ° R 0 °		
RIDE HEIGHT SPACER 0.5 ☐ 1.0 ☐ 2.0 ☐		RIDE HEIGHT FRONT 4 mm		
SUSPENSION INSERT Narrow ☐ Mid ☐ Wide ☒		TRACK WIDTH 116,8 mm		REAR TIRES Brand Parma Grå Hardness _____ Diameter _____ Additive _____ Additive time 40 min innan Treated surface _____
CASTER SPACERS All in front ☐ Medium ☒ All in back ☐		UPPER ARM INSERTS Inside ☐ Outside ☒		
CENTER SPRING 10 ☐ 16 ☐ 12 ☒ 18 ☐ 14 ☐		SPUR GEAR Pitch _____ Teeth _____		
SHOCK OIL PISTON 800 CST		SCHOCKTOWER CENTER 		PINION GEAR Pitch _____ Teeth _____
SIDE SPRING 4.5 ☐ 6.0 ☐ 5.0 ☒ 6.5 ☐ 5.5 ☐ 7.0 ☐		RIDE HEIGHT REAR 4 mm		
SHOCK OIL PISTON 2000		POD DROOP 0 mm		
AXLE INSERT 0 ☐ 2.5 ☐ 0.5 ☐ 3 ☐ 1.0 ☐ 3.5 ☐ 1.5 ☐ 4 ☐ 2 ☐		BATTERY Brand _____ Type/Cap. _____		MOTOR Brand Stock Turns _____ Timing _____
BODY Brand / Type _____ / XCEED		BATTERY POSITION Front ☐ Rear ☒		
REMARKS 170 mm bredd bak 85% styrutslag, -30% styrexp.		ESC Brand Advanced Type _____ Setting _____		