



SET UP

NAME R.Luis		RACE 1		DATE	
TRACK Modelis		CITY/COUNTRY Leiria		CONTACT	
TRACK SIZE	<input checked="" type="checkbox"/> OPEN	<input type="checkbox"/> MEDIUM	<input type="checkbox"/> TIGHT	TEMP: F° / °C	
TRACK TRACTION	<input checked="" type="checkbox"/> HIGH	<input type="checkbox"/> MEDIUM	<input type="checkbox"/> LOW	AIR 22 °C TRACK	
TRACK SURFACE	<input type="checkbox"/> SMOOTH	<input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> BUMPY	LAPS	
TRACK TYPE	<input type="checkbox"/> HARD PACKED	<input checked="" type="checkbox"/> SOFT DIRT	<input type="checkbox"/> CLAY	BEST LAPTIME 29.903 in LAP	
	<input type="checkbox"/> BLUE GROOVE	<input type="checkbox"/> ASTRO TURF	<input type="checkbox"/> GRASS	RACE LENGTH 35 Min	
TRACK CONDITION	<input type="checkbox"/> DRY	<input type="checkbox"/> DUSTY	<input type="checkbox"/> MUD	RACE RESULT 1st	

DIFFERENTIAL OIL		
FRONT	CENTER	REAR
5000 CST	4000 CST	3000 CST

CLUTCH	
TYPE: STANDARD <input checked="" type="checkbox"/>	OPTIONAL <input type="checkbox"/>
SHOE: ALU 2 PCS	SPRING X-Hard
CARBON 2 PCS	SPRING Hard

GEARING	
CLUTCH BELL 16 T	SPUR GEAR 46 T

BRAKE BALANCERS	
50/50 <input checked="" type="checkbox"/>	BALANCER CLIPS: 0.5 MM
OPTION <input type="checkbox"/>	0.75MM
	1.0 MM
	1.25MM
	1.5 MM

SHOCKS		
FRONT	SPRING	REAR
C= 4.8 <input type="checkbox"/>	PINK	C= 2.8 <input checked="" type="checkbox"/>
C= 5.0 <input checked="" type="checkbox"/>	BLUE	C= 3.0 <input type="checkbox"/>
C= 5.2 <input type="checkbox"/>	PURPLE	C= 3.2 <input type="checkbox"/>
C= 5.4 <input type="checkbox"/>	GREEN	C= 3.4 <input type="checkbox"/>
C= 5.6 <input type="checkbox"/>	GREY	C= 3.6 <input type="checkbox"/>
C= 5.8 <input type="checkbox"/>	YELLOW	C= 3.8 <input type="checkbox"/>
C= 6.0 <input type="checkbox"/>	WHITE	C= 4.0 <input type="checkbox"/>
C= <input type="checkbox"/>	OTHER	C= <input type="checkbox"/>
400	OIL/CST	400
30	REBOUND %	30

PISTON	
HOLE SIZE	
<input type="checkbox"/> 1.1MM	<input type="checkbox"/>
<input type="checkbox"/> 1.2MM	<input type="checkbox"/>
<input type="checkbox"/> 1.3MM	<input type="checkbox"/>
<input type="checkbox"/> 1.4 MM	<input type="checkbox"/>
OTHER	
8x1.2mm	8x1.3mm

TYRES		BODY	
BRAND AKA	BRAND	TYPE Crossbrace	TYPE SS
INSERT Black	WING	OPTIONAL	
WHEELS AKA	STOCK <input checked="" type="checkbox"/>	BRAND	TYPE

ENGINE	
TYPE	O.S VZ-B Speed
MANIFOLD	HN
MUFFLER	O.S
PLUG	P3
FUEL	Runner Time 25%

COMMENTS	
<p>Track Bumpy during the final.</p> <p>Rear Shock Position placed Inner hole on rear arm worked perfect in bumps</p> <p>During Smooth Track, outer hole in rear arm and 2 holes out in shock tower.</p> <p>Try steel flywheel next time.</p>	

STEERING BLOCK	CASTER BLOCK
<input checked="" type="checkbox"/> PLASTIC	<input checked="" type="checkbox"/> PLASTIC
<input type="checkbox"/> ALU	<input type="checkbox"/> ALU

HEX ADAPTER	<input type="checkbox"/> -2MM	<input type="checkbox"/> -1MM	<input checked="" type="checkbox"/> 0MM
-------------	-------------------------------	-------------------------------	---

CASTER	<input checked="" type="checkbox"/> 10°	<input type="checkbox"/> 12°
SPINDLE	<input type="checkbox"/> HIGH	<input checked="" type="checkbox"/> LOW
BRACE	<input type="checkbox"/> PLASTIC	<input checked="" type="checkbox"/> ALU
BRACE	<input type="checkbox"/> PLASTIC	<input checked="" type="checkbox"/> ALU
INSERT NR. 2	<input checked="" type="checkbox"/> UP	<input type="checkbox"/> DOWN
INSERT NR. 2	<input type="checkbox"/> UP	<input checked="" type="checkbox"/> DOWN
ANTI ROLLBAR	<input type="checkbox"/> 1.8MM	<input type="checkbox"/> 2.0MM
	<input checked="" type="checkbox"/> 2.3MM	<input type="checkbox"/> 2.5MM
	<input type="checkbox"/> 2.7MM	
SERVO SAVER SPRING	<input type="checkbox"/> STANDARD	<input checked="" type="checkbox"/> HARD
STEERING BAR	<input type="checkbox"/> OPT 1	<input checked="" type="checkbox"/> OPT 2
	<input type="checkbox"/> OPT 3	

FRONT CAMBER	<input type="checkbox"/> +	<input type="checkbox"/> -	<input type="checkbox"/> 1°
SHOCKLENGTH AT FULL DROOP	MM		
ADJUST SHOCKLENGTH WITH THIS SCREW			
ADJUST RIDE HEIGHT WITH SPRING COLLAR			
RIDE HEIGHT	28 MM		

UPRIGHT	<input checked="" type="checkbox"/> PLASTIC	<input type="checkbox"/> ALU
HEX ADAPTER	<input type="checkbox"/> -2MM	<input type="checkbox"/> -1MM
	<input checked="" type="checkbox"/> 0MM	

BRACE	<input type="checkbox"/> PLASTIC	<input checked="" type="checkbox"/> ALU
BRACE	<input type="checkbox"/> PLASTIC	<input checked="" type="checkbox"/> ALU
INSERT NR. 5	<input type="checkbox"/> UP	<input checked="" type="checkbox"/> DOWN
INSERT NR. 5	<input type="checkbox"/> IN	<input checked="" type="checkbox"/> OUT
STANDARD BRACKET	<input type="checkbox"/> STANDARD BRACKET	<input checked="" type="checkbox"/> OPTIONAL TYPE
OPTIONAL TYPE		

WHEELBASE SHIMS	<input type="checkbox"/> 1.25	<input type="checkbox"/> 2.5	<input type="checkbox"/> 3.75	<input checked="" type="checkbox"/> 5MM
ANTI ROLLBAR	<input type="checkbox"/> 1.8MM	<input type="checkbox"/> 2.0MM	<input type="checkbox"/> 2.3MM	<input checked="" type="checkbox"/> 2.5MM
	<input type="checkbox"/> 2.7MM			
WING LOCATION IN MM				

REAR CAMBER	<input type="checkbox"/> -	<input type="checkbox"/> +	<input type="checkbox"/> 2°
SHOCKLENGTH AT FULL DROOP	MM		
ADJUST SHOCKLENGTH WITH THIS SCREW			
ADJUST RIDE HEIGHT WITH SPRING COLLAR			
RIDE HEIGHT	29 MM		