



SET UP

NAME Alberto Garcia

RACE

2

DATE

April 2011

TRACK

1.5

CITY/COUNTRY

Spain

CONTACT

procar.rc@gmail.com

TRACK SIZE

☐ OPEN

☒ MEDIUM

☐ TIGHT

TRACK TRACTION

☐ HIGH

☒ MEDIUM

☐ LOW

TRACK SURFACE

☒ SMOOTH

☐ MEDIUM

☐ BUMPY

TRACK TYPE

☒ HARD PACKED

☐ SOFT DIRT

☐ CLAY

TRACK CONDITION

☐ BLUE GROOVE

☐ ASTRO TURF

☐ GRASS

☒ DRY

☐ DUSTY

☐ MUD

TEMP. F° / °C

AIR 20°C TRACK 11°C

LAPS 72v

BEST LAPTIME

35.1 in LAP -

RACE LENGTH

45:03

RACE RESULT

TQ + Win

DIFFERENTIAL OIL

FRONT

CENTER

REAR

5.000 CST

5.000 CST

3.000 CST

CLUTCH

TYPE: STANDARD ☒ OPTIONAL ☐

SHOE: ALU 2 PCS

SPRING 1

CARBON 2 PCS

SPRING 0.9

GEARING

CLUTCH BELL 16 T

SPUR GEAR 46 T

BRAKE BALANCERS

50/50 ☒

BALANCER CLIPS: 0.5 MM

pcs

OPTION ☐

0.75MM pcs

1.0 MM pcs

1.25MM pcs

1.5 MM pcs

SHOCKS

FRONT

SPRING

REAR

C= 4.8 ☒

PINK

C= 2.8 ☐

C= 5.0 ☐

BLUE

C= 3.0 ☐

C= 5.2 ☐

PURPLE

C= 3.2 ☒

C= 5.4 ☐

GREEN

C= 3.4 ☐

C= 5.6 ☐

GREY

C= 3.6 ☐

C= 5.8 ☐

YELLOW

C= 3.8 ☐

C= 6.0 ☐

WHITE

C= 4.0 ☐

C= ☐

OTHER

C= ☐

40

OIL/CST

30

25

REBOUND %

25

PISTON

HOLES SIZE

☐ 1.1MM

☐ 1.2MM

☒ 1.3MM

☐ 1.4 MM

OTHER

TYRES

BODY

BRAND PROLINE

BRAND SERPENT

TYPE SNIPER M2

TYPE

INSERT STD

WING

OPTIONAL

WHEELS V2

STOCK ☒

BRAND

TYPE

ENGINE

TYPE REDS XR21T

MANIFOLD REDS

MUFFLER REDS 2021

PLUG REDS T6

FUEL MECCAFUEL 25%

COMMENTS

STEERING BLOCK

☒ PLASTIC

☐ ALU

CASTER BLOCK

☒ PLASTIC

☐ ALU

HEX ADAPTER ☒ -2MM

☐ -1MM

☐ 0MM

HEX ADAPTER ☐ -2MM

☐ -1MM

☒ 0MM

CASTER

☐ 10°

☒ 12°

SPINDLE

☒ HIGH

☐ LOW

BRACE

☐ PLASTIC

☒ ALU

INSERT NR. 0

☐ UP

☒ DOWN

INSERT NR. 3

☒ UP

☐ DOWN

BRACE

☐ PLASTIC

☒ ALU

ANTI ROLLBAR

☐ 1.8MM

☐ 2.0MM

☒ 2.3MM

☐ 2.5MM

☐ 2.7MM

OUT (-)

IN (+)

-

+ 1.5°

FRONT TOE

SERVO SAVER SPRING

☐ STANDARD

☒ HARD

STEERING BAR

☐ OPT 1

☐ OPT 2

☐ OPT 3

WHEELBASE SHIMS

☐ 1.25

☒ 2.5

☐ 3.75

☐ 5MM

ANTI ROLLBAR

☐ 1.8MM

☐ 2.0MM

☐ 2.3MM

☒ 2.5MM

☐ 2.7MM

FRONT CAMBER

+ - 2°

SHOCKLENGTH AT FULL DROOP

MM

ADJUST SHOCKLENGTH WITH THIS SCREW

ADJUST RIDE HEIGHT WITH SPRING COLLAR

RIDE HEIGHT 25 MM

REAR CAMBER

- 3° +

SHOCKLENGTH AT FULL DROOP

MM

ADJUST SHOCKLENGTH WITH THIS SCREW

ADJUST RIDE HEIGHT WITH SPRING COLLAR

RIDE HEIGHT 26 MM