

SET UP

733

NAME 733		RACE test EC 2011		DATE	
-----------------	--	--------------------------	--	-------------	--

TRACK Ettlingen					
FRONT		REAR		REAR	

1 ST		SPUR		2ND	
<input type="checkbox"/> 61	<input checked="" type="checkbox"/> 60	<input type="checkbox"/> 59	<input checked="" type="checkbox"/> 54	<input type="checkbox"/> 55	<input type="checkbox"/> 56

1 ST		PINION		2ND	
<input type="checkbox"/> 16	<input checked="" type="checkbox"/> 17	<input type="checkbox"/> 18	<input type="checkbox"/> 21	<input checked="" type="checkbox"/> 22	<input type="checkbox"/> 23

FRONT		DRIVETRAIN		REAR	
GEAR DIFF <input type="checkbox"/> CST <input type="checkbox"/> ONE WAY <input checked="" type="checkbox"/> SPOOL		GEAR DIFF <input checked="" type="checkbox"/> 60000 CST <input type="checkbox"/> SOLID			

FRONT		SHOCK ABSORBERS		REAR	
OIL/CST				OIL/CST	
1000				1000	
SPRING				SPRING	
blue				pink	

ANTI-ROLL BARS					
FRONT			REAR		
<input type="checkbox"/> 1.8	<input checked="" type="checkbox"/> 2.2	<input type="checkbox"/> 2.5	<input type="checkbox"/> 2.3	<input checked="" type="checkbox"/> 2.5	

FRONT		REAR	
LEFT	RIGHT	LEFT	RIGHT
32 °	35 °	37 °	40 °
mm	mm	mm	mm
DIAMETER		DIAMETER	
5-MIN WEAR		5-MIN WEAR	

ENGINE Xceed ZX 12 DS4-EM			
TYPE		HEADSHIMS	std mm
GLOWPLUG	Xceed 7	CARB DIA'	std mm

EXHAUST picco 2607			
FIXED HEADER	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
	LONG	MED	SHORT
	YES	NO	NO

FUEL Xceed NITRO 16 %	
------------------------------	--

BODY	
BODY-TYPE	Blitz Audi RS4
POSITION	WING

REMARKS
 Diff with 1 axle = 2 small gears. Rear anti rollbar grinded to 1.5mm in between collars. "0" Steeringblocks. Ride height with set-up wheels. Hard Plastics. Standard rear lower arm mounts. Body 2mm more forward. Wing level with mounts. side stiffener with balljoints

STIFFNERS	
FRONT BRACKET SCREWS <input type="checkbox"/> YES <input type="checkbox"/> NO	
REAR BRACKET SCREWS <input type="checkbox"/> YES <input type="checkbox"/> NO	

TRACK WIDTH	
FRONT	BACK
199 mm	199.5 mm

CAMBER	
L -1.5 ° R -1.5 °	L -2.5 ° R -3.5 °

TOE IN (+) TOE OUT (-)	
-1.0 °	1.0 °

CASTER	
4 mm	

ACKERMANN	
<input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2	

WHEEL BASE	
<input checked="" type="checkbox"/> 0mm <input type="checkbox"/> -1mm <input type="checkbox"/> -2mm	