



SET UP

NAME	jeremy whiting	RACE	midwest nitro round #5	DATE	8-20-2011
TRACK	moline ill.	CITY/COUNTRY	usa	CONTACT	
TRACK SIZE	<input type="checkbox"/> OPEN	<input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> TIGHT	TEMP: F° / °C	
TRACK TRACTION	<input checked="" type="checkbox"/> HIGH	<input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> LOW	AIR	TRACK
TRACK SURFACE	<input type="checkbox"/> SMOOTH	<input checked="" type="checkbox"/> MEDIUM	<input checked="" type="checkbox"/> BUMPY	LAPS	
TRACK TYPE	<input checked="" type="checkbox"/> HARD PACKED	<input checked="" type="checkbox"/> SOFT DIRT	<input type="checkbox"/> CLAY	BEST LAP TIME	in LAP
	<input checked="" type="checkbox"/> BLUE GROOVE	<input type="checkbox"/> ASTRO TURF	<input type="checkbox"/> GRASS	RACE LENGTH	
TRACK CONDITION	<input checked="" type="checkbox"/> DRY	<input checked="" type="checkbox"/> DUSTY	<input type="checkbox"/> MUD	RACE RESULT	

DIFFERENTIAL OIL		
FRONT	CENTER	REAR
4000 CST	4000 CST	2000 CST

CLUTCH	
TYPE: STANDARD <input checked="" type="checkbox"/>	OPTIONAL buku komposite
SHOE: ALU <input type="checkbox"/> PCS	SPRING adjust
CARBON <input type="checkbox"/> PCS	SPRING

GEARING	
CLUTCH BELL 16 T	SPUR GEAR 46 T

BRAKE BALANCERS	
50/50 <input checked="" type="checkbox"/>	BALANCER CLIPS: 0.5 MM pcs
OPTION <input type="checkbox"/>	0.75MM pcs
	1.0 MM pcs
	1.25MM pcs
	1.5 MM pcs

SHOCKS		
FRONT	SPRING	REAR
C= 4.8 <input type="checkbox"/>	PINK	C= 2.8 <input type="checkbox"/>
C= 5.0 <input type="checkbox"/>	BLUE	C= 3.0 <input type="checkbox"/>
C= 5.2 <input type="checkbox"/>	PURPLE	C= 3.2 <input type="checkbox"/>
C= 5.4 <input type="checkbox"/>	GREEN	C= 3.4 <input type="checkbox"/>
C= 5.6 <input type="checkbox"/>	GREY	C= 3.6 <input type="checkbox"/>
C= 5.8 <input type="checkbox"/>	YELLOW	C= 3.8 <input type="checkbox"/>
C= 6.0 <input type="checkbox"/>	WHITE	C= 4.0 <input checked="" type="checkbox"/>
C= <input checked="" type="checkbox"/>	OTHER	C= <input type="checkbox"/>
40	OIL/CST	32.5
25	REBOUND %	25

PISTON	
HOLE SIZE	
1.1MM <input type="checkbox"/>	
1.2MM <input type="checkbox"/>	
1.3MM <input checked="" type="checkbox"/>	
1.4 MM <input type="checkbox"/>	
8 hole tapered pistons	8 hole tapered pistons

TYRES	
BRAND aka	BRAND stock
TYPE i-beams	TYPE
INSERT black	WING OPTIONAL
WHEELS vp-pro	STOCK <input checked="" type="checkbox"/> BRAND
	TYPE

ENGINE	
TYPE green alpha	
MANIFOLD alpha	
MUFFLER alpha 0801	
PLUG 99t od	
FUEL high rev s&w	

COMMENTS
red serpent front springs try 2.5 rear sway bar to stop over-rotation try #2 ackerman plate to ease steering one piece motor mount rear bracket.. 600276 low roll center

STEERING BLOCK	CASTER BLOCK
<input checked="" type="checkbox"/> PLASTIC	<input checked="" type="checkbox"/> PLASTIC
<input type="checkbox"/> ALU	<input type="checkbox"/> ALU

HEX ADAPTER ☐ -2MM ☐ -1MM ☒ 0MM

UPRIGHT
<input checked="" type="checkbox"/> PLASTIC
<input type="checkbox"/> ALU

HEX ADAPTER ☐ -2MM ☐ -1MM ☒ 0MM

CASTER	SPINDLE
<input type="checkbox"/> 10°	<input type="checkbox"/> HIGH
<input checked="" type="checkbox"/> 12°	<input checked="" type="checkbox"/> LOW

INSERT NR. 6 ☐ UP ☐ DOWN

BRACE
<input type="checkbox"/> PLASTIC
<input checked="" type="checkbox"/> ALU

INSERT NR. 6 ☐ UP ☐ DOWN

ANTI ROLLBAR	SERVO SAVER SPRING
<input type="checkbox"/> 1.8MM	<input type="checkbox"/> STANDARD
<input type="checkbox"/> 2.0MM	<input checked="" type="checkbox"/> HARD
<input type="checkbox"/> 2.3MM	
<input checked="" type="checkbox"/> 2.5MM	
<input type="checkbox"/> 2.7MM	

STEERING BAR ☐ OPT 1 ☐ OPT 2 ☒ OPT 3

WHEELBASE SHIMS	WING LOCATION
<input checked="" type="checkbox"/> 1.25	IN MM stock
<input type="checkbox"/> 2.5	
<input type="checkbox"/> 3.75	
<input type="checkbox"/> 5MM	

ANTI ROLLBAR ☐ 1.8MM ☐ 2.0MM ☒ 2.3MM ☐ 2.5MM ☐ 2.7MM

FRONT CAMBER
+ - 2°
SHOCKLENGTH AT FULL DROOP 97.5 MM
ADJUST SHOCKLENGTH WITH THIS SCREW
ADJUST RIDE HEIGHT WITH SPRING COLLAR
RIDE HEIGHT 28 MM

REAR CAMBER
- 2° +
SHOCKLENGTH AT FULL DROOP 113 MM
ADJUST SHOCKLENGTH WITH THIS SCREW
ADJUST RIDE HEIGHT WITH SPRING COLLAR
RIDE HEIGHT 28 MM