



SET UP

DIFFERENTIAL OIL

FRONT	CENTER	REAR
CST	CST	CST

CLUTCH

TYPE: STANDARD	☐	OPTIONAL	☐
SHOE: ALU	☐	PCS	☐
	☐	SPRING	☐
CARBON	☐	PCS	☐
	☐	SPRING	☐

GEARING

CLUTCH BELL	☐	T	SPUR GEAR	☐	T
-------------	--------------------------	---	-----------	--------------------------	---

BRAKE BALANCERS

50/50	☐	BALANCER CLIPS:	0.5 MM	pcs
OPTION	☐		0.75MM	pcs
			1.0 MM	pcs
			1.25MM	pcs
			1.5 MM	pcs

SHOCKS

FRONT	SPRING	REAR		
C= 4.8	☐	PINK	C= 2.8	☐
C= 5.0	☐	BLUE	C= 3.0	☐
C= 5.2	☐	PURPLE	C= 3.2	☐
C= 5.4	☐	GREEN	C= 3.4	☐
C= 5.6	☐	GREY	C= 3.6	☐
C= 5.8	☐	YELLOW	C= 3.8	☐
C= 6.0	☐	WHITE	C= 4.0	☐
C=	☐	OTHER	C=	☐
	☐	OIL/CST	☐	
	☐	REBOUND %	☐	

PISTON

HOLES SIZE		
☐	1.1MM	☐
☐	1.2MM	☐
☐	1.3MM	☐
☐	1.4 MM	☐
☐	OTHER	☐

TYRES

BRAND	BRAND		
TYPE	TYPE		
INSERT	WING	OPTIONAL	
WHEELS	STOCK	BRAND	TYPE

ENGINE

TYPE
MANIFOLD
MUFFLER
PLUG
FUEL

COMMENTS

--

NAME	RACE	DATE	
TRACK	CITY/COUNTRY	CONTACT	
TRACK SIZE	☐ OPEN	☐ MEDIUM	☐ TIGHT
TRACK TRACTION	☐ HIGH	☐ MEDIUM	☐ LOW
TRACK SURFACE	☐ SMOOTH	☐ MEDIUM	☐ BUMPY
TRACK TYPE	☐ HARD PACKED	☐ SOFT DIRT	☐ CLAY
	☐ BLUE GROOVE	☐ ASTRO TURF	☐ GRASS
TRACK CONDITION	☐ DRY	☐ DUSTY	☐ MUD
TEMP. F ° / ° C			
AIR TRACK			
LAPS			
BEST LAP TIME in LAP			
RACE LENGTH			
RACE RESULT			

STEERING BLOCK ☐ PLASTIC ☐ ALU	CASTER BLOCK ☐ PLASTIC ☐ ALU	UPRIGHT ☐ PLASTIC ☐ ALU
		HEX ADAPTER ☐ -2MM ☐ -1MM ☐ 0MM

CASTER ☐ 10° ☐ 12°	SPINDLE ☐ HIGH ☐ LOW	BRACE ☐ PLASTIC ☐ ALU
		BRACE ☐ PLASTIC ☐ ALU
INSERT NR. ☐ UP ☐ DOWN		INSERT NR. ☐ IN ☐ OUT
STANDARD BRACKET ☐ OPTIONAL TYPE ☐		STANDARD BRACKET ☐ OPTIONAL TYPE ☐

ANTI ROLLBAR ☐ 1.8MM ☐ 2.0MM ☐ 2.3MM ☐ 2.5MM ☐ 2.7MM	WHEELBASE SHIMS ☐ 1.25 ☐ 2.5 ☐ 3.75 ☐ 5MM	WING LOCATION IN MM
SERVO SAVER SPRING ☐ STANDARD ☐ HARD		ANTI ROLLBAR ☐ 1.8MM ☐ 2.0MM ☐ 2.3MM ☐ 2.5MM ☐ 2.7MM
STEERING BAR ☐ OPT 1 ☐ OPT 2 ☐ OPT 3		

FRONT CAMBER ☐ + ☐ 0 ☐ -	REAR CAMBER ☐ - ☐ 0 ☐ +
SHOCKLENGTH AT FULL DROOP MM	
ADJUST SHOCKLENGTH WITH THIS SCREW	
ADJUST RIDE HEIGHT WITH SPRING COLLAR	
RIDE HEIGHT MM	