



# SET UP

## DIFFERENTIAL OIL

FRONT	CENTER	REAR
5000 CST	5000 CST	3000 CST

## CLUTCH

TYPE: STANDARD ☒ OPTIONAL ☐

SHOE: ALU ☐ PCS SPRING ☐

CARBON ☒ 4 PCS SPRING ☐ Std

## GEARING

CLUTCH BELL ☐ 16 T SPUR GEAR ☐ 46 T

## BRAKE BALANCERS

50/50 ☒ BALANCER CLIPS: 0.5 MM ☐ pcs

OPTION ☐ 0.75MM ☐ pcs

1.0 MM ☐ pcs

1.25MM ☐ pcs

1.5 MM ☐ pcs

## SHOCKS

FRONT	SPRING	REAR
C= 4.8 <input type="checkbox"/>	PINK	C= 2.8 <input type="checkbox"/>
C= 5.0 <input checked="" type="checkbox"/>	BLUE	C= 3.0 <input type="checkbox"/>
C= 5.2 <input type="checkbox"/>	PURPLE	C= 3.2 <input type="checkbox"/>
C= 5.4 <input type="checkbox"/>	GREEN	C= 3.4 <input checked="" type="checkbox"/>
C= 5.6 <input type="checkbox"/>	GREY	C= 3.6 <input type="checkbox"/>
C= 5.8 <input type="checkbox"/>	YELLOW	C= 3.8 <input type="checkbox"/>
C= 6.0 <input type="checkbox"/>	WHITE	C= 4.0 <input type="checkbox"/>
C= <input type="checkbox"/>	OTHER	C= <input type="checkbox"/>
40	OIL/CST	35
50	REBOUND %	50

## PISTON

HOLES SIZE

☐ 1.1MM ☐

☐ 1.2MM ☐

☐ 1.3MM ☐

☒ 1.4 MM ☒

OTHER ☐

## TYRES

BRAND Aka

TYPE Crossbrace

INSERT SS

WHEELS Aka

## BODY

BRAND Serpent

TYPE

WING

OPTIONAL

STOCK ☒ BRAND

TYPE

## ENGINE

TYPE Alpha f830

MANIFOLD Standard

MUFFLER Alpha 2090 with 8 mm stinger

PLUG Os P3

FUEL Merlin Pro racing 25% Evo 2

## COMMENTS

NAME	Key Koops	RACE	Buggycup	DATE	15 July
TRACK	Appingedam	CITY/COUNTRY	Appingedam	CONTACT	
TRACK SIZE	<input type="checkbox"/> OPEN	<input type="checkbox"/> MEDIUM	<input type="checkbox"/> TIGHT	TEMP. F ° / ° C	
TRACK TRACTION	<input type="checkbox"/> HIGH	<input type="checkbox"/> MEDIUM	<input type="checkbox"/> LOW	AIR	TRACK
TRACK SURFACE	<input type="checkbox"/> SMOOTH	<input type="checkbox"/> MEDIUM	<input type="checkbox"/> BUMPY	LAPS	
TRACK TYPE	<input type="checkbox"/> HARD PACKED	<input type="checkbox"/> SOFT DIRT	<input type="checkbox"/> CLAY	BEST LAPTIME	in LAP
	<input type="checkbox"/> BLUE GROOVE	<input type="checkbox"/> ASTRO TURF	<input type="checkbox"/> GRASS	RACE LENGTH	
TRACK CONDITION	<input type="checkbox"/> DRY	<input type="checkbox"/> DUSTY	<input type="checkbox"/> MUD	RACE RESULT	

STEERING BLOCK <input checked="" type="checkbox"/> PLASTIC <input type="checkbox"/> ALU	CASTER BLOCK <input checked="" type="checkbox"/> PLASTIC <input type="checkbox"/> ALU	UPRIGHT <input checked="" type="checkbox"/> PLASTIC <input type="checkbox"/> ALU
HEX ADAPTER <input type="checkbox"/> -2MM <input type="checkbox"/> -1MM <input checked="" type="checkbox"/> 0MM		HEX ADAPTER <input type="checkbox"/> -2MM <input type="checkbox"/> -1MM <input checked="" type="checkbox"/> 0MM

CASTER <input type="checkbox"/> 10° <input checked="" type="checkbox"/> 12°	SPINDLE <input checked="" type="checkbox"/> HIGH <input type="checkbox"/> LOW	BRACE <input checked="" type="checkbox"/> PLASTIC <input type="checkbox"/> ALU
INSERT NR. 0 <input type="checkbox"/> UP <input type="checkbox"/> DOWN	INSERT NR. 0 <input type="checkbox"/> UP <input type="checkbox"/> DOWN	BRACE <input checked="" type="checkbox"/> PLASTIC <input type="checkbox"/> ALU
BRACE <input checked="" type="checkbox"/> PLASTIC <input type="checkbox"/> ALU		BRACE <input checked="" type="checkbox"/> PLASTIC <input type="checkbox"/> ALU
INSERT NR. 4 <input checked="" type="checkbox"/> UP <input type="checkbox"/> DOWN		INSERT NR. 6 <input type="checkbox"/> IN <input checked="" type="checkbox"/> OUT
STANDARD BRACKET <input checked="" type="checkbox"/> OPTIONAL TYPE <input type="checkbox"/>		STANDARD BRACKET <input checked="" type="checkbox"/> OPTIONAL TYPE <input type="checkbox"/>

ANTI ROLLBAR <input type="checkbox"/> 1.8MM <input type="checkbox"/> 2.0MM <input checked="" type="checkbox"/> 2.3MM <input type="checkbox"/> 2.5MM <input type="checkbox"/> 2.7MM	WHEELBASE SHIMS <input type="checkbox"/> 1.25 <input type="checkbox"/> 2.5 <input checked="" type="checkbox"/> 3.75 5MM	WING LOCATION IN MM
STEERING BAR <input type="checkbox"/> OPT 1 <input type="checkbox"/> OPT 2 <input checked="" type="checkbox"/> OPT 3	ANTI ROLLBAR <input type="checkbox"/> 1.8MM <input checked="" type="checkbox"/> 2.0MM <input type="checkbox"/> 2.3MM <input type="checkbox"/> 2.5MM <input type="checkbox"/> 2.7MM	

FRONT CAMBER + 0 -1.5°	REAR CAMBER - 1° + 0°
SHOCKLENGTH AT FULL DROOP 97 MM	SHOCKLENGTH AT FULL DROOP 113 MM
ADJUST SHOCKLENGTH WITH THIS SCREW	ADJUST SHOCKLENGTH WITH THIS SCREW
ADJUST RIDE HEIGHT WITH SPRING COLLAR	ADJUST RIDE HEIGHT WITH SPRING COLLAR
RIDE HEIGHT 25 MM	RIDE HEIGHT 28 MM