



# SET UP

NAME	jeremy whitig	RACE	midwest nitro series	DATE	9-15-12
TRACK	clark rc park	CITY/COUNTRY	usa	CONTACT	
TRACK SIZE	<input type="checkbox"/> OPEN	<input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> TIGHT	TEMP: F° / °C	
TRACK TRACTION	<input checked="" type="checkbox"/> HIGH	<input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> LOW	AIR 52° TRACK 55°	
TRACK SURFACE	<input checked="" type="checkbox"/> SMOOTH	<input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> BUMPY	LAPS 51	
TRACK TYPE	<input type="checkbox"/> HARD PACKED	<input type="checkbox"/> SOFT DIRT	<input type="checkbox"/> CLAY	BEST LAPTIME	in LAP
	<input checked="" type="checkbox"/> BLUE GROOVE	<input type="checkbox"/> ASTRO TURF	<input type="checkbox"/> GRASS	RACE LENGTH	25 min
TRACK CONDITION	<input checked="" type="checkbox"/> DRY	<input checked="" type="checkbox"/> DUSTY	<input type="checkbox"/> MUD	RACE RESULT	6th

## DIFFERENTIAL OIL

FRONT	CENTER	REAR
5000 CST	5000 CST	3000 CST

## CLUTCH

TYPE: STANDARD	<input type="checkbox"/> OPTIONAL	buku 3 shoe
SHOE: ALU	<input type="checkbox"/> PCS	SPRING
CARBON	<input type="checkbox"/> PCS	SPRING

## GEARING

CLUTCH BELL	16 T	SPUR GEAR	46 T
-------------	------	-----------	------

## BRAKE BALANCERS

50/50	<input type="checkbox"/>	BALANCER CLIPS:	0.5 MM	pcs
OPTION	<input type="checkbox"/>		0.75MM	pcs
			1.0 MM	pcs
			1.25MM	pcs
			1.5 MM	pcs

## SHOCKS

FRONT	SPRING	REAR
C= 4.8	<input type="checkbox"/> PINK	C= 2.8
C= 5.0	<input checked="" type="checkbox"/> BLUE	C= 3.0
C= 5.2	<input type="checkbox"/> PURPLE	C= 3.2
C= 5.4	<input type="checkbox"/> GREEN	C= 3.4
C= 5.6	<input type="checkbox"/> GREY	C= 3.6
C= 5.8	<input type="checkbox"/> YELLOW	C= 3.8
C= 6.0	<input type="checkbox"/> WHITE	C= 4.0
C=	<input type="checkbox"/> OTHER	C=
40wt	OIL/CST	32.5
25	REBOUND %	25

## PISTON

HOLES SIZE	<input type="checkbox"/> 1.1MM	<input type="checkbox"/>
	<input checked="" type="checkbox"/> 1.2MM	<input checked="" type="checkbox"/>
	<input type="checkbox"/> 1.3MM	<input type="checkbox"/>
	<input type="checkbox"/> 1.4 MM	<input type="checkbox"/>
6 taper down	OTHER	6 taper down
losi oil		losi oil

TYRES	BODY
BRAND beta	BRAND stock
TYPE freeride	TYPE
INSERT dual	WING OPTIONAL
WHEELS beta	STOCK <input checked="" type="checkbox"/> BRAND
	TYPE

## ENGINE

TYPE	alpha a-852
MANIFOLD	stock round alpha
MUFFLER	alpha 2090
PLUG	97t od
FUEL	vp 30%

## COMMENTS

option 2 took steering away during the day.  
option 3 gave steering back during the main  
for the cold track temp..  
car is very easy to drive. qualified 4th..  
really good in the rough sections..

Webbed Bladders

STEERING BLOCK <input checked="" type="checkbox"/> PLASTIC <input type="checkbox"/> ALU	CASTER BLOCK <input checked="" type="checkbox"/> PLASTIC <input type="checkbox"/> ALU	UPRIGHT <input checked="" type="checkbox"/> PLASTIC <input type="checkbox"/> ALU
HEX ADAPTER <input type="checkbox"/> -2MM <input type="checkbox"/> -1MM <input checked="" type="checkbox"/> 0MM		HEX ADAPTER <input type="checkbox"/> -2MM <input type="checkbox"/> -1MM <input checked="" type="checkbox"/> 0MM

CASTER <input type="checkbox"/> 10° <input checked="" type="checkbox"/> 12°	SPINDLE <input type="checkbox"/> HIGH <input checked="" type="checkbox"/> LOW	BRACE <input type="checkbox"/> PLASTIC <input checked="" type="checkbox"/> ALU
INSERT NR. 1 <input checked="" type="checkbox"/> UP <input type="checkbox"/> DOWN	INSERT NR. 0 <input type="checkbox"/> UP <input type="checkbox"/> DOWN	BRACE <input checked="" type="checkbox"/> STANDARD BRACKET <input type="checkbox"/> OPTIONAL TYPE
		BRACE <input checked="" type="checkbox"/> STANDARD BRACKET <input type="checkbox"/> OPTIONAL TYPE lrc

ANTI ROLLBAR <input type="checkbox"/> 1.8MM <input type="checkbox"/> 2.0MM <input type="checkbox"/> 2.3MM <input checked="" type="checkbox"/> 2.5MM <input type="checkbox"/> 2.7MM	SERVO SAVER SPRING <input type="checkbox"/> STANDARD <input checked="" type="checkbox"/> HARD	WHEELBASE SHIMS <input type="checkbox"/> 1.25 <input checked="" type="checkbox"/> 2.5 <input type="checkbox"/> 3.75 <input type="checkbox"/> 5MM
STEERING BAR <input type="checkbox"/> OPT 1 <input checked="" type="checkbox"/> OPT 2 <input checked="" type="checkbox"/> OPT 3	ANTI ROLLBAR <input type="checkbox"/> 1.8MM <input type="checkbox"/> 2.0MM <input checked="" type="checkbox"/> 2.3MM <input type="checkbox"/> 2.5MM <input type="checkbox"/> 2.7MM	WING LOCATION IN MM 25

FRONT CAMBER + - 2°	REAR CAMBER - 2° + 1°
SHOCK LENGTH AT FULL DROOP 99.7 MM	SHOCK LENGTH AT FULL DROOP 114 MM
ADJUST SHOCK LENGTH WITH THIS SCREW	ADJUST SHOCK LENGTH WITH THIS SCREW
ADJUST RIDE HEIGHT WITH SPRING COLLAR	ADJUST RIDE HEIGHT WITH SPRING COLLAR
RIDE HEIGHT 29 MM	RIDE HEIGHT 29 MM