



2013 COBBLE

SET UP

DRIVER Chris Aretakis	RACE CRCORCS Champ. Race	DATE 10/14/12
TRACK Dirt Works	CITY Burlington, CO	COUNTRY USA
TRACK SIZE <input type="checkbox"/> OPEN <input type="checkbox"/> MEDIUM <input type="checkbox"/> TIGHT TRACK TRACTION <input type="checkbox"/> HIGH <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> LOW TRACK SURFACE <input type="checkbox"/> SMOOTH <input checked="" type="checkbox"/> MEDIUM <input checked="" type="checkbox"/> BUMPY TRACK TYPE <input checked="" type="checkbox"/> HARD PACKED <input type="checkbox"/> SOFT DIRT <input type="checkbox"/> CLAY <input type="checkbox"/> BLUE GROOVE <input type="checkbox"/> ASTRO TURF <input type="checkbox"/> GRASS TRACK CONDITION <input checked="" type="checkbox"/> DRY <input checked="" type="checkbox"/> DUSTY <input type="checkbox"/> WET	TEMP °F / °C AIR 72 F TRACK _____ LAPS _____ BEST LAPTIME 33.6 QUALI RESULT _____ RACE RESULT 5th	

DIFFERENTIAL OIL

FRONT	CENTER	REAR
5000 CST	6000 CST	4000 CST

CLUTCH

TYPE: STANDARD <input type="checkbox"/> OPTIONAL TLR Steel <input type="checkbox"/>
SHOE: ALU 2 PCS <input type="checkbox"/> SPRING Green <input type="checkbox"/>
CARBON 2 PCS <input type="checkbox"/> SPRING Black <input type="checkbox"/>

GEARING

CLUTCH BELL 16 T	SPUR GEAR 46 T
-------------------------	-----------------------

BRAKE BALANCERS

50/50 <input checked="" type="checkbox"/>	BALANCER CLIPS: 0.5 MM <input type="checkbox"/> pcs
OPTION <input type="checkbox"/>	0.75MM <input type="checkbox"/> pcs
	1.0 MM <input type="checkbox"/> pcs
	1.25MM <input type="checkbox"/> pcs
	1.5MM <input type="checkbox"/> pcs

SHOCKS

FRONT	SPRING	REAR
<input type="checkbox"/>	Orange	<input type="checkbox"/>
<input type="checkbox"/>	Red	<input type="checkbox"/>
<input type="checkbox"/>	Pink	<input type="checkbox"/>
<input checked="" type="checkbox"/>	Blue	<input type="checkbox"/>
<input type="checkbox"/>	Purple	<input type="checkbox"/>
<input type="checkbox"/>	Green	<input type="checkbox"/>
<input type="checkbox"/>	Other	<input checked="" type="checkbox"/>
65	OIL/CST	55
1/2	REBOUND %	1/2

PISTON

<input type="radio"/> OPEN	PISTON	<input checked="" type="radio"/> CLOSED
HOLES SIZE <input type="checkbox"/> 1.1MM <input type="checkbox"/> <input type="checkbox"/> 1.2MM <input type="checkbox"/> <input type="checkbox"/> 1.3MM <input type="checkbox"/> <input type="checkbox"/> 1.4 MM <input type="checkbox"/> OTHER <input type="checkbox"/>		
V2 RED CSI		V2 Red CSI

TYRES	BODY
BRAND JCONCEPTS	BRAND Serpent
TYPE Blue Hybrids	TYPE Stock TE Body
INSERT JC CC	WING <input type="checkbox"/> OPTIONAL <input type="checkbox"/>
WHEELS JC	STOCK <input type="checkbox"/> BRAND TLR <input type="checkbox"/>
	TYPE Universal

ENGINE

TYPE Novarossi Plus-4C Team
MANIFOLD Novarossi 41021
MUFFLER Novarossi 2096SS
PLUG Novarossi #5
FUEL Byrons Race Gen 40%

COMMENTS

Yellow Rear Springs

Might go to Blue CSI pistons with 60F oil and 50R oil

STEERING BLOCK <input checked="" type="checkbox"/> PLASTIC <input type="checkbox"/> ALU	CASTER BLOCK <input checked="" type="checkbox"/> PLASTIC <input type="checkbox"/> ALU
--	--

HEX ADAPTER ☐ -2MM ☐ -1MM ☒ 0MM

UPRIGHT <input checked="" type="checkbox"/> PLASTIC <input type="checkbox"/> ALU

HEX ADAPTER ☐ -2MM ☐ -1MM ☒ 0MM

CASTER <input type="checkbox"/> 10° <input checked="" type="checkbox"/> 12°	SPINDLE <input checked="" type="checkbox"/> HIGH <input type="checkbox"/> LOW
--	--

BRACE
☐ PLASTIC
☒ ALU

INSERT NR. 0 ☒ UP ☐ DOWN

BRACE
☐ PLASTIC
☒ ALU

BRACE <input type="checkbox"/> PLASTIC <input checked="" type="checkbox"/> ALU

INSERT NR. 6 ☒ UP ☐ DOWN

BRACE
☒ STANDARD BRACKET
☐ OPTIONAL TYPE _____

BRACE
☐ PLASTIC
☒ ALU

INSERT NR. 6 ☒ IN ☐ OUT

BRACE
☒ STANDARD BRACKET
☐ OPTIONAL TYPE LRC

ANTI ROLLBAR <input type="checkbox"/> 1.8MM <input type="checkbox"/> 2.0MM <input checked="" type="checkbox"/> 2.3MM <input type="checkbox"/> 2.5MM <input type="checkbox"/> 2.7MM	WHEELBASE SHIMS <input type="checkbox"/> 1.25 <input checked="" type="checkbox"/> 2.5 <input type="checkbox"/> 3.75 <input type="checkbox"/> 5MM
--	--

STEERING BAR
☐ OPT 1
☒ OPT 2
☐ OPT 3

SERVO SAVER SPRING
☐ STANDARD
☒ HARD

ANTI ROLLBAR <input type="checkbox"/> 1.8MM <input checked="" type="checkbox"/> 2.0MM <input type="checkbox"/> 2.3MM <input type="checkbox"/> 2.5MM <input type="checkbox"/> 2.7MM
--

WING LOCATION IN MM +DF

FRONT CAMBER + -2°

SHOCKLENGTH AT FULL DROOP 100 MM

ADJUST SHOCKLENGTH WITH THIS SCREW

ADJUST RIDE HEIGHT WITH SPRING COLLAR

RIDE HEIGHT 29 MM

REAR CAMBER -2° +

SHOCKLENGTH AT FULL DROOP 123 MM

ADJUST SHOCKLENGTH WITH THIS SCREW

ADJUST RIDE HEIGHT WITH SPRING COLLAR

RIDE HEIGHT 30 MM