



SET UP

NAME	Frank L	RACE	DNC 2013	DATE	02-24-2013
TRACK	Fear Farm	CITY/COUNTRY	Phoenix, AZ	CONTACT	
TRACK SIZE	<input checked="" type="checkbox"/> OPEN	<input type="checkbox"/> MEDIUM	<input type="checkbox"/> TIGHT	TEMP. F ° / ° C	
TRACK TRACTION	<input checked="" type="checkbox"/> HIGH	<input type="checkbox"/> MEDIUM	<input type="checkbox"/> LOW	AIR	TRACK
TRACK SURFACE	<input type="checkbox"/> SMOOTH	<input type="checkbox"/> MEDIUM	<input checked="" type="checkbox"/> BUMPY	LAPS	
TRACK TYPE	<input checked="" type="checkbox"/> HARD PACKED	<input type="checkbox"/> SOFT DIRT	<input type="checkbox"/> CLAY	BEST LAPTIME in LAP	
<input type="checkbox"/> BLUE GROOVE	<input type="checkbox"/> ASTRO TURF	<input type="checkbox"/> GRASS	RACE LENGTH		
TRACK CONDITION	<input checked="" type="checkbox"/> DRY	<input checked="" type="checkbox"/> DUSTY	<input type="checkbox"/> MUD	RACE RESULT	

DIFFERENTIAL OIL

FRONT	CENTER	REAR
12000 CST	12000 CST	12000 CST

CLUTCH

TYPE: STANDARD ☐ OPTIONAL ☐

SHOE: ALU ☐ PCS ☐ SPRING ☐

CARBON ☐ PCS ☐ SPRING ☐

GEARING

CLUTCH BELL 17 T SPUR GEAR stk T

BRAKE BALANCERS

50/50	<input type="checkbox"/>	BALANCER CLIPS:	0.5 MM	pcs
OPTION	<input type="checkbox"/>		0.75MM	pcs
			1.0 MM	pcs
			1.25MM	pcs
			1.5 MM	pcs

SHOCKS

FRONT	SPRING	REAR
C= 4.8 <input type="checkbox"/>	PINK	C= 2.8 <input type="checkbox"/>
C= 5.0 <input type="checkbox"/>	BLUE	C= 3.0 <input type="checkbox"/>
C= 5.2 <input type="checkbox"/>	PURPLE	C= 3.2 <input type="checkbox"/>
C= 5.4 <input type="checkbox"/>	GREEN	C= 3.4 <input type="checkbox"/>
C= 5.6 <input type="checkbox"/>	GREY	C= 3.6 <input type="checkbox"/>
C= 5.8 <input checked="" type="checkbox"/>	YELLOW	C= 3.8 <input checked="" type="checkbox"/>
C= 6.0 <input type="checkbox"/>	WHITE	C= 4.0 <input type="checkbox"/>
C= <input type="checkbox"/>	OTHER	C= <input type="checkbox"/>
800	OIL/CST	700
	REBOUND %	

PISTON

HOLES SIZE

1.1MM ☐

1.2MM ☐

1.3MM ☐

1.4 MM ☐

OTHER ☐

CSI Blue

TYRES

BRAND	AKA	BRAND	Serpent
TYPE	Grid Iron	TYPE	BE
INSERT	Red	WING	OPTIONAL
WHEELS	Evo	STOCK	BRAND Upgrade
		TYPE	Vortex

ENGINE

TYPE Tekin 1900 RX8

MANIFOLD

MUFFLER

PLUG

FUEL

COMMENTS

1.0 Version BE Buggy
Springs are V1
Rear Hex is +2
Stock rear shocks
HB alum steering servo horn

STEERING BLOCK

☒ PLASTIC

☐ ALU

CASTER BLOCK

☒ PLASTIC

☐ ALU

HEX ADAPTER ☐ -2MM ☐ -1MM ☐ 0MM

UPRIGHT

☒ PLASTIC

☐ ALU

CASTER

☐ 10°

☒ 12°

SPINDLE

☐ HIGH

☒ LOW

BRACE

☐ PLASTIC

☒ ALU

BRACE

☐ PLASTIC

☒ ALU

ANTI ROLLBAR

☐ 1.8MM

☐ 2.0MM

☐ 2.3MM

☒ 2.5MM

☐ 2.7MM

WHEELBASE SHIMS

☐ 1.25

☐ 2.5

☐ 3.75

☐ 5MM

SERVO SAVER SPRING

☒ STANDARD

☐ HARD

ANTI ROLLBAR

☒ 1.8MM

☐ 2.0MM

☐ 2.3MM

☐ 2.5MM

☐ 2.7MM

FRONT CAMBER

+ ° - 3 °

SHOCKLENGTH AT FULL DROOP 98 MM

ADJUST SHOCKLENGTH WITH THIS SCREW

ADJUST RIDE HEIGHT WITH SPRING COLLAR

RIDE HEIGHT 28 MM

REAR CAMBER

- 1 ° + °

SHOCKLENGTH AT FULL DROOP 114 MM

ADJUST SHOCKLENGTH WITH THIS SCREW

ADJUST RIDE HEIGHT WITH SPRING COLLAR

RIDE HEIGHT 28 MM