

SET UP

Use www.pdfescape.com to edit, save and send.



NAME		RACE BRCA Adur		DATE	
-------------	--	-----------------------	--	-------------	--

1 ST		SPUR		2ND	
<input type="checkbox"/> 60	<input checked="" type="checkbox"/> 59	<input type="checkbox"/> 58	<input type="checkbox"/> 53	<input type="checkbox"/> 54	<input checked="" type="checkbox"/> 55

1 ST		PINION		2ND	
<input checked="" type="checkbox"/> 16	<input type="checkbox"/> 17	<input type="checkbox"/> 18	<input type="checkbox"/> 21	<input checked="" type="checkbox"/> 22	<input type="checkbox"/> 23

FRONT		DRIVE TRAIN		REAR	
GEAR DIFF		GEAR DIFF		GEAR DIFF	
<input type="checkbox"/> 150,000 CST		<input type="checkbox"/> 60,000 CST		<input type="checkbox"/> 60,000 CST	
NUMBER OF GEARS		NUMBER OF GEARS		NUMBER OF GEARS	
2 <input type="checkbox"/> 4 <input checked="" type="checkbox"/>		2 <input type="checkbox"/> 4 <input checked="" type="checkbox"/>		2 <input type="checkbox"/> 4 <input checked="" type="checkbox"/>	
<input type="checkbox"/> ONE WAY		<input type="checkbox"/> ONE WAY		<input type="checkbox"/> ONE WAY	
<input type="checkbox"/> SPOOL		<input type="checkbox"/> SPOOL		<input type="checkbox"/> SPOOL	

FRONT		SHOCK ABSORBERS		REAR	
OIL/CST		TYPE:RCC <input type="checkbox"/> TYPE:RCM <input type="checkbox"/>		OIL/CST	
600		OPEN		500	
SPRING		CLOSED		SPRING	
pink		orange		orange	

FRONT		ANTI-ROLL BARS		REAR	
<input type="checkbox"/> 1.8		<input checked="" type="checkbox"/> 2.5		<input type="checkbox"/> 1.8	
<input type="checkbox"/> 2.2		<input type="checkbox"/> 2.8		<input type="checkbox"/> 1.9	
<input type="checkbox"/> 2.5		<input type="checkbox"/> 2.0		<input type="checkbox"/> 2.1	
<input type="checkbox"/> 2.8		<input type="checkbox"/> 2.2		<input type="checkbox"/> 2.3	
<input type="checkbox"/> 2.0		<input type="checkbox"/> 2.5		<input type="checkbox"/> 2.0	

FRONT		TYRES		REAR	
LEFT		RIGHT		LEFT	
xceed		MAKE		xceed	
32 °		SHORE		37 °	
mm		DIAMETER		mm	
mm		5-MIN WEAR		mm	

ENGINE		Novarossi	
TYPE		keep <input checked="" type="checkbox"/> HEADSHIMS	
GLOWPLUG		CARB DIA'	
5		std mm	

EXHAUST		2660	
FIXED HEADER		CONICAL	
<input type="checkbox"/> LONG MED SHORT		<input checked="" type="checkbox"/> YES NO	

FUEL		mecca		NITRO 16 %	
-------------	--	-------	--	------------	--

BODY		PF srs	
WING		std	
BODY-TYPE		mm	

REMARKS

TRACK Adur	
-------------------	--

FRONT

SHOCK MOUNTING POSITION

UPPER ARM POSITION

0 mm

ROLL CENTER SPACER

REAR

SHOCK MOUNTING POSITION

UPPER PIVOT POINT

SHIMS 3 mm

ANTI-ROLL BAR MOUNTING POSITION

REAR

SHOCK MOUNTING POSITION

ROLL CENTER INSERTS

STANDARD ☒

CARBON EXTENSION ☐

STEERING BLOCKS

0 ☒ 1 ☐

-1 mm

TYPE WHEEL HEX

DOWN STOPS

std mm

TYPE WHEEL HEX

FRONT

0 mm

REAR

3 mm

FRONT

L 2 °

R 2 °

REAR

L 3.5 °

R 3 °

FRONT

RIDE HEIGHT 7 mm

WITH TYRE Ø

REAR

RIDE HEIGHT 7 mm

WITH TYRE Ø

FRONT

TOE IN (+) TOE OUT (-)

CASTER 4 mm

SPACERS FRONT

ACKERMANN ☒ 1 ☐ 2

WHEEL BASE

REAR

WHEEL BASE

2.5 °

FRONT

FLEX YES ☒ NO ☐

CHASSIS CONNECTORS ALU ☒ RUBBER ☐

REAR

weight position

weight position

weight position