



2013 COBBLE

SET UP

DRIVER	Jeffrey Halsema	RACE	Bugycup	DATE	13-5-2013
TRACK	MVV	CITY	Purmerend	COUNTRY	Holland
TRACK SIZE	<input checked="" type="checkbox"/> OPEN	<input type="checkbox"/> MEDIUM	<input type="checkbox"/> TIGHT	TEMP. F / °C	
TRACK TRACTION	<input type="checkbox"/> HIGH	<input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> LOW	AIR	TRACK
TRACK SURFACE	<input type="checkbox"/> SMOOTH	<input type="checkbox"/> MEDIUM	<input checked="" type="checkbox"/> BUMPY	LAPS	
TRACK TYPE	<input type="checkbox"/> HARD PACKED	<input type="checkbox"/> SOFT DIRT	<input type="checkbox"/> CLAY	BEST LAPTIME	
	<input type="checkbox"/> BLUE GROOVE	<input checked="" type="checkbox"/> ASTRO TURF	<input type="checkbox"/> GRASS	QUALI RESULT	
TRACK CONDITION	<input checked="" type="checkbox"/> DRY	<input type="checkbox"/> DUSTY	<input type="checkbox"/> WETT	RACE RESULT	2

DIFFERENTIAL OIL

FRONT	CENTER	REAR
7000 CST	10000 CST	5000 CST

CLUTCH

TYPE: STANDARD	<input checked="" type="checkbox"/> OPTIONAL	
SHOE: ALU	PCS	SPRING
CARBON	4 PCS	SPRING 1.0

GEARING

CLUTCH BELL	13 T	SPUR GEAR	48 T
-------------	------	-----------	------

BRAKE BALANCERS

50/50	<input type="checkbox"/>	BALANCER CLIPS:	0.5 MM	pcs
OPTION	<input checked="" type="checkbox"/>		0.75MM	pcs
			1.0 MM	pcs
			1.25MM	pcs
			1.5MM	pcs

SHOCKS

FRONT	SPRING	REAR
<input type="checkbox"/>	Orange	<input type="checkbox"/>
<input type="checkbox"/>	Red	<input type="checkbox"/>
<input type="checkbox"/>	Pink	<input type="checkbox"/>
<input type="checkbox"/>	Blue	<input type="checkbox"/>
<input type="checkbox"/>	Purple	<input type="checkbox"/>
<input type="checkbox"/>	Green	<input type="checkbox"/>
<input checked="" type="checkbox"/>	Other	<input checked="" type="checkbox"/>
450	OIL/CST	400
10	REBOUND %	10

☐ OPEN **PISTON** ☒ CLOSED

HOLES SIZE	
<input type="checkbox"/> 1.1MM	<input type="checkbox"/>
<input type="checkbox"/> 1.2MM	<input type="checkbox"/>
<input checked="" type="checkbox"/> 1.3MM	<input checked="" type="checkbox"/>
<input type="checkbox"/> 1.4 MM	<input type="checkbox"/>
8-holes conical	OTHER
	8-holes conical

TYRES

BRAND	Tourex	BRAND	Serpent
TYPE	X300 syntrax	TYPE	Aventura
INSERT		WING	OPTIONAL
WHEELS		STOCK	<input checked="" type="checkbox"/> BRAND
		TYPE	

ENGINE

TYPE	OS-Speed2
MANIFOLD	OS
MUFFLER	OS
PLUG	P3
FUEL	Tornado

COMMENTS

Yellow springs front
Yellow springs rear

STEERING BLOCK	<input checked="" type="checkbox"/> PLASTIC	<input type="checkbox"/> ALU
CASTER BLOCK	<input checked="" type="checkbox"/> PLASTIC	<input type="checkbox"/> ALU

HEX ADAPTER ☐ -2MM ☐ -1MM ☒ 0MM

UPRIGHT	<input type="checkbox"/> PLASTIC	<input checked="" type="checkbox"/> ALU
----------------	----------------------------------	---

HEX ADAPTER ☐ -2MM ☐ -1MM ☒ 0MM

CASTER	<input checked="" type="checkbox"/> 10°	<input type="checkbox"/> 12°
---------------	---	------------------------------

SPINDLE ☐ HIGH ☒ LOW

BRACE ☐ PLASTIC ☒ ALU

INSERT NR. 0 ☐ UP ☐ DOWN

INSERT NR. 0 ☐ UP ☐ DOWN

BRACE	<input type="checkbox"/> PLASTIC	<input checked="" type="checkbox"/> ALU
--------------	----------------------------------	---

INSERT NR. 4 ☒ UP ☐ DOWN

INSERT NR. 6 ☐ IN ☒ OUT

☐ STANDARD BRACKET ☒ STANDARD BRACKET

☐ OPTIONAL TYPE ☐ OPTIONAL TYPE

ANTI ROLL BAR	<input type="checkbox"/> 1.8MM	<input type="checkbox"/> 2.0MM	<input checked="" type="checkbox"/> 2.3MM	<input type="checkbox"/> 2.5MM	<input type="checkbox"/> 2.7MM
----------------------	--------------------------------	--------------------------------	---	--------------------------------	--------------------------------

STEERING BAR ☐ OPT 1 ☐ OPT 2 ☒ OPT 3

SERVO SAVER SPRING ☒ STANDARD ☐ HARD

WHEELBASE SHIMS	<input checked="" type="checkbox"/> 1.25	<input type="checkbox"/> 2.5	<input type="checkbox"/> 3.75	<input type="checkbox"/> 5MM
------------------------	--	------------------------------	-------------------------------	------------------------------

ANTI ROLL BAR ☐ 1.8MM ☐ 2.0MM ☒ 2.3MM ☐ 2.5MM ☐ 2.7MM

WING LOCATION IN MM std

FRONT CAMBER	<input type="checkbox"/> + <input type="checkbox"/> 0 <input type="checkbox"/> -1°
---------------------	--

SHOCKLENGTH AT FULL DROOP 99 MM

ADJUST SHOCKLENGTH WITH THIS SCREW

ADJUST RIDE HEIGHT WITH SPRING COLLAR

RIDE HEIGHT 24 MM

REAR CAMBER	<input type="checkbox"/> -3° <input type="checkbox"/> +
--------------------	---

SHOCKLENGTH AT FULL DROOP 123 MM

ADJUST SHOCKLENGTH WITH THIS SCREW

ADJUST RIDE HEIGHT WITH SPRING COLLAR

RIDE HEIGHT 27 MM