

# SET UP

Use [www.pdfescape.com](http://www.pdfescape.com) to edit, save and send.



<b>NAME</b> Michael Salven		<b>RACE</b> German National 1/10		<b>DATE</b> 31-08-2013	
----------------------------	--	----------------------------------	--	------------------------	--

  

<b>TRACK</b> Ettlingen					
------------------------	--	--	--	--	--

  

<b>1 ST</b> <b>SPUR</b> <b>2ND</b> <input type="checkbox"/> 60 <input checked="" type="checkbox"/> 59 <input type="checkbox"/> 58   <input type="checkbox"/> 53 <input checked="" type="checkbox"/> 54 <input type="checkbox"/> 55	
<b>1 ST</b> <b>PINION</b> <b>2ND</b> <input type="checkbox"/> 16 <input checked="" type="checkbox"/> 17 <input type="checkbox"/> 18   <input checked="" type="checkbox"/> 21 <input type="checkbox"/> 22 <input type="checkbox"/> 23	
<b>FRONT</b> <b>DRIVE TRAIN</b> <b>REAR</b> GEAR DIFF <input type="checkbox"/> CST <input checked="" type="checkbox"/> 60000 CST NUMBER OF GEARS 2 <input type="checkbox"/> 4 <input type="checkbox"/>   2 <input type="checkbox"/> 4 <input checked="" type="checkbox"/> ONE WAY <input type="checkbox"/> SPOOL <input checked="" type="checkbox"/> SOLID <input type="checkbox"/>	
<b>FRONT</b> <b>SHOCK ABSORBERS</b> <b>REAR</b> OIL/CST 700 TYPE:RCC <input type="checkbox"/> TYPE:RCM <input checked="" type="checkbox"/> OIL/CST 700 SPRING red OPEN CLOSED SPRING red 	
<b>FRONT</b> <b>ANTI-ROLL BARS</b> <b>REAR</b> <input type="checkbox"/> 1.8 <input checked="" type="checkbox"/> 2.2 <input type="checkbox"/> 2.5 <input type="checkbox"/> 2.8   <input type="checkbox"/> 1.8 <input type="checkbox"/> 1.9 <input type="checkbox"/> 2.0 <input type="checkbox"/> 2.1 <input checked="" type="checkbox"/> 2.2 <input type="checkbox"/> 2.3 <input type="checkbox"/> 2.5	
<b>FRONT</b> <b>TYRES</b> <b>REAR</b> LEFT RIGHT MAKE LEFT RIGHT 35° 35° SHORE 37° 37° 62 mm 62 mm DIAMETER 64 mm 64 mm 5-MIN WEAR	
<b>ENGINE</b> Xceed ZX 12 DS6 TYPE EDO HEADSHIMS 0.4 mm GLOWPLUG 6 cold CARB DIA' 5.5 mm	
<b>EXHAUST</b> 2669 FIXED HEADER <input type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/> CONICAL <input checked="" type="checkbox"/> <input type="checkbox"/> LONG MED SHORT YES NO	
<b>FUEL</b> Xceed <b>NITRO</b> 16%	
<b>BODY</b> Protoform P37 WING standard BODY-TYPE light 45 mm	

  
  

**REMARKS**  
 handout race tires LRP Vetec.  
 RCM-SS shocks.  
 ride-height with set-up wheels Ø 64.8

  

<b>FRONT</b> SHOCK MOUNTING POSITION UPPER ARM POSITION 0.5/1 mm ROLL CENTER SPACER		<b>REAR</b> SHIMS 2 mm UPPER PIVOT POINT ANTI-ROLL BAR MOUNTING POSITION		<b>REAR</b> SHOCK MOUNTING POSITION ROLL CENTER INSERTS STANDARD <input checked="" type="checkbox"/> CARBON EXTENSION <input type="checkbox"/>	
<b>DOWN STOPS</b> STEERING BLOCKS <input checked="" type="checkbox"/> 0 <input type="checkbox"/> 1 5 mm TYPE WHEEL HEX FRONT 2 mm REAR 5 mm					
<b>CAMBER</b> L -2° R -3° CAMBER RIDE HEIGHT 6.5 mm WITH TYRE Ø 64.8 mm RIDE HEIGHT 6.5 mm WITH TYRE Ø 64.8 mm					
<b>TOE IN (+) TOE OUT (-)</b> CASTER 5 mm SPACERS FRONT ACKERMANN <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2 WHEEL BASE 3° 0mm <input type="checkbox"/> -1mm <input checked="" type="checkbox"/> -2mm <input type="checkbox"/> WHEEL BASE					
FLEX YES <input type="checkbox"/> NO <input checked="" type="checkbox"/> CHASSIS CONNECTORS ALU <input checked="" type="checkbox"/> RUBBER <input type="checkbox"/>					
197 mm 			200 mm 		
9 9 9 9 9			weight position ○○○○○○ weight position ○●○○○○○ weight position ○○○○○○		