



### DIFFERENTIAL OIL

| FRONT     | CENTER    | REAR      |
|-----------|-----------|-----------|
| 15000 CST | 20000 CST | 10000 CST |

### CLUTCH

TYPE: STANDARD ☐ OPTIONAL ☐

SHOE: ALU ☐ PCS ☐ SPRING ☐

CARBON ☐ PCS ☐ SPRING ☐

### GEARING

CLUTCH BELL 17 T SPUR GEAR 50 T

### BRAKE BALANCERS

50/50 ☐ BALANCER CLIPS: 0.5 MM ☐ pcs

OPTION ☐ 0.75MM ☐ pcs

1.0 MM ☐ pcs

1.25MM ☐ pcs

1.5 MM ☐ pcs

### SHOCKS

| FRONT                                      | SPRING | REAR                                       |
|--|--------|--|
| C= 4.8 <input checked="" type="checkbox"/> | PINK   | C= 2.8 <input type="checkbox"/>            |
| C= 5.0 <input type="checkbox"/>            | BLUE   | C= 3.0 <input type="checkbox"/>            |
| C= 5.2 <input type="checkbox"/>            | PURPLE | C= 3.2 <input type="checkbox"/>            |
| C= 5.4 <input type="checkbox"/>            | GREEN  | C= 3.4 <input type="checkbox"/>            |
| C= 5.6 <input type="checkbox"/>            | GREY   | C= 3.6 <input type="checkbox"/>            |
| C= 5.8 <input type="checkbox"/>            | YELLOW | C= 3.8 <input type="checkbox"/>            |
| C= 6.0 <input type="checkbox"/>            | WHITE  | C= 4.0 <input checked="" type="checkbox"/> |
| C= <input type="checkbox"/>                | OTHER  | C= <input type="checkbox"/>                |

450 OIL/CST 400

5mm REBOUND % 5mm

### PISTON

HOLES SIZE

☐ 1.1MM ☐

☒ 1.2MM ☒

☐ 1.3MM ☐

☐ 1.4 MM ☐

OTHER ☐

6H taper ☐ 6H taper up ☐

| TYRES  | AKA         | BODY  | Serpent       |
|--------|-------------|-------|---------------|
| BRAND  | AKA         | BRAND | Serpent       |
| TYPE   | Impact soft | TYPE  | Etruggy       |
| INSERT | red         | WING  | OPTIONAL      |
| WHEELS | evo         | STOCK | BRAND Serpent |
|        |             | TYPE  | Low           |

### ENGINE

TYPE Tekin 2000KV truggy

MANIFOLD timing 5 current limiter 30

MUFFLER

PLUG

FUEL

### COMMENTS

Buggy V2 rear hubs and castor blocks, 600611 steering blocks, Etruggy rear tower, if use nitro rear tower #3 on tower for shock, web bladders, wheelbase full short, +3mm buggy hexes front only

| NAME            | Paul Ciccarello                                 | RACE                                       | ROAR E NATS                    | DATE                |
|-----------------|---|--|--------------------------------|---------------------|
| TRACK           | LCRC  | CITY/COUNTRY                               |                                | CONTACT             |
| TRACK SIZE      | <input checked="" type="checkbox"/> OPEN        | <input type="checkbox"/> MEDIUM            | <input type="checkbox"/> TIGHT | TEMP: F° / °C       |
| TRACK TRACTION  | <input type="checkbox"/> HIGH                   | <input checked="" type="checkbox"/> MEDIUM | <input type="checkbox"/> LOW   | AIR TRACK           |
| TRACK SURFACE   | <input type="checkbox"/> SMOOTH                 | <input checked="" type="checkbox"/> MEDIUM | <input type="checkbox"/> BUMPY | LAPS                |
| TRACK TYPE      | <input checked="" type="checkbox"/> HARD PACKED | <input type="checkbox"/> SOFT DIRT         | <input type="checkbox"/> CLAY  | BEST LAPTIME in LAP |
|                 | <input type="checkbox"/> BLUE GROOVE            | <input type="checkbox"/> ASTRO TURF        | <input type="checkbox"/> GRASS | RACE LENGTH         |
| TRACK CONDITION | <input checked="" type="checkbox"/> DRY         | <input type="checkbox"/> DUSTY             | <input type="checkbox"/> MUD   | RACE RESULT         |

| STEERING BLOCK                          | CASTER BLOCK                                | UPRIGHT                                     |
|---|---|---|
| <input type="checkbox"/> PLASTIC        | <input checked="" type="checkbox"/> PLASTIC | <input checked="" type="checkbox"/> PLASTIC |
| <input checked="" type="checkbox"/> ALU | <input type="checkbox"/> ALU                | <input type="checkbox"/> ALU                |

HEX ADAPTER ☐ +2MM ☐ +1MM ☐ 0MM

HEX ADAPTER ☐ +2MM ☐ +1MM ☒ 0MM

| CASTER                                  | SPINDLE                                 | BRACE                                   |
|---|---|---|
| <input checked="" type="checkbox"/> 10° | <input type="checkbox"/> HIGH           | <input type="checkbox"/> PLASTIC        |
| <input type="checkbox"/> 12°            | <input checked="" type="checkbox"/> LOW | <input checked="" type="checkbox"/> ALU |

INSERT NR. 1 ☐ UP ☒ DOWN

INSERT NR. 0 ☐ UP ☐ DOWN

BRACE ☒ PLASTIC ☐ ALU

BRACE ☒ STANDARD BRACKET ☐ STANDARD BRACKET

BRACE ☐ OPTIONAL TYPE ☐ OPTIONAL TYPE LR

| ANTI ROLLBAR                              | WHEELBASE SHIMS   | ANTI ROLLBAR                              |
|---|-------------------|---|
| <input type="checkbox"/> 1.8MM            | 1.25 2.5 3.75 5MM | <input type="checkbox"/> 1.8MM            |
| <input type="checkbox"/> 2.0MM            |                   | <input type="checkbox"/> 2.0MM            |
| <input checked="" type="checkbox"/> 2.3MM |                   | <input type="checkbox"/> 2.3MM            |
| <input type="checkbox"/> 2.5MM            |                   | <input type="checkbox"/> 2.5MM            |
| <input type="checkbox"/> 2.7MM            |                   | <input checked="" type="checkbox"/> 2.7MM |

SERVO SAVER SPRING ☐ STANDARD ☒ HARD

STEERING BAR ☐ OPT 1 ☐ OPT 2 ☒ OPT 3

WING LOCATION IN MM

| FRONT CAMBER | REAR CAMBER |
|--------------|-------------|
| + 2°         | - 3° +      |

SHOCKLENGTH AT FULL DROOP 113 MM

SHOCKLENGTH AT FULL DROOP 123 MM

ADJUST RIDE HEIGHT WITH SPRING COLLAR

ADJUST RIDE HEIGHT WITH SPRING COLLAR

ADJUST SHOCKLENGTH WITH THIS SCREW

ADJUST SHOCKLENGTH WITH THIS SCREW

RIDE HEIGHT 37 MM

RIDE HEIGHT 41 MM