



2.1 COBBLE

SET UP

DIFFERENTIAL OIL

| FRONT | CENTER | REAR |
|------------------------------|------------------------------|------------------------------|
| <input type="checkbox"/> CST | <input type="checkbox"/> CST | <input type="checkbox"/> CST |

CLUTCH

TYPE: STANDARD ☐ OPTIONAL ☐

SHOE: ALU ☐ PCS ☐ SPRING ☐

CARBON ☐ PCS ☐ SPRING ☐

GEARING

CLUTCH BELL ☐ T ☐ SPUR GEAR ☐ T ☐

BRAKE BALANCERS

50/50 ☐ BALANCER CLIPS: 0.5 MM ☐ pcs

OPTION ☐ 0.75MM ☐ pcs

1.0 MM ☐ pcs

1.25MM ☐ pcs

1.5MM ☐ pcs

SHOCKS

| FRONT | SPRING | REAR |
|--------------------------|-----------|--------------------------|
| <input type="checkbox"/> | Orange | <input type="checkbox"/> |
| <input type="checkbox"/> | Red | <input type="checkbox"/> |
| <input type="checkbox"/> | Pink | <input type="checkbox"/> |
| <input type="checkbox"/> | Blue | <input type="checkbox"/> |
| <input type="checkbox"/> | Purple | <input type="checkbox"/> |
| <input type="checkbox"/> | Green | <input type="checkbox"/> |
| <input type="checkbox"/> | Other | <input type="checkbox"/> |
| <input type="checkbox"/> | OIL/CST | <input type="checkbox"/> |
| <input type="checkbox"/> | REBOUND % | <input type="checkbox"/> |

☐ OPEN ☐ PISTON ☐ CLOSED

| HOLES SIZE | |
|--------------------------|---------------------------------|
| <input type="checkbox"/> | 1.1MM <input type="checkbox"/> |
| <input type="checkbox"/> | 1.2MM <input type="checkbox"/> |
| <input type="checkbox"/> | 1.3MM <input type="checkbox"/> |
| <input type="checkbox"/> | 1.4 MM <input type="checkbox"/> |
| <input type="checkbox"/> | OTHER <input type="checkbox"/> |

TYRES

BODY

| | | |
|--------|--------------------------------|----------|
| BRAND | BRAND | |
| TYPE | TYPE | |
| INSERT | WING | OPTIONAL |
| WHEELS | STOCK <input type="checkbox"/> | BRAND |
| | | TYPE |

ENGINE

| TYPE |
|----------|
| MANIFOLD |
| MUFFLER |
| PLUG |
| FUEL |

COMMENTS

| DRIVER | RACE | DATE |
|--|---|---------|
| TRACK | CITY | COUNTRY |
| TRACK SIZE <input type="checkbox"/> OPEN <input type="checkbox"/> MEDIUM <input type="checkbox"/> TIGHT | TEMP: F ° / ° C | |
| TRACK TRACTION <input type="checkbox"/> HIGH <input type="checkbox"/> MEDIUM <input type="checkbox"/> LOW | AIR <input type="text"/> TRACK <input type="text"/> | |
| TRACK SURFACE <input type="checkbox"/> SMOOTH <input type="checkbox"/> MEDIUM <input type="checkbox"/> BUMPY | LAPS <input type="text"/> | |
| TRACK TYPE <input type="checkbox"/> HARD PACKED <input type="checkbox"/> SOFT DIRT <input type="checkbox"/> CLAY | BEST LAP TIME <input type="text"/> | |
| <input type="checkbox"/> BLUE GROOVE <input type="checkbox"/> ASTRO TURF <input type="checkbox"/> GRASS | QUALI RESULT <input type="text"/> | |
| TRACK CONDITION <input type="checkbox"/> DRY <input type="checkbox"/> DUSTY <input type="checkbox"/> WETT | RACE RESULT <input type="text"/> | |

STEERING BLOCK ☐ PLASTIC ☐ ALU

CASTER BLOCK ☐ PLASTIC ☐ ALU

HEX ADAPTER ☐ -2MM ☐ -1MM ☐ 0MM

UPRIGHT ☐ PLASTIC ☐ ALU

HEX ADAPTER ☐ -2MM ☐ -1MM ☐ 0MM

CASTER ☐ 10° ☐ 12°

SPINDLE ☐ HIGH ☐ LOW

BRACE ☐ PLASTIC ☐ ALU

INSERT NR. ☐ UP ☐ DOWN

BRACE ☐ PLASTIC ☐ ALU

BRACE ☐ PLASTIC ☐ ALU

INSERT NR. ☐ UP ☐ DOWN

STANDARD BRACKET ☐ OPTIONAL TYPE ☐

STANDARD BRACKET ☐ OPTIONAL TYPE ☐

ANTI ROLLBAR ☐ 1.8MM ☐ 2.0MM ☐ 2.3MM ☐ 2.5MM ☐ 2.7MM

OUT (-) ☐ IN (+) ☐

SERVO SAVER SPRING ☐ STANDARD ☐ HARD

STEERING BAR ☐ OPT 1 ☐ OPT 2 ☐ OPT 3

WHEELBASE SHIMS ☐ 1.25 ☐ 2.5 ☐ 3.75 ☐ 5MM

WING LOCATION IN MM

ANTI ROLLBAR ☐ 1.8MM ☐ 2.0MM ☐ 2.3MM ☐ 2.5MM ☐ 2.7MM

FRONT CAMBER ☐ + ☐ 0 ☐ -

SHOCKLENGTH AT FULL DROOP MM

ADJUST SHOCKLENGTH WITH THIS SCREW

ADJUST RIDE HEIGHT WITH SPRING COLLAR

RIDE HEIGHT MM

REAR CAMBER ☐ - ☐ 0 ☐ +

SHOCKLENGTH AT FULL DROOP MM

ADJUST SHOCKLENGTH WITH THIS SCREW

ADJUST RIDE HEIGHT WITH SPRING COLLAR

RIDE HEIGHT MM