

# SET UP



1ST			SPUR			2ND		
<input checked="" type="checkbox"/> 61	<input type="checkbox"/> 62	<input type="checkbox"/> 63	<input type="checkbox"/> 56	<input checked="" type="checkbox"/> 57	<input type="checkbox"/> 58			

1ST			PINION			2ND		
<input type="checkbox"/> 18	<input checked="" type="checkbox"/> 19	<input type="checkbox"/> 20	<input checked="" type="checkbox"/> 23	<input type="checkbox"/> 24	<input type="checkbox"/> 25			

SHOCK ABSORBERS			
FRONT		REAR	
OIL 1000 cst		OIL 1000 cst	
SPRINGS grey		SPRINGS pink	
<input type="radio"/> Open <input checked="" type="radio"/> Closed		<input type="radio"/> Open <input checked="" type="radio"/> Closed	

FRONT		TYRES		REAR	
RIGHT	LEFT	Controlled Tyre <input type="checkbox"/>		RIGHT	LEFT
Enneti	Enneti	MAKE		Enneti	Enneti
		SHORE			
		DIAMETER			
		5-MIN WEAR			

FRONT			ANTI-ROLL BARS			REAR		
<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
SOFT	MEDIUM	HARD	SOFT	MEDIUM	HARD	SOFT	MEDIUM	HARD

ENGINE			
ENGINE	Picco Otto		
VERSION	HEADSHIMS	mm	
GLOWPLUG	Picco 7	CARB DIA	9 mm
PIPE	2120	MANIFOLD	short "front"
FUEL	RunnerTime	NITRO	16 %

CENTAX			
CLUTCHBELL	ALU <input type="checkbox"/>	ALU COATED <input checked="" type="checkbox"/>	STEEL <input type="checkbox"/>
CLUTCHSHOE	YELLOW <input checked="" type="checkbox"/>	RED <input type="checkbox"/>	BLACK <input type="checkbox"/>
CLUTCH SPRING	Serpent hard "edge"		
CLUTCH BELL GAP	0.6 mm		

AERODYNAMIC CONFIGURATION			
BODY			
BRAND	Blitz	TYPE	TS0040
BODY POSITION	22 mm		
AIR TRIM POSITION	8 mm		
BUMPER INSERTS	<input checked="" type="checkbox"/> YES <input type="checkbox"/> NO		

REMARKS
Long rear upper arm "old position"

RACE	ENS Ettlingen	DATE	19.06.2016
TRACK	MC-Ettlingen	QUALIFYING POSITION	3
DRIVER	Merlin Depta	QUALIFYING TIME	18L4:00.626
TRACTION: LOW <input type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH <input checked="" type="checkbox"/>	STARTING POSITION	5	
TRACK TEMP <input type="checkbox"/>	AIR TEMP	20°C	
FINAL POSITION		9	

FRONT		REAR	
AERO DISKS YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	UPPER ARM INSERTS <input checked="" type="checkbox"/>	SHOCK POSITION	SHOCK POSITION
OFFSET 0.2 mm		SHIMS 2 mm	AERO DISKS YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>
DOWNSTOP 2 mm		DOWNSTOP 8 mm	OFFSET 1.2 mm

SHOCK BRACKET NARROW <input checked="" type="checkbox"/> WIDE <input type="checkbox"/>	SUSPENSION BRACKET WIDE <input checked="" type="checkbox"/> NARROW <input type="checkbox"/>	ROLL CENTER INSERTS Front <input type="checkbox"/> Rear <input type="checkbox"/>
--	---	--

FRONT CAMBER		REAR CAMBER	
R 2 °	L 1.5 °	R 2.5 °	L 2 °

ROLL CENTER SPACER Shims Front 0 mm Shims Rear 0 mm	FRONT TOE -1 °	REAR TOE +3.5 °
CASTER SPACERS 0 mm	WHEEL BASE 0 1 2 3	REAR TOE +3.5 °

INSERT POSITION	KINGPIN 1 mm	ACKERMANN
SHIMS 2 mm	WHEEL BASE 0 1 2 3	TRACKROD POSITION

TRACK WIDTH 255 mm	TOTAL CAR WEIGHT 2405 grams	WEIGHT POSITION 38 grams	WEIGHT POSITION 38 grams
TRACK WIDTH 265 mm			