

DRIVER, TRACK AND RESULTS

DRIVER	Dominic Greiner	COUNTRY	Austria	WEATHER	AIR TEMP	25	TRACK TEMP	30	<input checked="" type="checkbox"/> DRY	<input type="checkbox"/> INTERMEDIATE	<input type="checkbox"/> WET
TRACK	Aigen/Schlägl										
TRACTION	<input type="checkbox"/> LOW <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH										
COMMENTS											
RACE	ENS Rd3	DATE		QUALY POS.	2	QUALY TIME		STARTING POS.	2	FINAL POS.	12

FRONT		DRIVE TRAIN		REAR	
<input checked="" type="checkbox"/> GEAR DIFF	2.000.000 cst	<input type="checkbox"/> SPOOL		GEAR DIFF	100.000 cst
1ST		SPUR GEARS		2ND	
<input type="checkbox"/> 58	<input type="checkbox"/> 59	<input checked="" type="checkbox"/> 60		<input type="checkbox"/> 53	<input type="checkbox"/> 54
<input type="checkbox"/> 55				<input checked="" type="checkbox"/> 55	
1ST		PINION		2ND	
<input type="checkbox"/> 15	<input checked="" type="checkbox"/> 16	<input type="checkbox"/> 17		<input type="checkbox"/> 20	<input checked="" type="checkbox"/> 21
<input type="checkbox"/> 22				<input type="checkbox"/> 22	
FRONT		SHOCK ABSORBERS		REAR	
900	cst	OIL		900	cst
red		SPRINGS		red	
6	mm	REBOUND		6	mm
<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
FRONT		ANTI-ROLL BARS		REAR	
<input type="checkbox"/> 1.8	<input type="checkbox"/> 2.2	<input checked="" type="checkbox"/> 2.5	<input type="checkbox"/> 2.8	<input type="checkbox"/> 1.6	<input type="checkbox"/> 1.8
<input type="checkbox"/> 2.0	<input checked="" type="checkbox"/> 2.2	<input type="checkbox"/> 2.5			
FRONT		TYRES		REAR	
Hotrace	MAKE	Hotrace			
37	SHORE	40			
62	DIAMETER	64			
	5-MIN WEAR				

POWER PACK	
ENGINE	
BRAND	Novarossi
TYPE	WC
GLOWPLUG	6
CARBØ	5,4 mm
HEAD CLEARANCE	0,3mm
EXHAUST	
PIPE	Novarossi 2660
MANIFOLD	short
FUEL	
BRAND	RunnerTime
NITRO	16

CLUTCH	
CLUTCH BELL	<input checked="" type="checkbox"/> ALU <input type="checkbox"/> STEEL
CLUTCH SHOE	<input type="checkbox"/> RED <input checked="" type="checkbox"/> YELLOW <input type="checkbox"/> BLACK
CLUTCH SPRING	Serpent X-Spring
CLUTCH BELL GAP	0,5 mm

FLEX CONFIGURATION	
CHASSIS STIFFENER	<input checked="" type="checkbox"/> YES <input type="checkbox"/> NO
FLEX	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

AERODYNAMIC CONFIGURATION	
BODY BRAND	SRC
BODY TYPE	Spark
BUMPERS HOLES	<input checked="" type="checkbox"/> YES <input type="checkbox"/> NO
BODY POSITION	10 mm

FRONT		REAR	
AERO DISKS <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	SHOCK POSITION	CAMBERLINK SHOCK POSITION	SHIMS 2 mm
WHEEL HEX 5 mm	DOWN STOP 3,5 mm	UPPER ARM INSERT	WHEEL HEX 4 mm
FRONT CAMBER R 2,5 L 2	ROLL CENTER INSERT FRONT REAR	REAR CAMBER R 3 L 3	DOWN STOP 3 mm
RIDE HEIGHT 1,5 mm	WITH TYRE Ø 50 mm	RIDE HEIGHT 1,5 mm	WITH TYRE Ø 50 mm
CASTER 7 mm	WHEEL BASE <input checked="" type="checkbox"/> 0 <input type="checkbox"/> 1 <input type="checkbox"/> 2	FRONT TOE +0,5	REAR TOE 2
ROLL CENTER SHIMS FR 1 mm RR 2,5 mm			
INSERT POSITION	SHIMS 0 mm	KINGPIN SHIMS 1 mm	ACKERMANN INSERTS
WHEEL BASE <input checked="" type="checkbox"/> 0 <input type="checkbox"/> 1 <input type="checkbox"/> 2		TRACKROD POSITION	
WEIGHT grams	WEIGHT grams	WEIGHT DISTRIBUTION	
		CAR WEIGHT 1660 grams	
		FR SUSPENSION BRACKET BRASS <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	
TRACK WIDTH 199 mm	WEIGHT POSITION 25 grams	WEIGHT POSITION 25 grams	WEIGHT POSITION grams

REMARKS Setup with Arrowmax tools, Arrowmax titan screws on the top, xrd aluminium clutch bell,