

DRIVER, TRACK AND RESULTS

DRIVER	NACHO LÓPEZ	COUNTRY	SPAIN	WEATHER	AIR TEMP	25	TRACK TEMP	30	<input checked="" type="checkbox"/> DRY <input type="checkbox"/> INTERMEDIATE <input type="checkbox"/> WET		
TRACK	VIGO	TRACTION	<input type="checkbox"/> LOW <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH	COMMENTS SOME DIRT ON THE TRACK							
RACE	SPANISH NATS	DATE	18-09-2016	QUALY POS.	6	QUALY TIME	1-1-SHIT-SHIT-SHIT	STARTING POS.	4	FINAL POS.	3

1ST SPUR GEARS		2ND	
<input type="checkbox"/> 61	<input checked="" type="checkbox"/> 62	<input type="checkbox"/> 63	<input type="checkbox"/> 56
			<input checked="" type="checkbox"/> 57
			<input type="checkbox"/> 58

1ST PINION		2ND	
<input type="checkbox"/> 18	<input checked="" type="checkbox"/> 19	<input type="checkbox"/> 20	<input type="checkbox"/> 23
			<input checked="" type="checkbox"/> 24
			<input type="checkbox"/> 25

FRONT SHOCK ABSORBERS		REAR	
900	cst	OIL	900
PURPLE	SPRINGS	PINK	
2	mm	REBOUND	2
<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

FRONT ANTI-ROLL BARS		REAR	
<input type="checkbox"/> SOFT	<input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> SOFT	<input type="checkbox"/> MEDIUM
	<input type="checkbox"/> HARD		<input checked="" type="checkbox"/> HARD

FRONT TYRES		REAR	
HOTRACE	MAKE	HOTRACE	
32	SHORE	35	
69	DIAMETER	76	
5-MIN WEAR			

POWER PACK	
ENGINE	
BRAND	PICCO
TYPE	OTTO
GLOWPLUG	PICCO 6 CARBØ 9 mm HEAD CLEARANCE 0.5 mm
EXAUSHT	
PIPE	PICCO 2120
MANIFOLD	NOVA MED
FUEL	
BRAND	RUNNER BLUE
NITRO	16%

CLUTCH	
CLUTCH BELL	<input checked="" type="checkbox"/> ALU <input type="checkbox"/> STEEL
CLUTCH SHOE	<input type="checkbox"/> RED <input checked="" type="checkbox"/> YELLOW <input type="checkbox"/> BLACK
CLUTCH SPRING	
SHEPHERD	CLUTCH BELL GAP 0.6 mm

FLEX CONFIGURATION		
FRONT STIFFENER	FLEX	REAR CONNECTORS
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	<input checked="" type="checkbox"/> YES <input type="checkbox"/> NO	<input checked="" type="checkbox"/> YES <input type="checkbox"/> NO

AERODYNAMIC CONFIGURATION	
BODY BRAND	BLITZ
BODY TYPE	TS040
BUMPER INSERTS	<input checked="" type="checkbox"/> YES <input type="checkbox"/> NO
AIR TRIM POSITION	10 mm
BODY POSITION	23 mm

FRONT		REAR	
AERO DISKS <input checked="" type="checkbox"/> YES <input type="checkbox"/> NO	SHOCK POSITION	CAMBERLINK SHOCK POSITION	SHIMS 0.5 mm
OFFSET 1.55 mm			AERO DISKS <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO
DOWN STOP 2 mm	UPPER ARM INSERT	ROLL CENTER INSERT	DOWN STOP 8 mm
FRONT CAMBER R -1 L -1.5		REAR CAMBER R -2 L -2.5	
RIDE HEIGHT 7 mm	WITH TYRE Ø 67 mm	RIDE HEIGHT 8 mm	WITH TYRE Ø 74 mm
SHOCK BRACKET WIDE <input checked="" type="checkbox"/> NARROW <input type="checkbox"/>	SUSPENSION BRACKET NARROW <input checked="" type="checkbox"/> WIDE <input type="checkbox"/>		
CASTER 2 mm	WHEEL BASE 0 <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2 <input type="checkbox"/> 3		
FRONT TOE -1		REAR TOE +2	
ROLL CENTER SHIMS FR 1 mm RR 1 mm			
SHIMS 0 mm	INSERT POSITION	KINGPIN SHIMS 1 mm	ACKERMANN INSERTS FORWARD MID REARWARD
		TRACKROD POSITION	
WHEEL BASE 0 <input type="checkbox"/> 1 <input type="checkbox"/> 2 <input checked="" type="checkbox"/> 3			
TRACK WIDTH 252 mm		TRACK WIDTH 266 mm	
TOTAL CAR WEIGHT 2410 grams	WEIGHT POSITION	WEIGHT POSITION	
		38 grams	

REMARKS 20 GRAMS IN THE RECEIVER BOX.