

SET UP

Serpent Cobra GT 3.0

FR SHOCK ABSORBERS		RR	
OIL	1000 cst	OIL	1000 cst
SPRINGS	SILVER	SPRINGS	BLACK
PISTON N° HOLES	6 Ø 1.3 mm	PISTON N° HOLES	6 Ø 1.3 mm
TYPE	<input checked="" type="checkbox"/> FLAT <input type="checkbox"/> CONICAL	TYPE	<input checked="" type="checkbox"/> FLAT <input type="checkbox"/> CONICAL

FRONT ANTI-ROLL BARS										REAR				
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		
1.8	2.0	2.3	2.5	2.7	1.8	2.0	2.3	2.5	2.7					

DIFFERENTIAL OIL	
FRONT DIFF OIL	1.000.000 cst
REAR DIFF OIL	150.000 cst

1ST		SPUR		2ND	
<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
61	62	63	56	57	58

1ST		PINION		2ND	
<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
18	19	20	23	24	25

CLUTCH	
CLUTCHBELL	ALU <input checked="" type="checkbox"/> STEEL <input type="checkbox"/>
CLUTCH SHOES	
SHOE TYPE	Yellow x 4 with SPRING TYPE 1.0 mm
SHOE TYPE	x with SPRING TYPE mm

FR TYRES		Controlled Tyre		RR	
ARROWMAX	MAKE	ARROWMAX	MAKE	ARROWMAX	MAKE
45	TYPE	45	TYPE	45	TYPE
	INSERTS		INSERTS		INSERTS
	WHEELS		WHEELS		WHEELS

ENGINE			
ENGINE	PICCO		
VERSION	EMX-GT	HEADSHIMS	0.5 mm
GLOWPLUG	6	CARB DIA	7 mm
PIPE	2046	MANIFOLD	STD
FUEL	BYRON	NITRO	25 %

AERODYNAMIC CONFIGURATION	
BODY	
BRAND	JZR
WING	TYPE
BRAND	JZR
TYPE	FLOW
BODY POSITION	
Centered mm	

RACE	KO PROPO	DATE	09/25/16
TRACK	GLARC	QUALIFYING POSITION	
DRIVER	PAOLO MORGANTI	QUALIFYING TIME	
TRACTION: LOW	<input type="checkbox"/>	MEDIUM	<input type="checkbox"/>
HIGH	<input checked="" type="checkbox"/>	STARTING POSITION	
TRACK TEMP		AIR TEMP	
		FINAL POSITION	

FRONT		REAR	
WHEEL HEX -2 mm	CAMBERLINK POSITION	SHOCK POSITION	SHOCK POSITION
DOWNSTOP 27 mm		DOWNSTOP 24 mm	

FRONT CAMBER		REAR CAMBER	
R -1.5 °	L -2.0 °	R -2.7 °	L -3.0 °
RIDE HEIGHT 9.5 mm WITH TYRE Ø		RIDE HEIGHT 10 mm WITH TYRE Ø	

FRONT TOE		REAR TOE	
-1 °		2.5 °	
STEERING BAR			
OPT 1	OPT 2	OPT 3	

CASTER BLOCK		SERVO SAVER SPRING		WHEEL BASE	
0°	<input checked="" type="checkbox"/>	6°	10°	12°	
STD	<input checked="" type="checkbox"/>	HARD			
FRONT BRACE	<input checked="" type="checkbox"/>	STOCK	ALU		
REAR BRACE	<input checked="" type="checkbox"/>	STOCK	ALU		
FRONT FR TOE BLOCK	INSERT POS.	FRONT RR TOE BLOCK	INSERT POS.	REAR FR TOE BLOCK	INSERT POS.
UP	<input checked="" type="checkbox"/>	UP	<input checked="" type="checkbox"/>	UP	<input checked="" type="checkbox"/>
DOWN	<input type="checkbox"/>	DOWN	<input type="checkbox"/>	DOWN	<input type="checkbox"/>
FRONT RR TOE BLOCK	INSERT POS.	REAR RR TOE BLOCK	INSERT POS.	TOE BLOCK TYPE	
UP	<input checked="" type="checkbox"/>	IN	<input checked="" type="checkbox"/>	STD	<input checked="" type="checkbox"/>
DOWN	<input type="checkbox"/>	OUT	<input type="checkbox"/>	HR3	<input type="checkbox"/>
				LR3	<input type="checkbox"/>

REMARKS

600684 3.0 REAR SWAY BAR, 600176 FR RR block, 600709 diff spacer, 600611 Steering Blocks