

DRIVER, TRACK AND RESULTS

DRIVER Viktor Wilck **COUNTRY** Sweden **WEATHER** AIR TEMP 20 TRACK TEMP 20 ☐ DRY ☐ INTERMEDIATE ☐ WET
TRACK Hässleholm MK **SURFACE** ☐ ASPHALT ☒ CARPET **TRACTION** ☐ LOW ☐ MEDIUM ☒ HIGH **COMMENTS** ETS carpet
RACE Swedish Nationals Indoor **DATE** 3-5march 2017 **QUALY POS.** 1 **QUALY TIME** **STARTING POS.** 1 **FINAL POS.** 1

FRONT	DRIVE TRAIN	REAR
<input type="checkbox"/> GEAR DIFF	cst	<input checked="" type="checkbox"/> GEAR DIFF 10k cst
<input checked="" type="checkbox"/> SPOOL		

FLEX CONFIGURATION		
CHASSIS	STIFFENERS	TOP DECK
<input checked="" type="checkbox"/> STD <input type="checkbox"/> FLEX	<input checked="" type="checkbox"/> FRONT <input checked="" type="checkbox"/> REAR	<input checked="" type="checkbox"/> NONE <input type="checkbox"/> mm

FRONT	HEAVE DAMPER	REAR
OIL 3000 cst		OIL 3000 cst
SPRINGS yellow		SPRINGS orange
<input type="checkbox"/> <input type="checkbox"/> <input checked="" type="checkbox"/>		<input type="checkbox"/> <input type="checkbox"/> <input checked="" type="checkbox"/>
N HOLES 2 Ø mm		N HOLES 2 Ø mm

FRONT	ROLL DAMPER	REAR
OIL 2500 cst		OIL 2500 cst
SPRINGS red		SPRINGS green
<input type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/>		<input type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/>
N HOLES 1 Ø mm		N HOLES 1 Ø mm

FRONT	TYRES	Controlled Tyre	REAR
Volante ETS	MAKE AND TYPE		Volante ETS
	INSERTS		
mighty gripper yellow	ADDITIVE		mighty gripper yellow
5min	ADDITIVE TIMING		5min

ELECTRONICS	
BATTERY	
BRAND Gens Ace	CAPACITY 6500 mAh
MOTOR	
BRAND Arrowmax	TYPE 4.5t TIMING
ESC	
BRAND Arrowmax	TYPE prototype

RATIO CONFIGURATION	
64	PITCH SPUR GEAR TEETH 112
64	PITCH PINION TEETH 30
FINAL DRIVE RATIO 7.46	ROLL OUT mm

AERODYNAMIC CONFIGURATION	
BODY BRAND PF	
BODY TYPE LTC-r LW	
BODY POSITION 10mm	

REMARKS

FRONT	REAR
PULLROD LENGTH 14.5mm	PULLROD LENGTH 15.5mm
WHEEL HEX -0.75mm	WHEEL HEX -0.75mm
ROLL CENTER SHIMS 3mm	ROLL CENTER SHIMS 3mm
DOWN STOP 1.0mm	DOWN STOP 0.5mm

FRONT	REAR
UPPER ARM INSERT	UPPER ARM INSERT
FRONT CAMBER R 2.0° L 2.0°	REAR CAMBER R 2.0° L 2.0°
RIDE HEIGHT 5.0mm WITH TYRE Ø	RIDE HEIGHT 5.2mm WITH TYRE Ø

FRONT	REAR
CASTER 3mm	SPACERS 6mm
FRONT TOE 1.0°	REAR TOE 2.25°
OUTER ACKERMANN	INNER ACKERMANN
	REAR REACTIVE SYSTEM
	SHIMS 0mm
	SHIMS 2.5mm

FRONT	REAR
WHEEL BASE 0 1 <input checked="" type="checkbox"/> 2 3 4	WHEEL BASE 0 1 2 <input checked="" type="checkbox"/> 3 4
SHIMS 2mm	
ROLL CENTER BOTTOM INSERTS MID LOW <input checked="" type="checkbox"/> MID HIGH HIGH	ROLL CENTER BOTTOM INSERTS MID LOW <input checked="" type="checkbox"/> MID HIGH HIGH

WEIGHT DISTRIBUTION	
CAR WEIGHT 1370 grams	
BATTERY POS. <input checked="" type="checkbox"/> FR <input type="checkbox"/> MID <input type="checkbox"/> RR	
TRACK WIDTH 187.5mm	TRACK WIDTH 187mm