

## DRIVER, TRACK AND RESULTS

DRIVER	Mark Green	COUNTRY	UK	WEATHER	AIR TEMP	TRACK TEMP	<input type="checkbox"/> DRY <input type="checkbox"/> INTERMEDIATE <input type="checkbox"/> WET
TRACK	Cassino	TRACTION	<input type="checkbox"/> LOW <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH	COMMENTS			
RACE	EFRA GP R1	DATE		QUALY POS.	15	QUALY TIME	
STARTING POS.		FINAL POS.					

1ST SPUR GEARS		2ND	
<input type="checkbox"/> 61	<input type="checkbox"/> 62	<input checked="" type="checkbox"/> 63	<input checked="" type="checkbox"/> 56
<input type="checkbox"/> 57	<input type="checkbox"/> 58		

1ST PINION		2ND	
<input type="checkbox"/> 18	<input checked="" type="checkbox"/> 19	<input type="checkbox"/> 20	<input checked="" type="checkbox"/> 23
<input type="checkbox"/> 24	<input type="checkbox"/> 25		

FRONT SHOCK ABSORBERS		REAR	
AE 800	cst	AE 800	cst
Green	SPRINGS	Pink	
mm REBOUND		mm	
<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>

FRONT ANTI-ROLL BARS		REAR	
<input type="checkbox"/> SOFT <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HARD	<input type="checkbox"/> SOFT <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HARD		

FRONT TYRES		REAR	
Matrix	MAKE	Matrix	
35	SHORE	32	
69	DIAMETER	76	
5-MIN WEAR			

POWER PACK	
BRAND	XRD
TYPE	FT Line
GLOWPLUG	xrd7
CARBØ	8.5 mm
HEAD CLEARANCE	0.5mm
EXAUSHT	
PIPE	XRD 2068
MANIFOLD	xrrd6
FUEL	
BRAND	Runnertime TOP
NITRO	16%

CLUTCH	
CLUTCH BELL	<input checked="" type="checkbox"/> ALU <input type="checkbox"/> STEEL
CLUTCH SHOE	<input type="checkbox"/> RED <input checked="" type="checkbox"/> YELLOW <input type="checkbox"/> BLACK
CLUTCH SPRING	X hard
CLUTCH BELL GAP	0.6 mm

FLEX CONFIGURATION	
FRONT STIFFENER	<input checked="" type="checkbox"/> YES <input type="checkbox"/> NO
FLEX	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO
REAR CONNECTORS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

AERODYNAMIC CONFIGURATION	
BODY BRAND	PF
BODY TYPE	R18
BUMPER INSERTS	<input checked="" type="checkbox"/> YES <input type="checkbox"/> NO
AIR TRIM POSITION	9 mm

FRONT		REAR	
AERO DISKS <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	SHOCK POSITION	CAMBERLINK SHOCK POSITION	SHIMS 0 mm
OFFSET 0.50 mm	DOWN STOP 1 mm	UPPER ARM INSERT	DOWN STOP 8 mm
FRONT CAMBER R 2 L 2	ROLL CENTER INSERT	REAR CAMBER R 2.52 L 2.0	ROLL CENTER INSERT
RIDE HEIGHT 8 mm	WITH TYRE Ø 69 mm	RIDE HEIGHT 9 mm	WITH TYRE Ø 76 mm
SHOCK BRACKET WIDE <input type="checkbox"/> NARROW <input checked="" type="checkbox"/>	SUSPENSION BRACKET NARROW <input type="checkbox"/> WIDE <input checked="" type="checkbox"/>		
CASTER 3 mm	WHEEL BASE 0 <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2 <input type="checkbox"/> 3		
FRONT TOE +5.0	REAR TOE 2.5		
ROLL CENTER FR 1 mm RR 1 mm	SHIMS 3 mm		
INSERT POSITION	KINGPIN SHIMS 1 mm		
WHEEL BASE 0 <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2 <input type="checkbox"/> 3	TRACKROD POSITION		
ACKERMANN INSERTS FORWARD MID REARWARD			
TRACK WIDTH 254 mm	WEIGHT POSITION	WEIGHT POSITION	TRACK WIDTH 262 mm
TOTAL CAR WEIGHT 2420 grams	grams	grams	

REMARKS

Alu wheel axles-Alu servo saver