

DRIVER, TRACK AND RESULTS

DRIVER	Viktor Wilck	COUNTRY	Sweden	WEATHER	AIR TEMP 25	TRACK TEMP 25	<input checked="" type="checkbox"/> DRY	<input type="checkbox"/> INTERMEDIATE	<input type="checkbox"/> WET
TRACK	ETS Madrid	SURFACE	<input checked="" type="checkbox"/> ASPHALT <input type="checkbox"/> CARPET	TRACTION	<input checked="" type="checkbox"/> LOW <input type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH	COMMENTS			
RACE	ETS Madrid	DATE	09-04-2017	QUALY POS.		QUALY TIME		STARTING POS.	
FINAL POS.									

FRONT	DRIVE TRAIN	REAR
<input type="checkbox"/> GEAR DIFF	cst	<input checked="" type="checkbox"/> GEAR DIFF 10.000 cst
<input checked="" type="checkbox"/> SPOOL		

FLEX CONFIGURATION		
CHASSIS	STIFFENERS	TOP DECK
<input checked="" type="checkbox"/> STD <input type="checkbox"/> FLEX	<input checked="" type="checkbox"/> FRONT <input checked="" type="checkbox"/> REAR	<input type="checkbox"/> NONE <input checked="" type="checkbox"/> mm

FRONT	HEAVE DAMPER	REAR
OIL 3000 cst		OIL 3000 cst
SPRINGS orange		SPRINGS orange
<input type="checkbox"/> <input type="checkbox"/> <input checked="" type="checkbox"/>		<input type="checkbox"/> <input type="checkbox"/> <input checked="" type="checkbox"/>
N HOLES 2 Ø mm		N HOLES 2 Ø mm

FRONT	ROLL DAMPER	REAR
OIL 3000 cst		OIL 3000 cst
SPRINGS red		SPRINGS pink
<input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>		<input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>
N HOLES 0 Ø mm		N HOLES 0 Ø mm

FRONT	TYRES	Controlled Tyre	REAR
ETS Volante	MAKE AND TYPE		ETS Volante
INSERTS			
ADDITIVE			
ADDITIVE TIMING			

ELECTRONICS	
BATTERY	
BRAND Gens Ace	CAPACITY 6500 mAh
MOTOR	
BRAND Arrowmax	TYPE 4.5 TIMING std
ESC	
BRAND Arrowmax	TYPE proto

RATIO CONFIGURATION	
112	PITCH SPUR GEAR TEETH 64
30	PITCH PINION TEETH 64
FINAL DRIVE RATIO 7.46	ROLL OUT mm

AERODYNAMIC CONFIGURATION	
BODY BRAND PF	
BODY TYPE LTC-r LW	
BODY POSITION 10 mm	

REMARKS
New XH arms front & rear New top deck

FRONT	REAR
PULLROD LENGTH 14.5 mm	PULLROD LENGTH 15.5 mm
WHEEL HEX -0.75 mm	WHEEL HEX -0.75 mm
ROLL CENTER SHIMS 3 mm	ROLL CENTER SHIMS 3 mm
DOWN STOP 1 mm	DOWN STOP 0.5 mm
UPPER ARM INSERT	UPPER ARM INSERT
FRONT CAMBER R 2° L 2°	REAR CAMBER R 2° L 2°
RIDE HEIGHT WITH TYRE Ø 4.8 mm	RIDE HEIGHT WITH TYRE Ø 5.2 mm
CASTER 3 mm	SPACERS 6 mm
FRONT TOE 1.0°	REAR TOE 2.0°
OUTER ACKERMANN	INNER ACKERMANN
REAR REACTIVE SYSTEM	
SHIMS 0 mm	SHIMS 1.0 mm
WHEEL BASE 0 1 <input checked="" type="checkbox"/> 2 3 4	WHEEL BASE 0 1 2 <input checked="" type="checkbox"/> 3 4
SHIMS 0 mm	
ROLL CENTER BOTTOM INSERTS MID LOW <input checked="" type="checkbox"/> MID HIGH <input type="checkbox"/> HIGH <input type="checkbox"/>	ROLL CENTER BOTTOM INSERTS MID LOW <input checked="" type="checkbox"/> MID HIGH <input type="checkbox"/> HIGH <input type="checkbox"/>
WEIGHT DISTRIBUTION CAR WEIGHT 1390 grams	
BATTERY POS. <input type="checkbox"/> FR <input checked="" type="checkbox"/> MID <input type="checkbox"/> RR	
TRACK WIDTH 186 mm	TRACK WIDTH 184 mm