

DRIVER, TRACK AND RESULTS

DRIVER	Mark JGreen	COUNTRY	uk	WEATHER	AIR TEMP	TRACK TEMP	<input checked="" type="checkbox"/> DRY <input type="checkbox"/> INTERMEDIATE <input type="checkbox"/> WET
TRACK	Halifax	TRACTION	<input checked="" type="checkbox"/> LOW <input type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH	COMMENTS			
RACE	Brca	DATE		QUALY POS.	QUALY TIME	STARTING POS.	FINAL POS.

1ST	SPUR GEARS			2ND
<input checked="" type="checkbox"/> 61 <input type="checkbox"/> 62 <input type="checkbox"/> 63	<input checked="" type="checkbox"/> 56 <input type="checkbox"/> 57 <input type="checkbox"/> 58			

1ST	PINION			2ND
<input type="checkbox"/> 18 <input checked="" type="checkbox"/> 19 <input type="checkbox"/> 20	<input checked="" type="checkbox"/> 23 <input type="checkbox"/> 24 <input type="checkbox"/> 25			

FRONT	SHOCK ABSORBERS		REAR
AE 800	cst	OIL	AE 800
Green	SPRINGS		Pink
mm		REBOUND	mm
<input type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>		

FRONT	ANTI-ROLL BARS		REAR
<input type="checkbox"/> SOFT <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HARD	<input type="checkbox"/> SOFT <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HARD		

FRONT	TYRES		Controlled Tyre	REAR
Conact	MAKE	contact		
32	SHORE	35		
DIAMETER				
5-MIN WEAR				

POWER PACK			
ENGINE			
BRAND	XRD	TYPE	FT Line
GLOWPLUG	xrd7	CARBØ	8.5 mm
HEAD CLEARANCE	std mm		
EXAUSHT			
PIPE	Xrd 2068	MANIFOLD	xrd5
FUEL			
BRAND	Runnertime	NITRO	16%

CLUTCH	
CLUTCH BELL <input checked="" type="checkbox"/> ALU <input type="checkbox"/> STEEL	CLUTCH SHOE <input type="checkbox"/> RED <input checked="" type="checkbox"/> YELLOW <input type="checkbox"/> BLACK
CLUTCH SPRING Xhard	CLUTCH BELL GAP mm

FLEX CONFIGURATION		
FRONT STIFFENER	FLEX	REAR CONNECTORS
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

AERODYNAMIC CONFIGURATION	
BODY BRAND	PF
BODY TYPE	R18
BUMPER INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO
AIR TRIM POSITION	9 mm

FRONT	REAR
AERO DISKS <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	AERO DISKS <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO
SHOCK POSITION	CAMBERLINK POSITION
SHIMS 0 mm	SHIMS 0 mm
OFFSET 0.25 mm	OFFSET 0.25 mm
DOWN STOP +1 mm	DOWN STOP 7 mm
UPPER ARM INSERT	ROLL CENTER INSERT

FRONT	REAR
FRONT CAMBER	REAR CAMBER
R 2 °	R 2 °
L 2 °	L 2.5 °
RIDE HEIGHT 8 mm WITH TYRE Ø	RIDE HEIGHT 9 mm WITH TYRE Ø

SHOCK BRACKET	SUSPENSION BRACKET
WIDE <input type="checkbox"/> NARROW <input checked="" type="checkbox"/>	NARROW <input checked="" type="checkbox"/> WIDE <input type="checkbox"/>

CASTER 3 mm	WHEEL BASE 0 <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2 <input type="checkbox"/> 3
FRONT TOE +1 °	REAR TOE 2.5 °
ROLL CENTER SHIMS	
FR 1 mm	RR 1 mm

SHIMS 3 mm	INSERT POSITION	KINGPIN SHIMS 1 mm	ACKERMANN INSERTS
			FORWARD
			MID
			REARWARD
WHEEL BASE 0 <input type="checkbox"/> 1 <input type="checkbox"/> 2 <input checked="" type="checkbox"/> 3	TRACKROD POSITION		

TRACK WIDTH 254 mm	TRACK WIDTH 263 mm
TOTAL CAR WEIGHT 2405 grams	WEIGHT POSITION
	grams

REMARKS

Alloy servo saver - alu wheel axles -