

DRIVER, TRACK AND RESULTS

DRIVER	Merlin Depta	COUNTRY	Germany	WEATHER	AIR TEMP	TRACK TEMP	<input type="checkbox"/> DRY <input type="checkbox"/> INTERMEDIATE <input type="checkbox"/> WET
TRACK	Mulhouse	TRACTION	<input type="checkbox"/> LOW <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH	COMMENTS			
RACE	ENS Rd1	DATE	21.05.17	QUALY POS.	16	QUALY TIME	
						STARTING POS.	9
						FINAL POS.	9

1ST SPUR GEARS		2ND	
<input type="checkbox"/> 61	<input checked="" type="checkbox"/> 62	<input type="checkbox"/> 63	
<input type="checkbox"/> 56	<input checked="" type="checkbox"/> 57	<input type="checkbox"/> 58	

1ST PINION		2ND	
<input type="checkbox"/> 18	<input checked="" type="checkbox"/> 19	<input type="checkbox"/> 20	
<input type="checkbox"/> 23	<input checked="" type="checkbox"/> 24	<input type="checkbox"/> 25	

FRONT SHOCK ABSORBERS		REAR	
800	cst	800	cst
purple	SPRINGS	pink	
3	mm	3	mm
<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>

FRONT ANTI-ROLL BARS		REAR	
<input type="checkbox"/> SOFT <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HARD		<input type="checkbox"/> SOFT <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/> HARD	

FRONT TYRES		REAR	
Matrix	MAKE	Matrix	
32	SHORE	35	
69	DIAMETER	76	
5-MIN WEAR			

POWER PACK			
ENGINE			
BRAND	O.S. Speed	TYPE	R2102
GLOWPLUG	7	CARBØ	8,5 mm
HEAD CLEARANCE 0,65 mm			
EXHAUST			
PIPE	2098	MANIFOLD	STD
FUEL			
BRAND	RunnerTime	NITRO	16%

CLUTCH			
CLUTCH BELL	<input checked="" type="checkbox"/> ALU <input type="checkbox"/> STEEL	CLUTCH SHOE	<input type="checkbox"/> RED <input checked="" type="checkbox"/> YELLOW <input type="checkbox"/> BLACK
CLUTCH SPRING X-HARD		CLUTCH BELL GAP 0,6 mm	

FLEX CONFIGURATION			
FRONT STIFFENER	FLEX	REAR CONNECTORS	
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	<input checked="" type="checkbox"/> YES <input type="checkbox"/> NO	

AERODYNAMIC CONFIGURATION	
BODY BRAND	BLITZ
BODY TYPE	TS0040
BUMPER INSERTS	<input checked="" type="checkbox"/> YES <input type="checkbox"/> NO
AIR TRIM POSITION	5 mm

FRONT		REAR	
AERO DISKS <input checked="" type="checkbox"/> YES <input type="checkbox"/> NO	SHOCK POSITION	CAMBERLINK SHOCK POSITION	SHIMS 3 mm
OFFSET 1,2 mm		DOWN STOP 1 mm	UPPER ARM INSERT
		ROLL CENTER INSERT	FRONT REAR
FRONT CAMBER R 1,5 L 2,0		REAR CAMBER R 2,5 L 3,0	
RIDE HEIGHT 8 mm	WITH TYRE Ø 69 mm	RIDE HEIGHT 9 mm	WITH TYRE Ø 76 mm
SHOCK BRACKET WIDE <input type="checkbox"/> NARROW <input checked="" type="checkbox"/>	SUSPENSION BRACKET NARROW <input type="checkbox"/> WIDE <input checked="" type="checkbox"/>		
CASTER 6 mm	WHEEL BASE 0 <input type="checkbox"/> 1 <input checked="" type="checkbox"/> 2 <input type="checkbox"/> 3		
FRONT TOE +1°		REAR TOE 3,0°	
ROLL CENTER SHIMS FR 0 mm RR 0 mm			
SHIMS 0 mm	INSERT POSITION	KINGPIN SHIMS 1 mm	ACKERMANN INSERTS FORWARD MID REARWARD
WHEEL BASE 0 <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2 <input type="checkbox"/> 3	TRACKROD POSITION		
TRACK WIDTH 251 mm		TRACK WIDTH 261 mm	
TOTAL CAR WEIGHT 2410 grams	WEIGHT POSITION	WEIGHT POSITION	

REMARKS