

DRIVER, TRACK AND RESULTS

DRIVER	Felix Law	COUNTRY	USA	WEATHER	AIR TEMP	TRACK TEMP	<input checked="" type="checkbox"/> DRY <input type="checkbox"/> INTERMEDIATE <input type="checkbox"/> WET
TRACK	Revolution RC	SURFACE	<input checked="" type="checkbox"/> ASPHALT <input type="checkbox"/> CARPET	TRACTION	<input type="checkbox"/> LOW <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH	COMMENTS	
RACE	Roar Regional	DATE	06/11/17	QUALY POS.	TQ	QUALY TIME	STARTING POS. 1 FINAL POS. 1

FRONT	DRIVE TRAIN	REAR
<input type="checkbox"/> GEAR DIFF	cst	<input type="checkbox"/> GEAR DIFF
<input checked="" type="checkbox"/> SPOOL		8000 cst

FLEX CONFIGURATION		
CHASSIS	STIFFENERS	TOP DECK
<input checked="" type="checkbox"/> STD <input type="checkbox"/> FLEX	<input checked="" type="checkbox"/> FRONT <input type="checkbox"/> REAR	<input checked="" type="checkbox"/> NONE <input type="checkbox"/> mm

FRONT	HEAVE DAMPER	REAR
OIL	2500 cst	OIL
SPRINGS	5.5	1500 cst
SPRINGS	5.5	5.5
<input type="checkbox"/> <input type="checkbox"/> <input checked="" type="checkbox"/>		<input type="checkbox"/> <input type="checkbox"/> <input checked="" type="checkbox"/>
N HOLES	Ø mm	N HOLES
		Ø mm

FRONT	ROLL DAMPER	REAR
OIL	10,000 cst	OIL
SPRINGS	8.4	12,000 cst
SPRINGS	8.4	9.2
<input type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/>		<input type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/>
N HOLES	Ø mm	N HOLES
		Ø mm

FRONT	TYRES	Controlled Tyre	REAR
Sweep 32 QTS	MAKE AND TYPE	<input checked="" type="checkbox"/>	Sweep 32 QTS
INSERTS			
Red v3	ADDITIVE		Red v3
5min	ADDITIVE TIMING		5min

ELECTRONICS	
BATTERY	
BRAND	Arrowmax
CAPACITY	7800 mAh
MOTOR	
BRAND	Motiv
TYPE	17.5
TIMING	42
ESC	
BRAND	HW
TYPE	XR10

RATIO CONFIGURATION	
64	PITCH SPUR GEAR TEETH
90	
64	PITCH PINION TEETH
42	
FINAL DRIVE RATIO	4.285
ROLL OUT	mm

AERODYNAMIC CONFIGURATION	
BODY BRAND	Protoform
BODY TYPE	LTCR
BODY POSITION	10 mm

REMARKS
- Gear Diff range between 5000 - 8000 depend on traction - Optional Parts were use at this event: • 401738- Vertical topdeck set 4X • 401742- Linear suspension set 4X • 401744- Spool outrdrive 4X-411 no-blade (2) • 401747- RRS Links Short (2) 4X • 401712- Spring green C9.5 4-X (2) • 401736- Wishbone upper frtr hard 4X (2) • 401735- Wishbone lower frtr hard 4X (2)

FRONT	REAR
PULLROD LENGTH	0 mm
ROLL CENTER SHIMS	3.5 mm
WHEEL HEX	4 mm
DOWN STOP	2.5 mm
UPPER ARM INSERT	
FRONT CAMBER	
R 2°	
L 2°	
RIDE HEIGHT	5.0 mm
WITH TYRE Ø	62 mm
CASTER	3 mm
FRONT TOE	1.5°
OUTER ACKERMANN	
INNER ACKERMANN	
REAR CAMBER	
R 2°	
L 2°	
RIDE HEIGHT	5.2 mm
WITH TYRE Ø	62 mm
SPACERS	5 mm
REAR TOE	2.5°
REAR REACTIVE SYSTEM	
SHIMS	0 mm
SHIMS	2 mm
WHEEL BASE	0 1 2 3 4
SHIMS	1 mm
ROLL CENTER BOTTOM INSERTS	
MID LOW MID HIGH HIGH	
WHEEL BASE	0 1 2 3 4
SHIMS	1 mm
ROLL CENTER BOTTOM INSERTS	
MID LOW MID HIGH HIGH	
WEIGHT DISTRIBUTION	
CAR WEIGHT	1368 grams
BATTERY POS.	<input checked="" type="checkbox"/> FR <input type="checkbox"/> MID <input type="checkbox"/> RR
TRACK WIDTH	185 mm
TRACK WIDTH	184 mm