

DRIVER, TRACK AND RESULTS

DRIVER	Viktor Wilck	COUNTRY	Sweden	WEATHER	AIR TEMP	20	TRACK TEMP	25	<input checked="" type="checkbox"/> DRY	<input type="checkbox"/> INTERMEDIATE	<input type="checkbox"/> WET
TRACK	Hudy Arena	SURFACE	<input checked="" type="checkbox"/> ASPHALT <input type="checkbox"/> CARPET	TRACTION	<input type="checkbox"/> LOW <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH	COMMENTS low too medium					
RACE	ETS rd5	DATE	2017-06-19	QUALY POS.	13	QUALY TIME	-	STARTING POS.	FINAL POS.		

FRONT	DRIVE TRAIN	REAR
<input type="checkbox"/> GEAR DIFF	cst	<input checked="" type="checkbox"/> GEAR DIFF 5000 cst
<input checked="" type="checkbox"/> SPOOL		

FLEX CONFIGURATION		
CHASSIS	STIFFENERS	TOP DECK
<input checked="" type="checkbox"/> STD <input type="checkbox"/> FLEX	<input type="checkbox"/> FRONT <input type="checkbox"/> REAR	<input type="checkbox"/> NONE <input checked="" type="checkbox"/> 3mm

FRONT	HEAVE DAMPER	REAR
OIL 2500 cst		OIL 2000 cst
SPRINGS orange		SPRINGS orange
<input type="checkbox"/> <input type="checkbox"/> <input checked="" type="checkbox"/>		<input type="checkbox"/> <input type="checkbox"/> <input checked="" type="checkbox"/>
N HOLES 2 Ø mm		N HOLES 2 Ø mm

FRONT	ROLL DAMPER	REAR
OIL 1500 cst		OIL 2500 cst
SPRINGS red		SPRINGS pink
<input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>		<input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>
N HOLES 0 Ø mm		N HOLES 0 Ø mm

FRONT	TYRES	REAR
Controlled Tyre		
Volante ETS	MAKE AND TYPE	Volante ETS
	INSERTS	
	ADDITIVE	
10min	ADDITIVE TIMING	10min

ELECTRONICS	
BATTERY	
BRAND Gens Ace LCG	CAPACITY 5500 mAh
MOTOR	
BRAND Arrowmax	TYPE 4.5 TIMING
ESC	
BRAND Arrowmax	TYPE prototype

RATIO CONFIGURATION	
64	PITCH SPUR GEAR TEETH 112
64	PITCH PINION TEETH 30
FINAL DRIVE RATIO 7.46	ROLL OUT mm

AERODYNAMIC CONFIGURATION	
BODY BRAND Protoform	
BODY TYPE LTC-r LW	
BODY POSITION 10mm	

REMARKS
- XH arms - new top deck - new short push rods

FRONT	REAR
PULLROD LENGTH short mm	PULLROD LENGTH short mm
WHEEL HEX -0.75 mm	WHEEL HEX -0.75 mm
ROLL CENTER SHIMS 3 mm	ROLL CENTER SHIMS 2 mm
DOWN STOP 1.0 mm	DOWN STOP 0 mm

FRONT	REAR
UPPER ARM INSERT	UPPER ARM INSERT
FRONT CAMBER R 2° L 2°	REAR CAMBER R 2° L 2°
RISE HEIGHT 5.0 mm WITH TYRE Ø	RISE HEIGHT 5.4 mm WITH TYRE Ø

FRONT	REAR
CASTER 3 mm	SPACERS 6 mm
FRONT TOE 1°	REAR TOE 2.5°
OUTER ACKERMANN	INNER ACKERMANN
	REAR REACTIVE SYSTEM
	SHIMS 0 mm
	SHIMS 2 mm

FRONT	REAR
WHEEL BASE 0 1 <input checked="" type="checkbox"/> 2 3 4	WHEEL BASE 0 1 2 <input checked="" type="checkbox"/> 3 4
SHIMS 0 mm	
ROLL CENTER BOTTOM INSERTS MID LOW <input checked="" type="checkbox"/> MID HIGH HIGH	ROLL CENTER BOTTOM INSERTS MID LOW <input checked="" type="checkbox"/> MID HIGH HIGH

WEIGHT DISTRIBUTION	
CAR WEIGHT 1355 grams	
BATTERY POS. <input checked="" type="checkbox"/> FR <input type="checkbox"/> MID <input type="checkbox"/> RR	
TRACK WIDTH 185.5 mm	TRACK WIDTH 184 mm