

DRIVER, TRACK AND RESULTS

DRIVER	StickKing	COUNTRY	China	WEATHER	AIR TEMP	43	TRACK TEMP	70	<input checked="" type="checkbox"/> DRY	<input type="checkbox"/> INTERMEDIATE	<input type="checkbox"/> WET	
TRACK	SURFACE <input checked="" type="checkbox"/> ASPHALT <input type="checkbox"/> CARPET TRACTION <input type="checkbox"/> LOW <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH COMMENTS											
RACE	China National 2017	DATE	8/25-8/26	QUALY POS.	1	QUALY TIME			STARTING POS.	1	FINAL POS.	4

FRONT	DRIVE TRAIN	REAR
<input type="checkbox"/> GEAR DIFF	cst	<input checked="" type="checkbox"/> GEAR DIFF
<input checked="" type="checkbox"/> SPOOL		10,000
	cst	

FLEX CONFIGURATION	
CHASSIS	TOP DECK
<input checked="" type="checkbox"/> CARBON 2.25mm <input type="checkbox"/> ALU 2mm <input type="checkbox"/> CARBON 2mm	<input type="checkbox"/> 1.75mm <input checked="" type="checkbox"/> 2mm <input type="checkbox"/> 2.5mm

FRONT	SHOCK ABSORBERS	REAR
LRP 45	cst	LRP 45
AXON 2.6	SPRINGS	AXON 2.6
0	mm	0
REBOUND		REBOUND
0	mm	0
<input type="checkbox"/> <input type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>		<input type="checkbox"/> <input type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>

FRONT	ANTI-ROLL BARS	REAR
<input type="checkbox"/> 1.2	<input checked="" type="checkbox"/> 1.4	<input type="checkbox"/> 1.2
<input type="checkbox"/> 1.6	<input type="checkbox"/> 1.8	<input checked="" type="checkbox"/> 1.4
<input type="checkbox"/> 1.6	<input type="checkbox"/> 1.8	<input type="checkbox"/> 1.6
<input type="checkbox"/> 1.8	<input type="checkbox"/> 1.8	<input type="checkbox"/> 1.8

FRONT	TYRES	REAR
RUSH 40x	MAKE AND TYPE	RUSH 40x
039M	INSERTS	039M
Spider RED	ADDITIVE	Spider RED
ADDITIVE TIMING		

ELECTRONICS	
BATTERY	
BRAND	scorpion
CAPACITY	6200 mAh
MOTOR	
BRAND	Scorpion
TYPE	4.5
TIMING	stock
ESC	
BRAND	Scorpion
TYPE	160amp

RATIO CONFIGURATION	
64	PITCH SPUR GEAR TEETH
112	
64	PITCH PINION TEETH
31	
FINAL DRIVE RATIO	7.22
ROLL OUT	mm

AERODYNAMIC CONFIGURATION	
BODY BRAND	Lex
BODY TYPE	
BODY POSITION	10 mm

REMARKS
- Bump Steering - 4mm - RRS on steering Block - 1mm - RRS Bump in 0.5 - RRS Castor 2 degree - Yellow Shock piston 160150 - No Post on Motor Mount

FRONT	REAR
SHIMS 0 mm	SHIMS 4 mm
SHOCK POSITION	SHOCK POSITION
WHEEL HEX stock mm	WHEEL HEX stock mm
DOWN STOP 8.5 mm	DOWN STOP 7.5 mm

FRONT CAMBER	REAR CAMBER
R 1.5 °	R 2.0 °
L 1.5 °	L 2.0 °
5 mm	5.5 mm
WITH TYRE Ø	WITH TYRE Ø

FRONT TOE	REAR TOE
0 °	2.5 °
WHEELBASE 3 mm	WHEELBASE 2 mm
OUTER ACKERMANN	ROLL CENTER
ROLL CENTER	OUTER 1 CAMBERLINK

STEERING BLOCK & C-HUBS	INNER ACKERMANN	REAR REACTIVE SYSTEM
STEERING BLOCK	SHIMS 1 mm	<input type="checkbox"/> NO <input checked="" type="checkbox"/> YES
<input checked="" type="checkbox"/> STOCK		SHIMS 1 mm
<input type="checkbox"/> ALU		
C-HUBS		
<input type="checkbox"/> STOCK		
<input checked="" type="checkbox"/> ALU		
<input type="checkbox"/> 2° <input checked="" type="checkbox"/> 4° <input type="checkbox"/> 6°		

FR FR SUSP. BRACKET	FR RR SUSP. BRACKET	RR RR SUSP. BRACKET
TYPE	TYPE	TYPE
<input type="checkbox"/> SOLID <input checked="" type="checkbox"/> SPLIT	<input type="checkbox"/> SOLID <input checked="" type="checkbox"/> SPLIT	<input type="checkbox"/> SOLID <input checked="" type="checkbox"/> SPLIT
STD 0.5	STD 0	STD 0
SPLIT L SHAPE N°	SPLIT L SHAPE N°	SPLIT L SHAPE N°
SPACER 185.5 mm	SPACER 185.5 mm	SPACER 0 mm
WEIGHT DISTRIBUTION CAR WEIGHT 1365 grams BATTERY POS. <input checked="" type="checkbox"/> FR <input type="checkbox"/> MID <input type="checkbox"/> RR		
TRACK WIDTH 185.5 mm	TRACK WIDTH 185.5 mm	TRACK WIDTH 185.5 mm