

DRIVER, TRACK AND RESULTS

DRIVER	Felix Law	COUNTRY	China	WEATHER	AIR TEMP	45	TRACK TEMP	70	<input checked="" type="checkbox"/> DRY	<input type="checkbox"/> INTERMEDIATE	<input type="checkbox"/> WET
TRACK	FS Raceway	TRACTION	<input type="checkbox"/> LOW <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH	COMMENTS							
RACE	China National	DATE	8/25- 8/26	QUALY POS.	5	QUALY TIME			STARTING POS.		
				FINAL POS.	3						

1ST SPUR GEARS		2ND	
<input type="checkbox"/> 61	<input checked="" type="checkbox"/> 62	<input type="checkbox"/> 63	<input checked="" type="checkbox"/> 56
<input type="checkbox"/> 57	<input type="checkbox"/> 58		

1ST PINION		2ND	
<input type="checkbox"/> 18	<input checked="" type="checkbox"/> 19	<input type="checkbox"/> 20	<input checked="" type="checkbox"/> 23
<input type="checkbox"/> 24	<input type="checkbox"/> 25		

FRONT SHOCK ABSORBERS		REAR	
LRP 60	cst	OIL	700
Purple	SPRINGS	Red	
mm REBOUND		mm	
<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>

FRONT ANTI-ROLL BARS		REAR	
<input type="checkbox"/> SOFT <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HARD	<input type="checkbox"/> SOFT <input type="checkbox"/> MEDIUM <input checked="" type="checkbox"/> HARD		

FRONT TYRES		REAR	
Arrowmax	MAKE	Arrowmax	
30	SHORE	35	
69	DIAMETER	75	
5-MIN WEAR			

POWER PACK	
ENGINE	
BRAND	REDS
GLowPLUG	TS7
CARBØ	mm
HEAD CLEARANCE	mm
EXAUSHT	
PIPE	2113
MANIFOLD	L
FUEL	
BRAND	Running Time
NITRO	25

CLUTCH	
CLUTCH BELL	<input checked="" type="checkbox"/> ALU <input type="checkbox"/> STEEL
CLUTCH SHOE	<input type="checkbox"/> RED <input checked="" type="checkbox"/> YELLOW <input type="checkbox"/> BLACK
CLUTCH SPRING	XRD
CLUTCH BELL GAP	0.6 mm

FLEX CONFIGURATION	
FRONT STIFFENER	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO
FLEX	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO
REAR CONNECTORS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

AERODYNAMIC CONFIGURATION	
BODY BRAND	PF
BODY TYPE	R18
BUMPER INSERTS	<input checked="" type="checkbox"/> YES <input type="checkbox"/> NO
AIR TRIM POSITION	mm

FRONT		REAR	
AERO DISKS <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	SHOCK POSITION	CAMBERLINK SHOCK POSITION	SHIMS 1 mm
OFFSET mm		DOWN STOP 1 mm	UPPER ARM INSERT
		ROLL CENTER INSERT	FRONT
		REAR	
FRONT CAMBER	R -2	REAR CAMBER	R -3
L -2		L -3	
RIDE HEIGHT	7 mm	WITH TYRE Ø	69 mm
SHOCK BRACKET	WIDE <input type="checkbox"/> NARROW <input checked="" type="checkbox"/>	SUSPENSION BRACKET	NARROW <input checked="" type="checkbox"/> WIDE <input type="checkbox"/>
CASTER	4 mm	WHEEL BASE	0 <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2 <input type="checkbox"/> 3
FRONT TOE	2	REAR TOE	2.5
ROLL CENTER SHIMS	FR 1 mm	RR 1 mm	
SHIMS	1 mm	INSERT POSITION	
KINGPIN SHIMS	0 mm	ACKERMANN INSERTS	FORWARD
		MID	
		REARWARD	
WHEEL BASE	0 <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2 <input type="checkbox"/> 3	TRACKROD POSITION	
TRACK WIDTH	254 mm	WEIGHT POSITION	38 grams
TOTAL CAR WEIGHT	grams	WEIGHT POSITION	38 grams
TRACK WIDTH	264 mm		

REMARKS