

DRIVER, TRACK AND RESULTS

DRIVER	default	COUNTRY		WEATHER	AIR TEMP	TRACK TEMP	<input type="checkbox"/> DRY <input type="checkbox"/> INTERMEDIATE <input type="checkbox"/> WET
TRACK	TRACTION <input type="checkbox"/> LOW <input type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH COMMENTS						
RACE	DATE	QUALY POS.	QUALY TIME	STARTING POS.	FINAL POS.		

1ST SPUR GEARS		2ND	
<input type="checkbox"/> 61	<input type="checkbox"/> 62	<input checked="" type="checkbox"/> 63	<input type="checkbox"/> 56
<input type="checkbox"/> 57	<input checked="" type="checkbox"/> 58		

1ST PINION		2ND	
<input type="checkbox"/> 18	<input checked="" type="checkbox"/> 19	<input type="checkbox"/> 20	<input type="checkbox"/> 23
<input checked="" type="checkbox"/> 24	<input type="checkbox"/> 25		

FRONT SHOCK ABSORBERS		REAR	
900	cst	OIL	900
purple	SPRINGS	pink	
mm REBOUND		mm	
<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>

ANTI-ROLL BARS	
FRONT ANTI-ROLL BAR	hard
REAR ANTI-ROLL BAR	medium

FRONT TYRES		Controlled Tyre <input type="checkbox"/> REAR	
MAKE			
SHORE			
DIAMETER			
5-MIN WEAR			

POWER PACK	
ENGINE	
BRAND	TYPE
GLOWPLUG	CARBØ mm HEAD CLEARANCE mm
EXHAUST	
PIPE	MANIFOLD
FUEL	
BRAND	NITRO

CLUTCH	
CLUTCH BELL	<input type="checkbox"/> ALU <input checked="" type="checkbox"/> STEEL
CLUTCH SHOE	<input type="checkbox"/> RED <input checked="" type="checkbox"/> YELLOW <input type="checkbox"/> BLACK
CLUTCH SPRING	x-hard
CLUTCH BELL GAP	0.6 mm

FLEX CONFIGURATION		
FR WISHBONES INSERTS	RR WISHBONES INSERTS	FLEX
<input checked="" type="checkbox"/> PLASTIC <input type="checkbox"/> CARBON	<input checked="" type="checkbox"/> PLASTIC <input type="checkbox"/> CARBON	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

AERODYNAMIC CONFIGURATION	
BODY BRAND	BODY POSITION mm
BODY TYPE	
BUMPER INSERTS	
<input type="checkbox"/> OPEN <input type="checkbox"/> CLOSE	
AIR TRIM POSITION	mm

FRONT		REAR	
AERO DISKS <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	SHOCK POSITION	SHOCK CAMBERLINK POSITION	SHIMS 0 mm
OFFSET 0.55 mm		DOWN STOP 2 mm	UPPER ARM INSERT
		ROLL CENTER INSERT	FRONT REAR
FRONT CAMBER R -1.5 L -1.5		REAR CAMBER R -2.5 L -2.5	
RIDE HEIGHT 7 mm	WITH TYRE Ø 67 mm	RIDE HEIGHT 9 mm	WITH TYRE Ø 74 mm
SHOCK BRACKET WIDE <input checked="" type="checkbox"/> NARROW	SUSPENSION BRACKET NARROW <input checked="" type="checkbox"/> WIDE		
CASTER 2 mm	WHEEL BASE 0 <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2		
FRONT TOE -1.0		REAR TOE 2.5	
ROLL CENTER SHIMS FR 1 mm RR 1 mm			
SHIMS 0 mm	INSERT POSITION	KINGPIN SHIMS 1 mm	ACKERMANN INSERTS FORWARD MID REARWARD
WHEEL BASE 0 <input type="checkbox"/> 1 <input type="checkbox"/> 2 <input checked="" type="checkbox"/> 3	TRACKROD POSITION		
TRACK WIDTH 252 mm		TRACK WIDTH 264 mm	
TOTAL CAR WEIGHT	grams	WEIGHT POSITION	grams

REMARKS