

DRIVER, TRACK AND RESULTS

DRIVER	Michael Salven	COUNTRY	Germany	WEATHER	AIR TEMP	22	TRACK TEMP	27	<input checked="" type="checkbox"/> DRY	<input type="checkbox"/> INTERMEDIATE	<input type="checkbox"/> WET
TRACK	Bad Breisig	TRACTION	<input type="checkbox"/> LOW <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH	COMMENTS							
RACE	German Nationals	DATE	27-08-2017	QUALY POS.	6	QUALY TIME		STARTING POS.	7	FINAL POS.	5

1ST SPUR GEARS		2ND	
<input type="checkbox"/> 61	<input type="checkbox"/> 62	<input checked="" type="checkbox"/> 63	
<input type="checkbox"/> 56	<input type="checkbox"/> 57	<input checked="" type="checkbox"/> 58	

1ST PINION		2ND	
<input type="checkbox"/> 18	<input checked="" type="checkbox"/> 19	<input type="checkbox"/> 20	
<input type="checkbox"/> 23	<input checked="" type="checkbox"/> 24	<input type="checkbox"/> 25	

FRONT SHOCK ABSORBERS		REAR	
900	cst	OIL	900
purple	SPRINGS	pink	
mm REBOUND		mm	
<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>

ANTI-ROLL BARS	
FRONT ANTI-ROLL BAR	soft
REAR ANTI-ROLL BAR	hard

FRONT TYRES		Controlled Tyre		REAR	
ARROWMAX	MAKE	ARROWMAX			
	SHORE				
	DIAMETER				
	5-MIN WEAR				

POWER PACK	
ENGINE	
BRAND	Picco
TYPE	WC
GLOWPLUG	7
CARBØ	9 mm
HEAD CLEARANCE	0.4 mm
EXHAUST	
PIPE	2016
MANIFOLD	regular
FUEL	
BRAND	RunnerTime
NITRO	16%

CLUTCH	
CLUTCH BELL	<input checked="" type="checkbox"/> ALU <input type="checkbox"/> STEEL
CLUTCH SHOE	<input type="checkbox"/> RED <input checked="" type="checkbox"/> YELLOW <input type="checkbox"/> BLACK
CLUTCH SPRING	x-hard
CLUTCH BELL GAP	0.6 mm

FLEX CONFIGURATION		
FR WISHBONES INSERTS	RR WISHBONES INSERTS	FLEX
<input type="checkbox"/> PLASTIC <input checked="" type="checkbox"/> CARBON	<input type="checkbox"/> PLASTIC <input checked="" type="checkbox"/> CARBON	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

AERODYNAMIC CONFIGURATION	
BODY BRAND	Blitz
BODY TYPE	040
BUMPER INSERTS	<input type="checkbox"/> OPEN <input checked="" type="checkbox"/> CLOSE
AIR TRIM POSITION	8 mm

FRONT		REAR	
AERO DISKS <input checked="" type="checkbox"/> YES <input type="checkbox"/> NO	SHOCK POSITION	SHOCK POSITION	CAMBERLINK POSITION
OFFSET 0.55 mm	DOWN STOP 1 mm	DOWN STOP 8 mm	SHIMS 1 mm
UPPER ARM INSERT	ROLL CENTER INSERT	ROLL CENTER INSERT	ROLL CENTER INSERT
FRONT CAMBER R -1.5° L -1.5°	REAR CAMBER R -2.5° L -2.0°	FRONT CAMBER	REAR CAMBER
RIDE HEIGHT 7 mm	WITH TYRE Ø 67 mm	RIDE HEIGHT 9 mm	WITH TYRE Ø 74 mm
SHOCK BRACKET WIDE <input type="checkbox"/> NARROW <input checked="" type="checkbox"/>	SUSPENSION BRACKET NARROW <input type="checkbox"/> WIDE <input checked="" type="checkbox"/>	CASTER 4 mm	WHEEL BASE 0 <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2
FRONT TOE -1.0°	REAR TOE 2.0°	ROLL CENTER SHIMS FR 1 mm RR 1 mm	SHIMS 0 mm
SHIMS 0 mm	INSERT POSITION	KINGPIN SHIMS 1 mm	ACKERMANN INSERTS FORWARD MID REARWARD
WHEEL BASE 0 <input type="checkbox"/> 1 <input checked="" type="checkbox"/> 2 <input type="checkbox"/> 3	TRACKROD POSITION	WHEEL BASE 0 <input type="checkbox"/> 1 <input checked="" type="checkbox"/> 2 <input type="checkbox"/> 3	
TRACK WIDTH 252 mm	WEIGHT POSITION	WEIGHT POSITION	TRACK WIDTH 264 mm
TOTAL CAR WEIGHT 2450 grams	grams	grams	36 grams

REMARKS