

## DRIVER, TRACK AND RESULTS

DRIVER	Viktor Wilck	COUNTRY	Sweden	WEATHER	AIR TEMP 25c	TRACK TEMP 45c	<input checked="" type="checkbox"/> DRY	<input type="checkbox"/> INTERMEDIATE	<input type="checkbox"/> WET
TRACK	GRC Korea	SURFACE	<input checked="" type="checkbox"/> ASPHALT <input type="checkbox"/> CARPET	TRACTION	<input type="checkbox"/> LOW <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH	COMMENTS			
RACE	AOC Korea	DATE	2017-09-10	QUALY POS.	4	QUALY TIME	STARTING POS. 4		FINAL POS. 4

FRONT	DRIVE TRAIN	REAR
<input type="checkbox"/> GEAR DIFF	cst	<input checked="" type="checkbox"/> GEAR DIFF 5000 cst
<input checked="" type="checkbox"/> SPOOL		

FLEX CONFIGURATION		
CHASSIS	STIFFENERS	TOP DECK
<input checked="" type="checkbox"/> STD <input type="checkbox"/> FLEX	<input type="checkbox"/> FRONT <input type="checkbox"/> REAR	<input type="checkbox"/> NONE <input checked="" type="checkbox"/> 3mmmm

FRONT	HEAVE DAMPER	REAR
OIL 2500 cst		OIL 1000 cst
SPRINGS orange		SPRINGS orange
<input type="checkbox"/> <input type="checkbox"/> <input checked="" type="checkbox"/>		<input type="checkbox"/> <input type="checkbox"/> <input checked="" type="checkbox"/>
N HOLES 2 Ø mm		N HOLES 2 Ø mm

FRONT	ROLL DAMPER	REAR
OIL 1500 cst		OIL 2500 cst
SPRINGS red		SPRINGS pink
<input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>		<input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>
N HOLES 0 Ø mm		N HOLES 0 Ø mm

FRONT	TYRES	Controlled Tyre	REAR
Sweep r30	MAKE AND TYPE		Sweep r30
Sweep	INSERTS		Sweep
mighty grip yellow	ADDITIVE		mighty grip yellow
10min	ADDITIVE TIMING		10min

ELECTRONICS	
BATTERY	
BRAND Arrowmax LCG	CAPACITY 5200 mAh
MOTOR	
BRAND DASH by AM	TYPE 4.5 TIMING 30
ESC	
BRAND DASH by AM	TYPE

RATIO CONFIGURATION	
64	PITCH SPUR GEAR TEETH 112
64	PITCH PINION TEETH 30
FINAL DRIVE RATIO 7.46	ROLL OUT mm

AERODYNAMIC CONFIGURATION	
BODY BRAND Protoform	
BODY TYPE Prototype PS7	
BODY POSITION 10mm	

REMARKS
- optional parallell top deck - optional short pullrods

FRONT	REAR
PULLROD LENGTH short optmm	PULLROD LENGTH short optmm
WHEEL HEX -0.75mm	WHEEL HEX -0.75 mm
ROLL CENTER SHIMS 3 mm	ROLL CENTER SHIMS 2 mm
DOWN STOP 1 mm	DOWN STOP 0 mm
FRONT CAMBER R 2° L 2°	REAR CAMBER R 2° L 2°
UPPER ARM INSERT	UPPER ARM INSERT
RISE HEIGHT WITH TYRE Ø 5.0 mm	RISE HEIGHT WITH TYRE Ø 5.4 mm
CASTER 3 mm	SPACERS 6 mm
FRONT TOE 0°	REAR TOE 2°
OUTER ACKERMANN	INNER ACKERMANN
REAR REACTIVE SYSTEM	
SHIMS 0 mm	SHIMS 1 mm
WHEEL BASE 0 1 <input checked="" type="checkbox"/> 2 3 4	WHEEL BASE 0 1 2 <input checked="" type="checkbox"/> 3 4
ROLL CENTER BOTTOM INSERTS MID LOW <input checked="" type="checkbox"/> MID HIGH HIGH	ROLL CENTER BOTTOM INSERTS MID LOW <input checked="" type="checkbox"/> MID HIGH HIGH
WEIGHT DISTRIBUTION	
CAR WEIGHT 1355 grams	
BATTERY POS. <input checked="" type="checkbox"/> FR <input type="checkbox"/> MID <input type="checkbox"/> RR	
TRACK WIDTH 185.5mm	TRACK WIDTH 184.5mm