

SET UP

Serpent Cobra GT 3.0

FR SHOCK ABSORBERS		RR	
OIL	1500 cst	OIL	1200 cst
SPRINGS	x-hard	SPRINGS	x-hard
PISTON N° HOLES	6 Ø 1.4mm	PISTON N° HOLES	6 Ø 1.4mm
TYPE	<input checked="" type="checkbox"/> FLAT <input type="checkbox"/> CONICAL	TYPE	<input checked="" type="checkbox"/> FLAT <input type="checkbox"/> CONICAL

FRONT ANTI-ROLL BARS										REAR				
<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>		
1.8	2.0	2.3	2.5	2.7	1.8	2.0	2.3	2.5	2.7					

DIFFERENTIAL OIL	
FRONT DIFF OIL	400k cst
REAR DIFF OIL	100k cst

1ST		SPUR		2ND	
<input type="checkbox"/>	61	<input type="checkbox"/>	62	<input checked="" type="checkbox"/>	63
<input type="checkbox"/>	62	<input checked="" type="checkbox"/>	56	<input type="checkbox"/>	57
<input type="checkbox"/>	58				

1ST		PINION		2ND	
<input type="checkbox"/>	18	<input checked="" type="checkbox"/>	19	<input type="checkbox"/>	20
<input type="checkbox"/>	20	<input checked="" type="checkbox"/>	23	<input type="checkbox"/>	24
<input type="checkbox"/>	25				

CLUTCH	
CLUTCHBELL	ALU <input type="checkbox"/> STEEL <input checked="" type="checkbox"/>
CLUTCH SHOES	CLUTCH SPRINGS
SHOE TYPE Alum x 2 with SPRING TYPE 1.0 mm	
SHOE TYPE x with SPRING TYPE mm	

FR TYRES		Controlled Tyre		RR	
Sweep	45	MAKE		Sweep	45
		TYPE			
		INSERTS			
		WHEELS			

ENGINE	
ENGINE	Picco EMX-GT
VERSION	GT1 HEADSHIMS 0.55 mm
GLOWPLUG	GSR GS7 CARB DIA 7.0 mm
PIPE	Picco 2046 MANIFOLD Nova 41032
FUEL	Runner Time NITRO 33 %

AERODYNAMIC CONFIGURATION	
BODY	
BRAND JZ Flow	TYPE JZ Flow
WING	
BRAND JZ Flow	
TYPE Stock	
BODY POSITION	

RACE	ROAR Nationals	DATE	10/1/17
TRACK	Lincoln	QUALIFYING POSITION	1st
DRIVER	Desoto Jr	QUALIFYING TIME	20 5:15
TRACTION: LOW <input type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH <input checked="" type="checkbox"/>	STARTING POSITION	1st	
TRACK TEMP 90	AIR TEMP 75	FINAL POSITION	2nd

FRONT		REAR	
WHEEL HEX -2 mm	CAMBERLINK POSITION	SHOCK POSITION	SHOCK POSITION
DOWNSTOP 24 mm		DOWNSTOP 24 mm	

FRONT CAMBER		REAR CAMBER	
R 1.5°	L 2.0°	R 2.5°	L 3.0°
RIDE HEIGHT 8 mm		RIDE HEIGHT 8 mm	

FRONT TOE		REAR TOE	
-1°		2°	
STEERING BAR			
OPT 1 <input checked="" type="checkbox"/> OPT 2 <input type="checkbox"/> OPT 3 <input type="checkbox"/>			

CASTER BLOCK		SERVO SAVER SPRING		WHEEL BASE	
0° <input type="checkbox"/> 6° <input type="checkbox"/> 10° <input checked="" type="checkbox"/> 12° <input type="checkbox"/>		STD <input type="checkbox"/> HARD <input checked="" type="checkbox"/>		0 <input type="checkbox"/> 1.25 <input type="checkbox"/> 2.5 <input checked="" type="checkbox"/> 3.75 <input type="checkbox"/> 5 <input type="checkbox"/>	
FRONT BRACE		REAR BRACE			
STOCK <input type="checkbox"/> ALU <input checked="" type="checkbox"/>		STOCK <input checked="" type="checkbox"/> ALU <input type="checkbox"/>			
FRONT FR TOE BLOCK		FRONT RR TOE BLOCK		REAR FR TOE BLOCK	
INSERT POS. UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/>		INSERT POS. UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/>		INSERT POS. UP <input type="checkbox"/> DOWN <input checked="" type="checkbox"/>	
TOE BLOCK TYPE 2		TOE BLOCK TYPE 2		TOE BLOCK TYPE 2	

REMARKS

Using 3.1 shock towers (600980/600981) and shock extensions (600982/600983)
 Rear bar 3.0mm
 Droop measured to bottom of hex
 Desoto Racing Aero bumper part#DES50005GT