

DRIVER, TRACK AND RESULTS

DRIVER	Mark Green	COUNTRY	UK	WEATHER	AIR TEMP	TRACK TEMP	<input checked="" type="checkbox"/> DRY <input type="checkbox"/> INTERMEDIATE <input type="checkbox"/> WET
TRACK	Fiorano	TRACTION	<input type="checkbox"/> LOW <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH	COMMENTS			
RACE	ENS R4	DATE		QUALY POS.	QUALY TIME	STARTING POS.	FINAL POS.

1ST		SPUR GEARS		2ND	
<input type="checkbox"/> 61	<input type="checkbox"/> 62	<input checked="" type="checkbox"/> 63	<input type="checkbox"/> 56	<input checked="" type="checkbox"/> 57	<input type="checkbox"/> 58

1ST		PINION		2ND	
<input type="checkbox"/> 18	<input checked="" type="checkbox"/> 19	<input type="checkbox"/> 20	<input checked="" type="checkbox"/> 23	<input type="checkbox"/> 24	<input type="checkbox"/> 25

FRONT		SHOCK ABSORBERS		REAR	
AE 55	cst	OIL	AE 55	cst	
Grey	SPRINGS		Pink		
mm		REBOUND	mm		
<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>

ANTI-ROLL BARS	
FRONT ANTI-ROLL BAR	REAR ANTI-ROLL BAR
I	III

FRONT TYRES		Controlled Tyre <input checked="" type="checkbox"/>	REAR	
MAKE				
SHORE				
DIAMETER				
5-MIN WEAR				

POWER PACK	
ENGINE	
BRAND	XRD
TYPE	FT Line
GLOWPLUG	7
CARBØ	9 mm
HEAD CLEARANCE	mm
EXHAUST	
PIPE	XRD 2068
MANIFOLD	XRD 5
FUEL	
BRAND	RunnerTime
NITRO	16

CLUTCH	
CLUTCH BELL	<input checked="" type="checkbox"/> ALU <input type="checkbox"/> STEEL
CLUTCH SHOE	<input type="checkbox"/> RED <input checked="" type="checkbox"/> YELLOW <input type="checkbox"/> BLACK
CLUTCH SPRING	X hard
CLUTCH BELL GAP	.7 mm

FLEX CONFIGURATION		
FR WISHBONES INSERTS	RR WISHBONES INSERTS	FLEX
<input type="checkbox"/> PLASTIC <input checked="" type="checkbox"/> CARBON	<input type="checkbox"/> PLASTIC <input checked="" type="checkbox"/> CARBON	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

AERODYNAMIC CONFIGURATION	
BODY BRAND	PF
BODY TYPE	R19
BUMPER INSERTS	<input type="checkbox"/> OPEN <input checked="" type="checkbox"/> CLOSE
AIR TRIM POSITION	9 mm

FRONT		REAR	
AERO DISKS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	SHOCK POSITION	SHOCK POSITION
OFFSET	.50 mm	SHIMS	3 mm
DOWN STOP	1 mm	UPPER ARM INSERT	DOWN STOP
		ROLL CENTER INSERT	8 mm

FRONT CAMBER	R 2°	L 2°	REAR CAMBER	R 2.5°	L 2°
RIDE HEIGHT		8 mm WITH TYRE Ø	RIDE HEIGHT		9 mm WITH TYRE Ø

SHOCK BRACKET	WIDE <input checked="" type="checkbox"/> NARROW	SUSPENSION BRACKET	NARROW <input checked="" type="checkbox"/> WIDE
CASTER	6 mm	WHEEL BASE	0 <input type="checkbox"/> 1 <input checked="" type="checkbox"/> 2
FRONT TOE	+1°	REAR TOE	2.5°
ROLL CENTER SHIMS	FR 0 mm	RR 0 mm	

SHIMS	0 mm	INSERT POSITION		KINGPIN SHIMS	1 mm	ACKERMANN INSERTS	FORWARD
							MID
							REARWARD
WHEEL BASE	<input checked="" type="checkbox"/> 0 <input type="checkbox"/> 1 <input type="checkbox"/> 2 <input type="checkbox"/> 3	TRACKROD POSITION					

TRACK WIDTH	253 mm	TRACK WIDTH	263 mm
TOTAL CAR WEIGHT	grams	WEIGHT POSITION	grams
		WEIGHT POSITION	grams

REMARKS

Alu wheel axles/Alu servo saver/Alu servo arms