

## DRIVER, TRACK AND RESULTS

DRIVER	COUNTRY	UK	WEATHER	AIR TEMP	TRACK TEMP	<input checked="" type="checkbox"/> DRY <input type="checkbox"/> INTERMEDIATE <input type="checkbox"/> WET
TRACK	Cotswold	TRACTION	<input checked="" type="checkbox"/> LOW <input type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH	COMMENTS		
RACE	BRCA	DATE	QUALY POS.	QUALY TIME	STARTING POS.	FINAL POS.

1ST	SPUR GEARS		2ND
<input type="checkbox"/> 61 <input type="checkbox"/> 62 <input checked="" type="checkbox"/> 63	<input checked="" type="checkbox"/> 56	<input type="checkbox"/> 57	<input type="checkbox"/> 58

1ST	PINION		2ND
<input type="checkbox"/> 18 <input checked="" type="checkbox"/> 19 <input type="checkbox"/> 20	<input checked="" type="checkbox"/> 23	<input type="checkbox"/> 24	<input type="checkbox"/> 25

FRONT	SHOCK ABSORBERS		REAR
AE 60	cst	OIL	AE 55
green	SPRINGS		pink
mm		REBOUND	mm
<input type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/>		

ANTI-ROLL BARS	
FRONT ANTI-ROLL BAR	REAR ANTI-ROLL BAR
I	III

FRONT	TYRES	Controlled Tyre	REAR
	MAKE		
	SHORE		
	DIAMETER		
	5-MIN WEAR		

POWER PACK	
ENGINE	
BRAND	XRD
TYPE	FT
GLOWPLUG	7
CARBØ	8.5 mm
HEAD CLEARANCE	.55 mm
EXHAUST	
PIPE	XRD 2068
MANIFOLD	XRD 5
FUEL	
BRAND	RunnerTime
NITRO	16%

CLUTCH	
CLUTCH BELL	<input checked="" type="checkbox"/> ALU <input type="checkbox"/> STEEL
CLUTCH SHOE	<input type="checkbox"/> RED <input checked="" type="checkbox"/> YELLOW <input type="checkbox"/> BLACK
CLUTCH SPRING	X hard
CLUTCH BELL GAP	0.6 mm

FLEX CONFIGURATION		
FR WISHBONES INSERTS	RR WISHBONES INSERTS	FLEX
<input type="checkbox"/> PLASTIC <input checked="" type="checkbox"/> CARBON	<input type="checkbox"/> PLASTIC <input checked="" type="checkbox"/> CARBON	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

AERODYNAMIC CONFIGURATION	
BODY BRAND	ProtoForm
BODY TYPE	R18
BUMPER INSERTS	<input type="checkbox"/> OPEN <input checked="" type="checkbox"/> CLOSE
AIR TRIM POSITION	9 mm

FRONT	REAR
AERO DISKS <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	AERO DISKS <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO
SHOCK POSITION	SHOCK POSITION
OFFSET 0.50 mm	OFFSET 0.25 mm
DOWN STOP 1 mm	DOWN STOP 8 mm
UPPER ARM INSERT	ROLL CENTER INSERT

FRONT CAMBER	REAR CAMBER
R 2°	R 2°
L 2°	L 2.5°
RIDE HEIGHT mm WITH TYRE Ø	RIDE HEIGHT mm WITH TYRE Ø

SHOCK BRACKET	SUSPENSION BRACKET
<input checked="" type="checkbox"/> WIDE <input type="checkbox"/> NARROW	<input checked="" type="checkbox"/> NARROW <input type="checkbox"/> WIDE
CASTER 6 mm	WHEEL BASE 0 <input type="checkbox"/> 1 <input checked="" type="checkbox"/> 2
FRONT TOE -1°	REAR TOE 2.5°
ROLL CENTER SHIMS	
FR 0 mm	RR 0 mm

SHIMS	INSERT POSITION	KINGPIN SHIMS	ACKERMANN INSERTS
0 mm		1 mm	FORWARD
			MID
			REARWARD
WHEEL BASE	<input checked="" type="checkbox"/> 0 <input type="checkbox"/> 1 <input type="checkbox"/> 2 <input type="checkbox"/> 3	TRACKROD POSITION	

TRACK WIDTH	
253 mm	263 mm
TOTAL CAR WEIGHT	grams
WEIGHT POSITION	grams
WEIGHT POSITION	grams

REMARKS

Alu servo saver/Alu wheel axles/