

DRIVER, TRACK AND RESULTS

DRIVER Merlin Depta **COUNTRY** Germany **WEATHER** AIR TEMP 25°C TRACK TEMP 30°C ☒ DRY ☐ INTERMEDIATE ☐ WET
TRACK MC Munster **TRACTION** ☐ LOW ☒ MEDIUM ☐ HIGH **COMMENTS** New track record: 14.071sec
RACE Regionals Rd1 **DATE** 22.04.2018 **QUALY POS.** 2 **QUALY TIME** 21L 5:05.354 **STARTING POS.** 2 **FINAL POS.** 1

1ST		SPUR GEARS		2ND	
<input type="checkbox"/> 61	<input type="checkbox"/> 62	<input checked="" type="checkbox"/> 63	<input type="checkbox"/> 56	<input type="checkbox"/> 57	<input checked="" type="checkbox"/> 58

1ST		PINION		2ND	
<input type="checkbox"/> 18	<input checked="" type="checkbox"/> 19	<input type="checkbox"/> 20	<input checked="" type="checkbox"/> 23	<input type="checkbox"/> 24	<input type="checkbox"/> 25

FRONT		SHOCK ABSORBERS		REAR	
900	cst	OIL	900	cst	
Purple	SPRINGS		Pink		
3	mm	REBOUND	3	mm	
<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>

ANTI-ROLL BARS	
FRONT ANTI-ROLL BAR	2
REAR ANTI-ROLL BAR	3

FRONT TYRES		Controlled Tyre		REAR	
Matrix	MAKE	Matrix			
32	SHORE	35			
68	DIAMETER	75			
2	5-MIN WEAR	2			

POWER PACK	
ENGINE	
BRAND OS Speed	TYPE 2103
GLOWPLUG RP7	CARBØ 8,5 mm HEAD CLEARANCE 0,55 mm
EXHAUST	
PIPE OS 2098	MANIFOLD OS original
FUEL	
BRAND RunnerTime	NITRO 16%

CLUTCH	
CLUTCH BELL <input checked="" type="checkbox"/> ALU <input type="checkbox"/> STEEL	CLUTCH SHOE <input type="checkbox"/> RED <input checked="" type="checkbox"/> YELLOW <input type="checkbox"/> BLACK
CLUTCH SPRING ARC X-hard CLUTCH BELL GAP 0,6 mm	

FLEX CONFIGURATION		
FR WISHBONES INSERTS	RR WISHBONES INSERTS	FLEX
<input type="checkbox"/> PLASTIC <input checked="" type="checkbox"/> CARBON	<input checked="" type="checkbox"/> PLASTIC <input type="checkbox"/> CARBON	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

AERODYNAMIC CONFIGURATION	
BODY BRAND Blitz	BODY POSITION 19 mm
BODY TYPE TS0040	
BUMPER INSERTS <input type="checkbox"/> OPEN <input checked="" type="checkbox"/> CLOSE	
AIR TRIM POSITION 5 mm	

FRONT		REAR	
AERO DISKS <input checked="" type="checkbox"/> YES <input type="checkbox"/> NO	SHOCK POSITION	SHOCK POSITION	CAMBERLINK SHIMS 3 mm
OFFSET 1,2 mm		OFFSET 1,2 mm	AERO DISKS <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO
DOWN STOP +2 mm	UPPER ARM INSERT	DOWN STOP +9 mm	ROLL CENTER INSERT FRONT REAR
FRONT CAMBER R 2,5 L 2		REAR CAMBER R 3,5 L 3	
RIDE HEIGHT 8 mm WITH TYRE Ø 69 mm		RIDE HEIGHT 9 mm WITH TYRE Ø 76 mm	
SHOCK BRACKET WIDE <input type="checkbox"/> NARROW <input checked="" type="checkbox"/>	SUSPENSION BRACKET NARROW <input type="checkbox"/> WIDE <input checked="" type="checkbox"/>		
CASTER 4 mm	WHEEL BASE 0 <input type="checkbox"/> 1 <input checked="" type="checkbox"/> 2		
FRONT TOE -1		REAR TOE 2,5	
ROLL CENTER SHIMS FR 0 mm RR 0 mm			
SHIMS 0 mm	INSERT POSITION	KINGPIN SHIMS 1 mm	ACKERMANN INSERTS FORWARD MID REARWARD
WHEEL BASE 0 <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2 <input type="checkbox"/> 3	TRACKROD POSITION		
TRACK WIDTH 251 mm		TRACK WIDTH 264 mm	
TOTAL CAR WEIGHT 2410 grams	WEIGHT POSITION no grams	WEIGHT POSITION no grams	

REMARKS

Bumper inserts top open