

DRIVER, TRACK AND RESULTS

DRIVER	PEUZIAT	COUNTRY	France	WEATHER	AIR TEMP	18	TRACK TEMP	<input checked="" type="checkbox"/> DRY <input type="checkbox"/> INTERMEDIATE <input type="checkbox"/> WET
RACE	AMRT	DATE	16/02/20	QUALY POS.	1	STARTING POS.	1	FINAL POS.
FASTEST LAP	13,2							
TRACK TYPE <input type="checkbox"/> INDOOR <input type="checkbox"/> OUTDOOR STYLE <input type="checkbox"/> TIGHT <input type="checkbox"/> MEDIUM <input type="checkbox"/> OPEN <input type="checkbox"/>								
SURFACE GRIP <input type="checkbox"/> LOW <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH <input type="checkbox"/> CONDITION <input checked="" type="checkbox"/> SMOOTH <input type="checkbox"/> ROUGH <input type="checkbox"/>								
TYPE <input type="checkbox"/> HARD PACKED <input type="checkbox"/> CLAY <input checked="" type="checkbox"/> CARPET <input type="checkbox"/> MULTI/SURFACE <input type="checkbox"/> GRASS <input type="checkbox"/> BLUE GROOVE <input type="checkbox"/> DIRT <input type="checkbox"/> ASTRO-TURF <input type="checkbox"/>								

FRONT SHOCK ABSORBERS		REAR	
500	cst OIL	450	cst
Green	SPRINGS	Blue	
0	mm REBOUND	0	mm
2	mm LIMITERS	2	mm
N° HOLES 2	Ø 1,6 mm PISTONS	N° HOLES 2	Ø 1,8 mm
PISTONS TYPE <input type="checkbox"/> STOCK <input type="checkbox"/> CONICAL <input checked="" type="checkbox"/> SQUARE			
<input type="checkbox"/> SHORT <input checked="" type="checkbox"/> LONG SPRING BUCKETS		<input checked="" type="checkbox"/> SHORT <input type="checkbox"/> LONG	
<input type="checkbox"/> BLADDER	SEAL TYPE	<input type="checkbox"/> BLADDER	<input checked="" type="checkbox"/> EMULSION
<input type="checkbox"/> EMULSION		<input checked="" type="checkbox"/> EMULSION	

FRONT ANTI-ROLL BARS		REAR	
FRONT ANTI-ROLL BAR	1,2 mm	REAR ANTI-ROLL BAR	1,2 mm

REAR DIFFERENTIAL	
<input type="checkbox"/> BALL DIFFERENTIAL	
<input type="checkbox"/> GEAR DIFF	30000 cst
DIFF HEIGHT	3

GEARING	
PINION	21 Teeth
SPUR GEAR	std Teeth

ELECTRONICS	
BATTERY	
BRAND	Orion
CAPACITY	4000 mAh
MOTOR	
BRAND	Reds
TYPE	6,5
TIMING	
ESC	
BRAND	Reds
TYPE	160A

AERODYNAMIC CONFIGURATION	
BODY BRAND	Serpent
TYPE	
REAR WING BRAND	Serpent
TYPE	
REAR WING WIDTH	REAR WING LIP mm
RR WING ANGLE	<input checked="" type="checkbox"/> 0° <input type="checkbox"/> 2° <input type="checkbox"/> 4° <input type="checkbox"/> 6° <input type="checkbox"/> 8° MOUNT <input type="checkbox"/> STD <input checked="" type="checkbox"/> LOW
FRONT WING	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO TYPE

FRONT TIRES		Controlled Tire		REAR	
	MAKE				
Cut stagger	TYPE	Cactus			
no	COMPOUND	Cragg			
	INSERTS				
Serpent	WHEELS	Serpent			
No	ADDITIVE	No			

FRONT		REAR	
CASTER BLOCK INSERTS <input checked="" type="checkbox"/> + <input type="checkbox"/> - <input type="checkbox"/> 0 <input type="checkbox"/> 2.5 <input checked="" type="checkbox"/> 5		SHOCK POSITION <input type="checkbox"/> REAR <input checked="" type="checkbox"/> FRONT	
SHIMS 2 mm 1 mm 2 mm 4 mm 5 mm		SHIMS 2 mm 4 mm 5 mm	
SPINDLE SHIMS 1 mm AXLE SPACER <input checked="" type="checkbox"/> YES <input type="checkbox"/> NO		SHOCK POSITION 1 2 3 3 2 1 1 2 3 3 2 1	
FRONT CAMBER R 2 ° L 2 °		REAR CAMBER R 2 ° L 2 °	
RIDE HEIGHT 15 mm		RIDE HEIGHT 15 mm	
FRONT BULKHEAD <input type="checkbox"/> STOCK <input type="checkbox"/> ALU <input checked="" type="checkbox"/> BRASS		FRONT CASTER BLOCK <input checked="" type="checkbox"/> STOCK <input type="checkbox"/> ALU STEERING SREW <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	
FRONT ARM <input checked="" type="checkbox"/> STRAIGHT ARM <input type="checkbox"/> GULL ARM		REAR WHEEL BASE <input type="checkbox"/> LONG <input checked="" type="checkbox"/> SHORT	
TRANSMISSION <input checked="" type="checkbox"/> 3 GEAR GEN 3 <input type="checkbox"/> 3 STAND UP <input type="checkbox"/> 4 STAND UP <input type="checkbox"/> 3 GEAR LD <input type="checkbox"/> 4 GEAR LD		REAR HUB <input type="checkbox"/> SHORT OFFSET HUB <input type="checkbox"/> LONG OFFSET HUB	
BUMP STEER <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO		REAR UPRIGHT INSERT AXLE HEIGHT <input type="checkbox"/> 0 <input type="checkbox"/> 0.5 <input type="checkbox"/> 1 <input type="checkbox"/> 1.5 <input type="checkbox"/> 2 <input type="checkbox"/> 2.5 <input checked="" type="checkbox"/> 3 INSERT OFFSET <input type="checkbox"/> -1 <input checked="" type="checkbox"/> 0	
ACKERMANN <input type="checkbox"/> OPT.0 <input checked="" type="checkbox"/> OPT.1 <input type="checkbox"/> OPT.2 <input type="checkbox"/> OPT.3 SHIMS 2 mm		REAR FRONT TOE BLOCK WIDTH	
REAR AXLE <input type="checkbox"/> LONG SHAFT <input type="checkbox"/> SHORT SHAFT		REAR REAR TOE BLOCK WIDTH	
DRIVETRAIN SHIMS <input type="checkbox"/> LONG SHAFT <input type="checkbox"/> SHORT SHAFT		SLIPPER <input checked="" type="checkbox"/> STOCK PLATES <input type="checkbox"/> VENTED PLATES DISTANCE 2 mm	
FRONT TOE 1 °		REAR TOE -2 °	
WEIGHT DISTRIBUTION CAR WEIGHT grams WEIGHT BIAS FR % RR % BATTERY LOCATION 10 mm			

REMARKS