

DRIVER, TRACK AND RESULTS

DRIVER **JEFF HAMON** COUNTRY **AUSTRALIA** WEATHER AIR TEMP TRACK TEMP DRY INTERMEDIATE WET

TRACK **QRCCRA** TRACTION LOW MEDIUM HIGH COMMENTS

RACE **PRACTICE** DATE **3/6/2020** QUALY POS. QUALY TIME STARTING POS. FINAL POS.

1ST		SPUR GEARS		2ND	
<input type="checkbox"/> 61	<input type="checkbox"/> 62	<input checked="" type="checkbox"/> 63	<input type="checkbox"/> 56	<input checked="" type="checkbox"/> 57	<input type="checkbox"/> 58

1ST		PINION		2ND	
<input type="checkbox"/> 18	<input checked="" type="checkbox"/> 19	<input type="checkbox"/> 20	<input checked="" type="checkbox"/> 23	<input type="checkbox"/> 24	<input type="checkbox"/> 25

FRONT		SHOCK ABSORBERS		REAR	
OIL AM 600 cst		OIL AM 600 cst		OIL AM 600 cst	
SPRINGS PINK		SPRINGS PINK		SPRINGS PINK	
<input checked="" type="checkbox"/> <input type="checkbox"/>		<input type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/>		<input type="checkbox"/>	

FRONT		HEAVE DAMPER		REAR	
OIL _____ cst		OIL _____ cst		OIL _____ cst	
SPRINGS _____		SPRINGS _____		SPRINGS _____	
<input type="checkbox"/>		<input type="checkbox"/>		<input type="checkbox"/>	

FRONT		ANTI-ROLL BARS		REAR	
ANTI-ROLL BAR 2 DOT		ANTI-ROLL BAR 3 DOT		ANTI-ROLL BAR 3 DOT	







FRONT		TYRES		Controlled Tyre		REAR	
HOT RACE		MAKE HOT RACE		<input type="checkbox"/>		HOT RACE	
32		SHORE 35		<input type="checkbox"/>		35	
67		DIAMETER 74		<input type="checkbox"/>		74	
5-MIN WEAR _____		5-MIN WEAR _____		<input type="checkbox"/>		5-MIN WEAR _____	

POWER PACK			
ENGINE			
BRAND MAX POWER	TYPE CALIFORNIA	GLOWPLUG RP7 CARB Ø 9mm HEAD CLEARANCE 0.55mm	
EXHAUST			
PIPE 2093	MANIFOLD 2299	FUEL	
BRAND VP RACIN	NITRO 25	CLUTCH	

CLUTCH			
CLUTCH BELL <input checked="" type="checkbox"/> ALU <input type="checkbox"/> STEEL	CLUTCH SHOE <input type="checkbox"/> RED <input checked="" type="checkbox"/> YELLOW <input type="checkbox"/> BLACK	CLUTCH SPRING CAP @ .50 CLUTCH BELL GAP .60 mm	

FLEX CONFIGURATION			
FR WISHBONES & INSERTS		RADIO PLATE THICKNESS	
<input type="checkbox"/> OPEN <input checked="" type="checkbox"/> CLOSED	<input type="checkbox"/> PLASTIC <input checked="" type="checkbox"/> CARBON	<input type="checkbox"/> STD (2mm) <input checked="" type="checkbox"/> OPT (2.5mm)	
RR WISHBONES INSERTS		RADIO PLATE STIFFENER	
<input checked="" type="checkbox"/> PLASTIC <input type="checkbox"/> CARBON		<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	

AERODYNAMIC CONFIGURATION		
BODY BRAND PROTOFORM	BUMPER TYPE <input type="checkbox"/> 989 <input checked="" type="checkbox"/> 977	BODY POSITION 80 mm
BODY TYPE R19		
AIR TRIM POSITION 11 mm		



REMARKS **BODY MEASURED FROM CUT OUT ON CHASSIS**