

DRIVER, TRACK AND RESULTS

DRIVER	Mark Green	COUNTRY	UK	WEATHER	AIR TEMP	TRACK TEMP	<input checked="" type="checkbox"/> DRY <input type="checkbox"/> INTERMEDIATE <input type="checkbox"/> WET
TRACK	Halifax	TRACTION	<input type="checkbox"/> LOW <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH	COMMENTS			
RACE	BRCA	DATE	27-8-2023	QUALY POS.	1	QUALY TIME	STARTING POS. 1 FINAL POS. 1

FRONT SHOCK ABSORBERS		REAR	
OIL	900 cst	OIL	900 cst
SPRINGS	Blue	SPRINGS	Pink fr
<input type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>		<input type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	

FRONT HEAVE DAMPER		REAR	
OIL	cst	OIL	cst
SPRINGS		SPRINGS	
<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>		<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	

ANTI-ROLL BARS	
FRONT ANTI-ROLL BAR	2
REAR ANTI-ROLL BAR	3

FRONT TYRES		REAR	
Controlled Tyre	<input type="checkbox"/>	Controlled Tyre	<input type="checkbox"/>
MAKE	Contact	MAKE	Contact
SHORE	32	SHORE	35
DIAMETER	68	DIAMETER	75
5-MIN WEAR			

ELECTRONICS	
BATTERY	<input checked="" type="checkbox"/> 4S <input type="checkbox"/> 6S
BRAND	IP
CAPACITY	10000 mAh
MOTOR	
BRAND	HW
TYPE	2800
TIMING	
ESC	
BRAND	HW
TYPE	HW

RATIO CONFIGURATION	
SPUR GEAR	46 teeth
PINION	20 teeth
FINAL DRIVE RATIO	
ROLL OUT	mm

FLEX CONFIGURATION	
FRONT RADIO PLATE FLEX	REAR CHASSIS PLATE FLEX
<input checked="" type="checkbox"/> STIFF (3 SCREWS)	<input checked="" type="checkbox"/> STIFF
<input type="checkbox"/> MID (2 SCREWS)	<input type="checkbox"/> FLEX
<input type="checkbox"/> FLEX (NO SCREWS)	

AERODYNAMIC CONFIGURATION	
BODY BRAND	Blitz
BUMPER TYPE	<input type="checkbox"/> 989 <input checked="" type="checkbox"/> 977
BODY POSITION	mm
BODY TYPE	Spider
AIR TRIM POS.	5 mm

FRONT		REAR	
UPPER ARM INSERT	SHOCK POSITION	SHOCK POSITION	CAMBERLINK POSITION
OFFSET Max mm			OFFSET 1 mm
DOWN STOP +1 mm			DOWN STOP +7 mm
SHOCK BRACKET <input checked="" type="checkbox"/> WIDE <input type="checkbox"/> NARROW	SUSPENSION BRACKET <input checked="" type="checkbox"/> NARROW <input type="checkbox"/> WIDE	ROLL CENTER INSERT FRONT <input type="checkbox"/> REAR <input type="checkbox"/>	

FRONT CAMBER		REAR CAMBER	
R -2°	L -2°	R -2.5°	L -3°
RIDE HEIGHT 10 mm WITH TYRE Ø hudy mm		RIDE HEIGHT 11 mm WITH TYRE Ø hudy mm	

FRONT TOE		REAR TOE	
-1°		1.5°	
ROLL CENTER SHIMS FR 0.5 mm RR 0.5 mm			

STEERING BLOCK INSERT		UPPER LINK HEIGHT		REAR REACTIVE STEERING SYSTEM	
<input type="checkbox"/> TRAILING <input type="checkbox"/> UP <input checked="" type="checkbox"/> DOWN <input type="checkbox"/> LEADING					
SHIMS 2 mm					
WHEEL BASE 0 <input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2 <input type="checkbox"/> 3					

ACKERMANN	
ACKERMANN INSERTS	STEERING BLOCK LEVERS <input type="checkbox"/> OPT. 1 <input checked="" type="checkbox"/> OPT. 2
LEFT BATTERY POSITION <input checked="" type="checkbox"/> FRONT <input type="checkbox"/> REAR	RIGHT BATTERY POSITION <input type="checkbox"/> FRONT <input type="checkbox"/> MID <input checked="" type="checkbox"/> REAR
TRACK WIDTH 251 mm	TRACK WIDTH 261 mm
TOTAL CAR WEIGHT grams	

REMARKS

Options used: 903760 Solidaxle light S989 - 903806 Oneway diff fr S9XX - 903857 Shockmount set FR flex S990