

## DRIVER, TRACK AND RESULTS

DRIVER **Paloschi Gabriele** COUNTRY **Italy** WEATHER AIR TEMP **25°** TRACK TEMP ☒ DRY ☐ INTERMEDIATE ☐ WET

TRACK **Asd Naxos world** TRACTION ☐ LOW ☐ MEDIUM ☒ HIGH COMMENTS

RACE **Ita. championship RD#** DATE **5/05/2024** QUALY POS. **2** QUALY TIME **15.0** STARTING POS. **2** FINAL POS. **3**

FRONT SHOCK ABSORBERS		REAR	
800 cst	OIL	800 cst	
HARD (39.5)	SPRINGS	X-HARD (42)	
mm	REBOUND	mm	
N° HOLES 6Ø 1.2mm	PISTONS	N° HOLES 6Ø 1.2mm	
<input checked="" type="checkbox"/> FLAT <input type="checkbox"/> CONICAL	PISTON TYPE	<input checked="" type="checkbox"/> FLAT <input type="checkbox"/> CONICAL	

ANTI-ROLL BARS	
FR ANTI-ROLL BAR 2.4mm	RR ANTI-ROLL BAR 2.7mm

DIFFERENTIAL OIL AND POSITION	
FR DIFF 500Kcst	RR DIFF 60Kcst
POSITION <input checked="" type="checkbox"/> LOW <input type="checkbox"/> MID LOW <input type="checkbox"/> HIGH <input type="checkbox"/> MID HIGH	POSITION <input type="checkbox"/> LOW <input type="checkbox"/> MID LOW <input checked="" type="checkbox"/> HIGH <input type="checkbox"/> MID HIGH

1ST PINION AND SPUR GEAR		2ND	
<input type="checkbox"/> 18 <input type="checkbox"/> 19 <input type="checkbox"/> 20	PINION	<input type="checkbox"/> 23 <input type="checkbox"/> 24 <input type="checkbox"/> 25	
<input type="checkbox"/> 61 <input checked="" type="checkbox"/> 62 <input type="checkbox"/> 63	SPUR GEAR	<input type="checkbox"/> 56 <input type="checkbox"/> 57 <input checked="" type="checkbox"/> 58	

CLUTCH	
CLUTCH BELL <input type="checkbox"/> STEEL <input checked="" type="checkbox"/> ALU <input type="checkbox"/> STANDARD <input checked="" type="checkbox"/> VENTED	
<input checked="" type="checkbox"/> ADJUSTABLE CLUTCH CLUTCH SHOES 2 BLACK/2 YELLOW	
CLUTCH SPRING BM CLUTCH CLUTCH PRELOAD 0.8mm	
<input type="checkbox"/> 4 PIN CLUTCH FLYWHEEL <input type="checkbox"/> STEEL <input type="checkbox"/> ALU	
CLUTCH SHOES	CLUTCH SPRINGS
SHOE TYPE x with SPRINGS TYPE mm	
SHOE TYPE x with SPRINGS TYPE mm	

ENGINE, PIPE AND FUEL	
ENGINE BRAND GIMAR	TYPE VENUS
HEADSHIMS mm	GLOWPLUG CARB Ø mm
EXHAUST PIPE GIMAR 2190	MANIFOLD GIMAR 2190
FUEL BRAND ENERGY	NITRO GT%

FLEX CONFIGURATION	
ENGINE MOUNT <input checked="" type="checkbox"/> STANDARD <input type="checkbox"/> MONOBLOCK	
FRONT TIRES Controlled Tire <input type="checkbox"/> REAR	
SM TYRES MAKE SM TYRES	
Y1 TYPE Y1	
INSERTS	
WHEELS	

AERODYNAMIC CONFIGURATION	
BODY BRAND & TYPE BLITZ GT6	BODY POSITION STANDARD mm
WING BRAND & TYPE BLITZ GT6	
REAR DIFFUSER <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	

FRONT		REAR	
WHEEL HEX 1 mm	SHOCK POSITION	SHOCK POSITION	WHEEL HEX 1 mm
CAMBERLINK POSITION		CAMBERLINK POSITION	
DOWN STOP 3 mm		DOWN STOP 2 mm	
FRONT CAMBER L 3° R 4°		REAR CAMBER L 4° R 5°	
RIDE HEIGHT 7 mm WITH TYRE Ø 98 mm		RIDE HEIGHT 8 mm WITH TYRE Ø 98 mm	
FRONT ARM SKIN <input type="checkbox"/> TOP <input type="checkbox"/> NYLON <input type="checkbox"/> CARBON <input type="checkbox"/> BOTTOM <input type="checkbox"/> NYLON <input type="checkbox"/> CARBON		REAR ARM SKIN <input type="checkbox"/> TOP <input type="checkbox"/> NYLON <input type="checkbox"/> CARBON <input type="checkbox"/> BOTTOM <input type="checkbox"/> NYLON <input type="checkbox"/> CARBON	
FRONT TOE 2°		REAR TOE 2°	
STEERING BLOCK ACKERMAN PLATE OPTION TYPE stock		REAR UPRIGHT ROLL CENTER INSERTS	
CASTER INSERT <input type="checkbox"/> 0° <input type="checkbox"/> 1° <input type="checkbox"/> 2° <input checked="" type="checkbox"/> 3°	SERVO SAVER SPRING <input checked="" type="checkbox"/> STD <input type="checkbox"/> HARD	REAR BRACE <input checked="" type="checkbox"/> STOCK <input type="checkbox"/> ALU	WHEEL BASE <input type="checkbox"/> 0 <input checked="" type="checkbox"/> 1.25 <input type="checkbox"/> 2.5 <input type="checkbox"/> 3.75 <input type="checkbox"/> 5
FRONT BRACE <input checked="" type="checkbox"/> STOCK <input type="checkbox"/> ALU			
SUSPENSION BRACKETS INSERTS			
FRONT FR INSERTS N° 10		REAR FR INSERTS N° 1.5	
FRONT RR INSERTS N° 1		REAR RR INSERTS N° 2	

## REMARKS

Pinions:  
 903876 Centax gear-pinion steel 17T XLI  
 903877 Centax gear-pinion steel 22T XLI  
 Ride height measured with new tyres