

# SETUP SHEET

VIPER  
990  
EVO

SERPENT

## DRIVER & TRACK

DRIVER M Green DATE   
TRACK Halifax GRIP Low

## FR SHOCK ABSORBERS RR

OIL 575 cst OIL kit 1000 cst  
SPRINGS Long Pink SPRINGS short pin  
PISTON 1 PISTON 3

## FR HEAVE DAMPER RR

OIL cst OIL cst  
SPRINGS SPRINGS  
PISTON PISTON

## ANTI-ROLL BARS

FRONT I REAR III

## FR TYRES Controlled Tyre RR

MAKE & TYPE Contact  
SHORE  
mm DIAMETER mm

## ELECTRONICS

BATTERY ☒ 4S ☐ 6S  
BRAND  
CAPACITY mAh  
MOTOR  
BRAND  
TYPE TIMMING  
ESC  
BRAND TYPE

## RATIO CONFIGURATION

SPUR GEAR 46 teeth PINION 20 teeth  
FINAL DRIVE RATIO  
ROLL OUT

## AERODYNAMIC CONFIGURATION

BODY BRAND Blitz BODY POSITION mm  
BODY TYPE Speed  
BUMPER TYPE 989 lite  
AIR TRIM POS. 2 mm

## REMARKS

front brace ball joint.  
Front spring on rear/ rear spring on front

## REAR SETUP

REAR BODYMOUNT POSITION SHOCK SHIMS 0 mm CAMBERLINK POSITION ROLL CENTER INSERT FRONT REAR  
☒ STANDARD ☐ CARBON  
REAR CAMBER R 3° L 3.2°  
RIDE HEIGHT 10 mm WITH TYRE Ø Hudy mm  
DOWN STOP 6 mm  
RR TRACK WIDTH 261 mm  
UPPER LINK HEIGHT UPRIGHT INSERT ☒ MID ☐ LOW  
REAR REACTIVE STEERING SYSTEM REAR TOE 3°  
WHEEL BASE ☐ 0 ☐ 1 ☒ 2 ☐ 3

## FRONT SETUP

SHOCK SHIMS 0 mm ROLL CENTER SHIMS FR 0 mm RR 0 mm UPPER ARM INSERT OFFSET SHIMS 0.5 mm  
FRONT CAMBER R 2.5° L 2.5°  
RIDE HEIGHT 8 mm WITH TYRE Ø Hudy mm  
DOWN STOP 0 mm  
FR TRACK WIDTH 251 mm  
SUSPENSION BRACKET NARROW WIDE ☒ WIDE ☐ NARROW  
SHOCK BRACKET  
STEERING BLOCK INSERT ACKERMANN  
ACKERMANN INSERTS  
FRONT TOE 0.5° CASTER 6 mm  
SHIMS 1 mm  
STEERING BLOCK LEVERS ☐ OPT. 1 ☒ OPT. 2  
WHEEL BASE ☐ 0 ☐ 1 ☒ 2 ☐ 3 ☐ 4

## FLEX SETUP & WEIGHT DISTRIBUTION

☒ STIFF (3 SCREWS) ☐ MID (2 SCREWS) ☐ FLEX (NO SCREWS)  
FR RADIO PLATE FLEX  
RIGHT BATTERY POSITION ☐ FRONT ☐ MID ☒ REAR  
VERTICAL TOPDECK ☐ YES ☐ NO  
FRONT WEIGHT grams mm  
SHOCKMOUNT BRACE ☒ YES ☐ NO  
REAR FLEX ☒ STIFF ☐ FLEX  
SHOCKMOUNT BRACE ☒ YES ☐ NO  
TOTAL CAR WEIGHT grams  
RIGHT BATTERY POSITION ☐ FRONT ☒ REAR